

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore L-8
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	800 lbs. @ 5 ft
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	The boom can be set at four positions between horizontal and 75 degrees. It will store vertically reducing space requirements when not in use.
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A

Boom stowed height from mounting surface	N/A
Crane mounting space requirement	N/A
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	360 degree rotation without restriction is standard.
Rotation system brake	manual band brake
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered 12.5 Ft. remote pendant
Control valve type	Tethered 12.5 Ft. remote pendant
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	Moment Rating is 4,500 Ft.-Lbs. with maximum lift capacity of 800 Lbs.
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 3,009.00

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore L-21
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	2,000 lbs. @ 3ft
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	telescopes manually from 3 Ft. to 5 Ft.
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A
	Boom stowed height from mounting surface	N/A

Crane mounting space requirement	N/A
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	360 degree rotation without restriction is standard.
Rotation system brake	manual brake band
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered 12.5 Ft. remote pendant
Control valve type	N/A
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	Moment Rating is 6,000 Ft.-Lbs.
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 3,526.00

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore 206EL
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	2,000 lbs. @ 3 ft
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	boom length in the horizontal position is 5.5 Ft.
	First Extension	manually telescoping section to 9.0 Ft.
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A
	Boom stowed height from mounting surface	N/A

Crane mounting space requirement	12 In. square with a 9.5 In. square bolt pattern.
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	N/A
Rotation system brake	N/A
Rotation system Drive	high torque, low speed hydraulic motor
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered 18 Ft. remote pendant
Control valve type	N/A
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	6,500 ft.-lb. Moment Rating with capacities as follows: *2000 Lbs. at 3 Ft. *1300 Lbs. at 5 Ft. *1083 Lbs. at 6 Ft. 929 Lbs. at 7 Ft. 722 Lbs. at 9 Ft.
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 5,604.00

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore 2000A
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation	2000 Lbs. at 3 Ft. 1500 Lbs. at 4 Ft. 1200 Lbs. at 5 Ft. 1000 Lbs. at 6 Ft. 660 Lbs. at 9 Ft.
	state distance & lift capacity	
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	manually extendable from 5 Ft. 6 In. to 9 Ft.
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A

Boom stowed height from mounting surface	N/A
Crane mounting space requirement	N/A
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	N/A
Rotation system brake	manual brake band
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered 12.5 Ft. remote pendant
Control valve type	N/A
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	Moment Rating is 6,000 Ft.-Lbs. with capacities as follows: 2000 Lbs. at 3 Ft. 1500 Lbs. at 4 Ft. 1200 Lbs. at 5 Ft. 1000 Lbs. at 6 Ft. 660 Lbs. at 9 Ft
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 4,649.00

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore 5000WX-20
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	5,000 lbs. @ 5 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	extends under power from 10 Ft. to 16 Ft
	First Extension	manually from 16 Ft. to 20 Ft.
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A
	Boom stowed height from mounting surface	N/A

Crane mounting space requirement	N/A
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	continuous and unlimited rotation.
Rotation system brake	N/A
Rotation system Drive	worm gearbox
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered 25-Ft. long remote pendant
Control valve type	N/A
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	5000 lbs. @ 5 ft. * 1785 lbs. @ 14 ft. 3125 lbs. @ 8 ft. * 1562 lbs. @ 16 ft. 2500 lbs. @ 10 ft. 1388 lbs. @ 18 ft. 2083 lbs. @ 12 ft. 1250 lbs. @ 20 ft.
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 17,646.00

Price quote for: **Crane Installed on Cab & Chassis**

Vendor Name:	Crysteel Truck Equipment
Contact Person:	Jim Wyatt
Street Address:	1130 - 73rd Avenue NE
P.O. Box:	
City, State, Zip	Fridley, MN 55432
Phone #:	763-571-1902
Toll Free #:	1-800-795-1280
Fax #:	763-571-5091
Email Address:	jwyatt@crysteeltruck.com

Spec #	Information Requested	Answer
1.0	MAKE AND MODEL	Liftmoore 6036WX-20
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	6,000 Lbs. at 6 Ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Powered Extension from 10 Ft. 4 In. to 16 Ft. 4 In.
	First Extension	Manual Pullout Section of 3 Ft. 8 In.
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	N/A
	Total vertical reach	N/A
	Horizontal hook approach from centerline of rotation	N/A
	Vertical hook approach from mounting surface	N/A
	Total horizontal reach	N/A
	Below chassis frame reach	N/A
	Boom stowed height from mounting surface	N/A

Crane mounting space requirement	N/A
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Power rotation is unlimited.
Rotation system brake	N/A
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
control locations & Description	Tethered A 25 Ft. remote pendant control
Control valve type	N/A
Wireless remote included	N/A
Number of wireless remote functions	N/A
Boom Cylinder description	N/A
Crane rating	36,000 ft.-lbs. moment rating
Country of origin for crane	USA

Warranty

Liftmoore, Inc. warrants each LIFTMOORE crane to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Under the terms of this warranty the crane structural components manufactured by LIFTMOORE, Inc. are warranted for thirty-six (36) months from the date of delivery to the original customer. LIFTMOORE, Inc. will repair or replace, as its sole discretion, any equipment or part that is returned f.o.b. to LIFTMOORE, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by LIFTMOORE, Inc. or its authorized dealer to have been defective at the time of original delivery.

BASE UNIT PRICE: 18,489

VENDOR:

Liftmoore

MAKE/MODEL

Liftmoore L21S

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 3,526.00
2.0	CRANE EXTENSION OPTIONS NA			
3.0	OUTRIGGER OPTIONS NA			
4.0	REMOTE CONTROLS NA			
5.0	ATTACHMENTS NA			
6.0	OTHER OPTIONS			
6.1	L21S-Same as L-21 except pedestal is eliminated & base plate added for mounting on service body compartment top.			\$ (30.00)
7.0	CUSTOM WORK NA			
8.0	EXTENDED WARRANTY OPTIONS NA			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES - (See Special Terms and Conditions)		0.00% % Discount	
	Price List Date and Number		2330, September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			
11.0	HOURLY SHOP RATE			\$ 69.00
	See Special Terms and Conditions			
11.1	EQUIPMENT INSPECTION AND REPAIR			\$ -
11.2	HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC			\$ -
11.3	HOURLY RATE FOR MECHANICAL REPAIRS			\$ -
Total Cost:				\$ 3,565.00

VENDOR: Liftmoore

MAKE/MODEL Liftmoore L21-7 ATB

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 3,526.00
2.0	CRANE EXTENSION OPTIONS NA			
3.0	OUTRIGGER OPTIONS NA			
4.0	REMOTE CONTROLS NA			
5.0	ATTACHMENTS NA			
6.0	OTHER OPTIONS			
6.1	Includes Anti-Two Block			\$ 562.00
7.0	CUSTOM WORK NA			
8.0	EXTENDED WARRANTY OPTIONS NA			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES		0.00% % Discount	
	Price List Date and Number		2330,September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			\$ 2.95
11.0	HOURLY SHOP RATE		6900.00%	
11.1	EQUIPMENT INSPECTION AND REPAIR			\$ -
11.2	HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC			\$ -
11.3	HOURLY RATE FOR MECHANICAL REPAIRS			\$ -

Total Cost: \$ 4,090.95

VENDOR:

Liftmoore

MAKE/MODEL

Liftmoore 206RELWS ATB

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 5,604.00
2.0	CRANE EXTENSION OPTIONS NA			
3.0	OUTRIGGER OPTIONS NA			
4.0	REMOTE CONTROLS NA			
5.0	ATTACHMENTS NA			
6.0	OTHER OPTIONS			
6.1	Same as 206ELW except pedestal is eliminated and base plate added for mounting on service body compartment top			\$ 796.00
7.0	CUSTOM WORK NA			
8.0	EXTENDED WARRANTY OPTIONS NA			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES - (See Special Terms and Conditions)		0.00% % Discount	
	Price List Date and Number		2330, September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			\$ -
11.0	HOURLY SHOP RATE			\$ 69.00
11.1	EQUIPMENT INSPECTION AND REPAIR			\$ -
11.2	HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC			\$ -
11.3	HOURLY RATE FOR MECHANICAL REPAIRS			\$ -
Total Cost:				\$ 6,469.00

VENDOR:

Liftmoore

MAKE/MODEL

Liftmoore 206REL ATB

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 5,604.00
2.0	CRANE EXTENSION OPTIONS <u>NA</u>			
3.0	OUTRIGGER OPTIONS <u>NA</u>			
4.0	REMOTE CONTROLS <u>NA</u>			
5.0	ATTACHMENTS <u>NA</u>			
6.0	OTHER OPTIONS			
6.1	Same as 206ELW except pedestal is eliminated and base plate added for mounting on service body compartment top			\$ 824.00
7.0	CUSTOM WORK <u>NA</u>			
8.0	EXTENDED WARRANTY OPTIONS <u>NA</u>			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES - (See Special Terms and Conditions)		0.00% % Discount	
	Price List Date and Number		2330, September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			\$ -
11.0	HOURLY SHOP RATE			\$ 69.00
11.1	EQUIPMENT INSPECTION AND REPAIR			\$ -
11.2	HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC			\$ -
11.3	HOURLY RATE FOR MECHANICAL REPAIRS			\$ -
Total Cost:				\$ 6,497.00

VENDOR: Liftmoore

MAKE/MODEL Liftmoore 206REL W ATB

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 5,604.00
2.0	CRANE EXTENSION OPTIONS NA			
3.0	OUTRIGGER OPTIONS NA			
4.0	REMOTE CONTROLS NA			
5.0	ATTACHMENTS NA			
6.0	OTHER OPTIONS			
6.1	Lower Pedestal Height of 22.75" Larger 2.7 HP, 2,000 lbs. single line capacity winch 62 Ft. of 1/4" wire rope w/swivel hook			\$ 786.00
7.0	CUSTOM WORK NA			
8.0	EXTENDED WARRANTY OPTIONS NA			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES - (See Special Terms and Conditions)		0.00% % Discount	
	Price List Date and Number		2330, September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			\$ -
11.0	HOURLY SHOP RATE			\$ 69.00
11.1	EQUIPMENT INSPECTION AND REPAIR			\$ -
11.2	HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC			\$ -
11.3	HOURLY RATE FOR MECHANICAL REPAIRS			\$ -
	Total Cost:			\$ 6,459.00

VENDOR: Liftmoore
Fridley, mn 55432
 MAKE/MODEL Liftmoore 5000WX-20

Spec #	Description	Qty	Price	Subtotal
1.0	BASE UNIT PRICE:			\$ 17,646.00
2.0	CRANE EXTENSION OPTIONS			
2.1	Full Power Extension from 12 Ft. to 20 Ft.			\$ 812.00
3.0	OUTRIGGER OPTIONS NA			
4.0	REMOTE CONTROLS NA			
5.0	ATTACHMENTS NA			
6.0	OTHER OPTIONS NA			
7.0	CUSTOM WORK NA			
8.0	EXTENDED WARRANTY OPTIONS NA			
9.0	DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES - (See Special Terms and Conditions)		0.00% % Discount	
	Price List Date and Number		2330, September 26, 2015	
10.0	DELIVERY CHARGES			
	DELIVERY STARTING POINT - City, State, Zip			
	Fridley, mn 55432			
	Price per loaded mile			\$ -
11.0	HOURLY SHOP RATE NA			\$ -
	Total Cost:			\$ 18,458.00