

MINNESOTA
PRICING SCHEDULE
(Typed responses required)

| | |
|------------------|----------------------------------|
| Vendor Name: | Deere & Company |
| Contact Person: | Tamara Hebert |
| Street Address: | 2000 John Deere Run |
| P.O. Box: | |
| City, State, Zip | Cary, NC 27513 |
| Phone #: | 800-358-5010, option 2 |
| Toll Free #: | 800-358-5010, option 2 |
| Fax #: | 309-749-2313 |
| Email Address: | GovContractSupport@JohnDeere.com |

| SPEC # | REQUESTED INFORMATION | ANSWER |
|--------|---|--|
| 1.0 | TRACTOR CATALOG SECTION PRICE PRICE LIST TITLE: | FR_Snow_20151109.pdf |
| | DATE AND ID# OF PRICE LIST: | FR_Snow_20151109 |
| | PERCENTAGE DISCOUNT TO BE APPLIED TO PRICE LIST: | 17% |
| 1.1 | Price for manuals, (service, parts, repair, and operations) | N/A |
| 1.2 | Price for set of fluid and air filters | N/A |
| 2.0 | <u>PERFORMANCE/EXTENDED WARRANTY OPTIONS</u> Offer performance/warranty options. Numbers starting with 2.1, 2.2, etc. (Specify years, miles or hours extended term covers.) | |
| 2.1 | _____ | No Bid |
| 2.2 | _____ | No Bid |
| 3.0 | <u>INSTALLATION - PER HOUR</u> Installation services may be requested on an "as needed" basis. See Special Terms and Conditions | N/A |
| 4.0 | <u>NEW EQUIPMENT RENTAL PROGRAM</u> If rental programs are available on the new equipment offered, with the option to purchase, list the hourly/weekly/monthly rental rate. Indicate the percent of rental fee paid by the purchaser that will be applied to the purchase price. See Solicitation Special Terms & Conditions. | |
| | Hourly Rental Rate: | No Bid |
| | Weekly Rental Rate: | No Bid |
| | Monthly Rental Rate: | No Bid |
| | Percent (%) of Rental Fee applied to purchase price: | N/A |
| | If the new rental equipment is purchased and finance charges are applicable for the actual rental term only, state the actual interest rate here: ___N/A_____ | |
| 5.0 | <u>VENDOR OWNED RENTAL RETURN OR DEMO EQUIPMENT PROGRAM</u> See Special Terms and Conditions. DEDUCT cost per Used Hour from the original Contract Price | No Bid |
| 6.0 | <u>PERCENTAGE DISCOUNT OFF LIST PRICE FOR RELATED PARTS & ACCESSORIES</u> See Special Terms and Conditions | 0% for incidental miscellaneous non-contract items; 17% for attachments/accessories on contract. |
| 7.0 | <u>DELIVERY STARTING POINT -</u> _____ City, State, Zip See Special Terms and Conditions - No flat rate allowed | Location of delivering John Deere dealer \$4 per loaded mile |

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - U.S. Equipment for Base Machine

| | |
|---|--|
| Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer | Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes |
|---|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 1601XF | | HP2025 - Hydraulic Power Unit, 25 HP - U.S. <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i> | 6,499.00 |
|--------|--|--|----------|

OIL COOLER

| | | | |
|------|--|--|---------------|
| 2000 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | | Less Oil Cooler | -1,660.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-------|
| 9040 | | Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 92.00 |
|------|--|--|-------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|----------|
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - U.S.

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - U.S. Equipment for Base Machine

| | |
|---|--|
| Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer | Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes |
|---|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 1611XF | | HP2134 - Hydraulic Power Unit, 34 HP - U.S. <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i> | 6,610.00 |
|--------|--|--|----------|

OIL COOLER

| | | | |
|------|--|--|---------------|
| 2000 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | | Less Oil Cooler | -1,660.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-------|
| | | Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | |
| 9040 | | | 92.00 |

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|----------|
| | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | |
| 5RDF0038 | | | 88.26 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - U.S.
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - Canada Equipment for Base Machine

| | |
|---|--|
| Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer | Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes |
|---|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 160AXF | | HP2025 - Hydraulic Power Unit, 25 HP - Canada <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i> | 6,810.11 |
|--------|--|--|----------|

OIL COOLER

| | | | |
|------|--|--|---------------|
| 2000 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | | Less Oil Cooler | -1,735.78 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|--------|
| 9040 | | Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 101.66 |
|------|--|--|--------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|----------|
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - Canada
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - Canada Equipment for Base Machine

| | |
|---|--|
| Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer | Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes |
|---|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 161AXF | | HP2134 - Hydraulic Power Unit, 34 HP - Canada <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i> | 6,924.73 |
|--------|--|--|----------|

OIL COOLER

| | | | |
|------|--|--|---------------|
| 2000 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | | Less Oil Cooler | -1,735.78 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|--------|
| 9040 | | Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 101.66 |
|------|--|--|--------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|----------|
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - Canada
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 73.75 In.

Shipping Weight: 490 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W74.5 In. x H30.75 In. x D34 In.

Capacity:

3.5 Cubic Foot

Operational Weight: 440 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|---|----------|
| 2191XF | | AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber.</i> <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 2,105.00 |
|--------|--|---|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |
|------|--|--|-----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|--------|
| 5MP43052 | | Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
|----------|--|--|--------|

FRONTIER PRODUCTS

Snow Products

**AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 85.75 In.

Shipping Weight: 527 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W86.25 In. x H30.75 In. x D34 In.

Capacity:

4 Cubic Foot

Operational Weight: 477 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|---|----------|
| 2192XF | | AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber.</i> <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 2,333.00 |
|--------|--|---|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |
|------|--|--|-----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|--|--|--|--------|
| | | Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
|--|--|--|--------|

FRONTIER PRODUCTS

Snow Products

**AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier
Equipment for Base Machine

Cutting Width: 97.75 In.

Shipping Weight: 564 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W98.25 In. x H30.75 In. x D34 In.

Capacity:

4.5 Cubic Foot

Operational Weight: 514 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|---|----------|
| 2193XF | | AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber.</i> <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 2,579.00 |
|--------|--|---|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |
|------|--|--|-----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|--|--------|
| 5MP43052 | | Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
|----------|--|--|--------|

FRONTIER PRODUCTS

Snow Products

**AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 98 In.
 Loader Series:
 300, 400, and 500
 Dimensions:
 W98.38 In. x H39.8 In. x D41.5 In.
 Capacity:
 7 Cubic Foot
 Optional Bolt-on Pull Back Kit Weight:
 163 lbs.

Operational Weight: 900 lbs.
 Shipping Weight: 950 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 2201XF | | AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 3,731.00 |
|--------|--|--|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9000 | | Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge) | 750.00 |
| 9010 | | Rubber Edge Kit for 8 Ft. AS11E <i>8 Ft. Back Drag attachment required.</i> | 401.00 |
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|---|----------|
| | | Miscellaneous: | |
| 5FP10730 | | Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge) | 1,305.27 |
| 5MP43052 | | French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
| 5FP10733 | | Rubber Edge Kit for 8 Ft. AS11E <i>5FP10730 - 8 Ft. Back Drag attachment required.</i> | 733.71 |

FRONTIER PRODUCTS

Snow Products

**AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500
Series Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 110 In.

Loader Series:
300, 400, and 500

Dimensions:
W110.38 In. x H39.8 In. x D41.5 In.

Capacity:
7.8 Cubic Foot

Optional Bolt-on Pull Back Kit Weight:
175 lbs.

Operational Weight: 943 lbs.

Shipping Weight: 993 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 2202XF | | AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 4,104.00 |
|--------|--|--|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9000 | | Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge) | 779.00 |
| 9010 | | Rubber Edge Kit for 9 Ft. AS11E <i>9 Ft. Back Drag attachment required.</i> | 447.00 |
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|---|----------|
| | | Miscellaneous: | |
| 5FP10731 | | Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge) | 1,423.16 |
| 5MP43052 | | French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
| 5FP10734 | | Rubber Edge Kit for 9 Ft. AS11E <i>5FP10731 - 9 Ft. Back Drag attachment required.</i> | 734.38 |

FRONTIER PRODUCTS

Snow Products

**AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500
Series Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 119.5 In.

Loader Series:
300, 400, and 500

Dimensions:
W110.875 In. x H39.8 In. x D41.5 In.

Capacity:
8.5 Cubic Foot

Optional Bolt-on Pull Back Kit Weight:
185 lbs.

Operational Weight: 980 lbs.

Shipping Weight: 1030 lbs.

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|---|----------|
| 2203XF | | AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Note: Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> | 4,467.00 |
|--------|--|---|----------|

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|--|-----------|
| 9000 | | Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge) | 817.00 |
| 9010 | | Rubber Edge Kit for 10 Ft. AS11E <i>10 Ft. Back Drag attachment required.</i> | 489.00 |
| 9200 | | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Charge |

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|----------|--|---|----------|
| | | Miscellaneous: | |
| 5FP10732 | | Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge) | 1,458.60 |
| 5MP43052 | | French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11 | 163.56 |
| 5FP10735 | | Rubber Edge Kit for 10 Ft. AS11E <i>5FP10732 - 10 Ft. Back Drag attachment required.</i> | 771.25 |

FRONTIER PRODUCTS

Snow Products

AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

| | |
|--|--|
| <p>Function: Snow Removal Working Width: 48 In. Transport Width: 48.5 In. Working Height: 24 5/8 In. Length: 38.5 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 1/4 In. Impeller Diameter: 20 In. Impeller Width: 6 In. Impeller Shaft Diameter: 1 In. Number of Impeller Blades: 4 Roller Chain: 50 Drive Sprocket: 17 Teeth Driven Sprocket: 36 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model L-25J Gear Box HP (Through Gears): 11 Gear Box HP (Straight Through): 30 Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 20 PTO Clutch Setting (Number): 900 Shearbolt Bolt Size and Grade (PTO): M6 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 1/4 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 12 Gauge Impeller Housing Thickness: 12 Gauge Impeller Blade Thickness: 3/16 In. Side Panel Bottom Thickness: 3/16 In.</p> | <p>Cutting Edge: Welded Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 8 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 16-35 HP Operating Weight: 375 lbs. Shipping Weight: 415 lbs. Approximate Set-up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses, and Tips Electric Actuator (5 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option, Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Motor, Including Flow Restrictors, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A</p> |
|--|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 3801XF | SB1148 - 48 In. 3-Point Medium Snowblower - U.S. | 2,448.97 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 350.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 283.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 54 In.
 Transport Width: 54.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 455 lbs.
 Shipping Weight: 495 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: MN/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 3802XF | | SB1154 - 54 In. 3-Point Medium Snowblower - U.S. | 2,721.00 |
|--------|--|--|----------|

CHUTES

| | | | |
|------|--|---|---------------|
| 1000 | | Manual Chute Rotation Kit | In Base Price |
| 1010 | | Hydraulic Cylinder Kit for Chute Rotation | 350.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|---|--------|
| 9000 | | Hydraulic Cylinder Kit for Chute Deflector | 283.00 |
| 9010 | | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0020 | | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 781.10 |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

| | |
|---|--|
| <p>Function: Snow Removal Working Width: 64 In. Transport Width: 64.5 In. Working Height: 26 In. Length: 41 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. Impeller Diameter: 24 In. Impeller Width: 7 In. Impeller Shaft Diameter: 1-3/8 In. Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-281A Gear Box HP (Through Gears): 23 HP Gear Box HP (Straight Through): 60 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 40 PTO Clutch Setting (Number): 1300 Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 12 Gauge Impeller Housing Thickness: 12 Gauge Impeller Blade Thickness: 3/16 In. Side Panel Bottom Thickness: 3/16 In.</p> | <p>Cutting Edge: Welded Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 8 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 20-50 HP Operating Weight: 479 lbs. Shipping Weight: 519 lbs. Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses, and Tips Electric Actuator (5 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Motor Including Flow Restrictors, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A</p> |
|---|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 3803XF | | SB1164 - 64 In. 3-Point Medium Snowblower - U.S. | 2,803.00 |
|--------|--|--|----------|

CHUTES

| | | | |
|------|--|---|---------------|
| 1000 | | Manual Chute Rotation Kit | In Base Price |
| 1010 | | Hydraulic Cylinder Kit for Chute Rotation | 350.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|---|--------|
| 9000 | | Hydraulic Cylinder Kit for Chute Deflector | 283.00 |
| 9010 | | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0020 | | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 781.10 |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In.
 Transport Width: 74.5 In.
 Working Height: 26 In.
 Length: 47.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 9 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting (Number): 1700
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 1/4 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 590 lbs.
 Shipping Weight: 635 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictor, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 3804XF | SB1174 - 74 In. 3-Point Medium Snowblower - U.S. | 3,531.00 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 350.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 283.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0021 | | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0018 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 552.50 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 84 In.
 Transport Width: 85.5 In.
 Working Height: 34 In.
 Length: 55.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 20 In.
 Auger Flighting Thickness: 3/8 In.
 Impeller Diameter: 27-1/2 In.
 Impeller Width: 10.5 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 38 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 3/16 In.
 Cutting Edge: Welded

Cutting Edge Dimension: 1/2 In. x 3 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I/II
 Quick Hitch Compatibility:
 iMatch Compatible and
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 35-90 HP
 Operating Weight: 958 lbs.
 Shipping Weight: 1003 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Cylinder (2 In. x 8 In.),
 Including Bracket, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 3805XF | SB1184 - 84 In. 3-Point Medium Snowblower - U.S. | 4,880.14 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 439.86 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 300.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| | 5RDF0021 | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| | 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| | 5RDF0018 | Hydraulic Cylinder Kit for Chute Rotation | 552.50 |
| | 5RDF0016 | Manual Chute Rotation Kit (SB11) | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

| | |
|--|---|
| <p>Function: Snow Removal Working Width: 94 In. (2,387.6 mm) Transport Width: 95.5 In. (2,425.7 mm) Working Height: 34 In. (863.6 mm) Length: 55.5 In. (1,409.7 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.5 mm) Impeller Diameter: 27-1/2 In. (698.5 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1-9/16 In. (39.7 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 N-m Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 11 Gauge (3.18 mm) Impeller Blade Thickness: 3/8 In. (9.5 mm) Side Panel Bottom Thickness: 3/16 In. (4.8 mm) Cutting Edge: Welded</p> | <p>Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm) Chute Diameter: 12 In. (304.8 mm) Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 35-90 HP (26.1 kW - 67.1 kW) Operating Weight: 1,121 lbs. (508.5 kg) Shipping Weight: 1,166 lbs. (528.9 kg) Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A</p> |
|--|---|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 3806XF | SB1194 - 94 In. 3-Point Medium Snowblower - U.S. | 5,063.14 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 439.86 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 300.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 820.01 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0021 | | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0018 | | Hydraulic Cylinder Kit for Chute Rotation | 552.50 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In. (1,879.6 mm)
 Transport Width: 74.5 In. (1892.3 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8mm)

Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 835 lbs. (378.7 kg)
 Shipping Weight: 875 lbs. (396.9 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 3831XF | | SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> | 6,828.00 |
|--------|--|--|----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|--|--|---|--------|
| | | Miscellaneous: 5RDF0028 Cutting Edge - CHT400 Steel | 262.91 |
|--|--|---|--------|

FRONTIER PRODUCTS

Snow Products

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 80 In. (2,032 mm)
 Transport Width: 80.5 In. (2,044.7 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8mm)

Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 895 lbs. (406 kg)
 Shipping Weight: 935 lbs. (424.1 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 3832XF | | SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> | 7,029.00 |
|--------|--|--|----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|--|--|---|--------|
| | | Miscellaneous: 5RDF0029 Cutting Edge - CHT400 Steel | 289.17 |
|--|--|---|--------|

FRONTIER PRODUCTS

Snow Products

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2233 lbs.
 Shipping Weight: 2280 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses, and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 3812XF | SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 12,109.57 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 557.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 295.74 |
| 9002 | Cutting Edge - Tivar | 631.16 |

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 612.59 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,405.83 |
| 9012 | | Serrated Main Auger | 2,691.73 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,078.44 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 255.14 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 742.54 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0065 | | 2nd Auger Kit - 15 In. Diameter | 1,300.56 |
| 5RDF0052 | | Cutting Edge - CHT400 Steel | 273.60 |
| 5RDF0060 | | Cutting Edge for SB1308 & SB1308R - Stainless Steel | 566.72 |
| 5RDF0056 | | Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 583.91 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0069 | | Serrated Main Auger for SB1308 & SB1308R | 2,490.16 |

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|---|-------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2160 lbs.
 Shipping Weight: 2205 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 3811XF | SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 10,426.08 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 557.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 295.74 |
| 9002 | Cutting Edge - Tivar | 631.16 |

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 612.59 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,405.83 |
| 9012 | | Serrated Main Auger | 2,691.73 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,078.44 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 255.14 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 742.54 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0065 | | 2nd Auger Kit - 15 In. Diameter | 1,300.56 |
| 5RDF0052 | | Cutting Edge - CHT400 Steel | 273.60 |
| 5RDF0060 | | Cutting Edge for SB1308 & SB1308R - Stainless Steel | 566.72 |
| 5RDF0056 | | Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 583.91 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0069 | | Serrated Main Auger for SB1308 & SB1308R | 2,490.16 |

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|---|-------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 104 In.
 Transport Width: 105 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2336 lbs.
 Shipping Weight: 2385 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 3813XF | SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 12,398.61 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 557.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 317.56 |
| 9002 | Cutting Edge - Tivar | 659.02 |

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 621.89 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,422.00 |
| 9012 | | Serrated Main Auger | 2,784.55 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,078.44 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 255.14 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 742.54 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0066 | | 2nd Auger Kit - 15 In. Diameter | 1,315.51 |
| 5RDF0053 | | Cutting Edge - CHT400 Steel | 293.78 |
| 5RDF0061 | | Cutting Edge for SB1309R - Stainless Steel | 575.31 |
| 5RDF0057 | | Cutting Edge for SB1309R - Tivar <i>Fully Plastic - Wear and Rust Resistant</i> | 609.67 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0070 | | Serrated Main Auger for SB1309R | 2,576.02 |

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 62.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12 3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1670 lbs.
 Shipping Weight: 1715 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|----------|
| 3815XF | SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 9,718.28 |
|--------|---|----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 608.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 257.11 |
| 9002 | Cutting Edge - Tivar | 584.76 |

FRONTIER PRODUCTS

Snow Products

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 594.03 |
| 9010 | | 2nd Auger Kit <i>14 In. diameter.</i> | 1,312.10 |
| 9012 | | Serrated Main Auger | 2,552.49 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9060 | | Quick Hitch Kit (SB1388 & SB1388R Snowblower) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 649.72 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0063 | | 2nd Auger Kit - 14 In. Diameter | 1,213.85 |
| 5RDF0050 | | Cutting Edge - CHT400 Steel | 237.86 |
| 5RDF0058 | | Cutting Edge for SB1388 & SB1388R - Stainless Steel | 549.55 |
| 5RDF0054 | | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 572.78 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0077 | | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 601.08 |
| 5RDF0067 | | Serrated Main Auger for SB1388 & SB1388R | 2,361.36 |
| 5RDF0062 | | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 61 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12-3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1552 lbs.
 Shipping Weight: 1597 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|----------|
| 3814XF | SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 8,252.41 |
|--------|---|----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 608.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 257.11 |
| 9002 | Cutting Edge - Tivar | 584.76 |

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 594.03 |
| 9010 | | 2nd Auger Kit <i>14 In. diameter.</i> | 1,312.10 |
| 9012 | | Serrated Main Auger | 2,552.49 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9060 | | Quick Hitch Kit (SB1388 & SB1388R Snowblower) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 649.72 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0063 | | 2nd Auger Kit - 14 In. Diameter | 1,213.85 |
| 5RDF0050 | | Cutting Edge - CHT400 Steel | 237.86 |
| 5RDF0058 | | Cutting Edge for SB1388 & SB1388R - Stainless Steel | 549.55 |
| 5RDF0054 | | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 572.78 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0077 | | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 601.08 |
| 5RDF0067 | | Serrated Main Auger for SB1388 & SB1388R | 2,361.36 |
| 5RDF0062 | | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 92 In.
 Transport Width: 93 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 75-125 HP
 Operating Weight: 2183 lbs.
 Shipping Weight: 2230 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses, and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 3817XF | SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 11,583.20 |
|--------|---|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 557.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 269.77 |
| 9002 | Cutting Edge - Tivar | 603.32 |

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 603.32 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,330.85 |
| 9012 | | Serrated Main Auger | 2,598.49 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,078.44 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 255.14 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 742.54 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0064 | | 2nd Auger Kit - 15 In. Diameter | 1,231.19 |
| 5RDF0051 | | Cutting Edge - CHT400 Steel | 249.57 |
| 5RDF0059 | | Cutting Edge for SB1392 & SB1392R - Stainless Steel | 558.14 |
| 5RDF0055 | | Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 558.14 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0068 | | Serrated Main Auger for SB1392 & SB1392R | 2,404.29 |

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|---|-------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 92 In.
 Transport Width: 93 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 75-125 HP
 Operating Weight: 2044 lbs.
 Shipping Weight: 2100 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 3816XF | SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | 10,006.00 |
|--------|---|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 557.00 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 269.77 |
| 9002 | Cutting Edge - Tivar | 603.32 |

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 603.32 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,330.85 |
| 9012 | | Serrated Main Auger | 2,598.49 |
| 9020 | | Drift Cutters | 348.58 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 300.00 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,078.44 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 255.14 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 742.54 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 510.50 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0064 | | 2nd Auger Kit - 15 In. Diameter | 1,231.19 |
| 5RDF0051 | | Cutting Edge - CHT400 Steel | 249.57 |
| 5RDF0059 | | Cutting Edge for SB1392 & SB1392R - Stainless Steel | 558.14 |
| 5RDF0055 | | Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 558.14 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0068 | | Serrated Main Auger for SB1392 & SB1392R | 2,404.29 |

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 3822XF | SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S. <i>Must only be used with HP2025 Hydraulic Power Unit.</i> | 13,259.57 |
|--------|---|-----------|

HYDRAULIC POWER UNITS

| | | |
|------|---|---------------|
| 1000 | HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness to control the loader mounted implement.</i> | In Base Price |
| 1095 | Less HP2025 Hydraulic Power Unit | -6,499.00 |

OIL COOLER

| | | |
|------|---|---------------|
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i> | In Base Price |
| 2095 | Less Oil Cooler | -1,660.00 |

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| CHUTES | | | |
| 3000 | | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | | SB2164 Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | 585.00 |
| ATTACHMENTS - ORDER AS DESIRED | | | |
| 9020 | | Drift Cutters (SB21) | 140.00 |
| 9040 | | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i> | 92.00 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0026 | | Drift Cutters (SB21) | 129.52 |
| 5RDF0027 | | Kit for Hydraulic Chute Deflector (SB2164) | 582.04 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Snow Removal
 Working Width: 76 In. (1,931.4 mm)
 Transport Width: 76 In. (1,931.4 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 8.5 In. (215.9 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 580 RPM
 Auger RPM: 180 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 5/16 In. (8 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 mm x 76.2 mm)
 Chute Diameter: 12 In. (0.3m)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual or Hydraulic Adjustable Tie Rod or Hydraulic Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, Wiring Harness and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|---|-----------|
| 3821XF | SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S. | Must only be used with HP2134 Hydraulic Power Unit. | 13,639.58 |
|--------|--|---|-----------|

HYDRAULIC POWER UNITS

| | | | |
|------|--------------------------------------|--|---------------|
| 1010 | HP2134 - Hydraulic Power Unit, 34 HP | Includes wiring harness to control the loader mounted implement. | In Base Price |
| 1095 | Less HP2134 Hydraulic Power Unit | | -6,610.00 |

OIL COOLER

| | | | |
|------|--|--|---------------|
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units | Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095. | In Base Price |
| 2095 | Less Oil Cooler | | -1,660.00 |

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S.

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| CHUTES | | | |
| 3000 | | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | | SB2176 Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | 585.00 |
| ATTACHMENTS - ORDER AS DESIRED | | | |
| 9020 | | Drift Cutters (SB21) | 140.00 |
| 9040 | | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i> | 92.00 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0026 | | Drift Cutters (SB21) | 129.52 |
| 5RDF0025 | | Kit for Hydraulic Chute Deflector (SB2176) | 582.04 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 48 In.
 Transport Width: 48.5 In.
 Working Height: 24 5/8 In.
 Length: 38.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 1/4 In.
 Impeller Diameter: 20 In.
 Impeller Width: 6 In.
 Impeller Shaft Diameter: 1 In.
 Number of Impeller Blades: 4
 Roller Chain: 50
 Drive Sprocket: 17 Teeth
 Driven Sprocket: 36 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model L-25J
 Gear Box HP (Through Gears): 11
 Gear Box HP (Straight Through): 30
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 20
 PTO Clutch Setting (Number): 900
 Shearbolt Bolt Size and Grade (PTO):
 M6 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 1/4 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 375 lbs.
 Shipping Weight: 415 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose
 an Option, Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 380AXF | | SB1148 - 48 In. 3-Point Medium Snowblower - Canada | 2,576.22 |
|--------|--|--|----------|

CHUTES

| | | | |
|------|--|---|---------------|
| 1000 | | Manual Chute Rotation Kit | In Base Price |
| 1010 | | Hydraulic Cylinder Kit for Chute Rotation | 387.37 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|---|--------|
| 9000 | | Hydraulic Cylinder Kit for Chute Deflector | 312.72 |
| 9010 | | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 54 In.
 Transport Width: 54.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 455 lbs.
 Shipping Weight: 495 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: MN/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 380BXF | SB1154 - 54 In. 3-Point Medium Snowblower - Canada | 2,862.39 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 387.37 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 312.72 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0020 | | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 781.10 |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In.
 Transport Width: 64.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 479 lbs.
 Shipping Weight: 519 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 380CXF | | SB1164 - 64 In. 3-Point Medium Snowblower - Canada | 2,948.65 |
|--------|--|--|----------|

CHUTES

| | | | |
|------|--|---|---------------|
| 1000 | | Manual Chute Rotation Kit | In Base Price |
| 1010 | | Hydraulic Cylinder Kit for Chute Rotation | 387.37 |

ATTACHMENTS - ORDER AS DESIRED

| | | | |
|------|--|---|--------|
| 9000 | | Hydraulic Cylinder Kit for Chute Deflector | 312.72 |
| 9010 | | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0020 | | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 781.10 |
| 5RDF0049A | | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 758.60 |
| 5RDF0019 | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 235.54 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0017 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 424.21 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In.
 Transport Width: 74.5 In.
 Working Height: 26 In.
 Length: 47.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 9 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting (Number): 1700
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 1/4 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 590 lbs.
 Shipping Weight: 635 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 380DXF | SB1174 - 74 In. 3-Point Medium Snowblower - Canada | 3,714.48 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 387.37 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 312.72 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|---|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| 5RDF0021 | | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| 5RDF0048A | | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 261.81 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0018 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 552.50 |
| 5RDF0047 | | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 493.02 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | 130.50 |
| 5RDF0046 | | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 84 In.
 Transport Width: 85.5 In.
 Working Height: 34 In.
 Length: 55.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 20 In.
 Auger Flighting Thickness: 3/8 In.
 Impeller Diameter: 27-1/2 In.
 Impeller Width: 10.5 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 38 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 3/16 In.
 Cutting Edge: Welded

Cutting Edge Dimension: 1/2 In. x 3 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I/II
 Quick Hitch Compatibility:
 iMatch Compatible and
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 35-90 HP
 Operating Weight: 958 lbs.
 Shipping Weight: 1003 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Cylinder (2 In. x 8 In.),
 Including Bracket, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 380EXF | SB1184 - 84 In. 3-Point Medium Snowblower - Canada | 5,133.71 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 446.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 331.50 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| | | Miscellaneous: | |
| | 5RDF0021 | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| | 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| | 5RDF0018 | Hydraulic Cylinder Kit for Chute Rotation | 552.50 |
| | 5RDF0016 | Manual Chute Rotation Kit (SB11) | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

| | |
|--|--|
| Function: Snow Removal | Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm) |
| Working Width: 94 In. (2,387.6 mm) | Chute Diameter: 12 In. (304.8 mm) |
| Transport Width: 95.5 In. (2,425.7 mm) | Chute Base: Standard |
| Working Height: 34 In. (863.6 mm) | Chute Rotation: 215 Degrees |
| Length: 55.5 In. (1,409.7 mm) | Parking Stand: Standard |
| Single/Dual Auger: Single | Hitch Category: Category II |
| Auger Diameter: 20 In. (508 mm) | Quick Hitch Compatibility: |
| Auger Flighting Thickness: 3/8 In. (9.5 mm) | Quick Coupler Compatible |
| Impeller Diameter: 27-1/2 In. (698.5 mm) | HP Requirements (Minimum-Maximum HP): |
| Impeller Width: 10.5 In. (266.7 mm) | 35-90 HP (26.1 kW - 67.1 kW) |
| Impeller Shaft Diameter: 1-9/16 In. (39.7 mm) | Operating Weight: 1,121 lbs. (508.5 kg) |
| Number of Impeller Blades: 4 | Shipping Weight: 1,166 lbs. (528.9 kg) |
| Roller Chain: 60 | Approximate Set-Up Time: 60 Minutes |
| Drive Sprocket: 10 Teeth | Chute Deflector Adjustment (Standard): |
| Driven Sprocket: 32 Teeth | Manual |
| Chain Idler: Manual Adjustment | Chute Deflector Adjustment Options: |
| Gear Box Manufacturer: Comer | Hydraulic Cylinder (2 In. x 8 In.) |
| Gear Box Description: Model T-27D | Including Hoses and Tips |
| Gear Box HP (Through Gears): 55 HP (41 kW) | Electric Actuator (8 In.) |
| Gear Box HP (Straight Through): 105 HP (78.3 kW) | Including Hardware, Switch, and Electric Cable |
| Tractor RPM: 540 RPM | Chute Rotation (Standard): Must choose an |
| Impeller RPM: 540 RPM | Option - Manual or Hydraulic |
| Auger RPM: 170 RPM | Chute Rotation Options: |
| PTO Manufacturer: Comer | Manual, Worm Gear with Crank |
| PTO Description: 60 | Hydraulic: Cylinder (2 In. x 8 In.), |
| PTO Clutch Setting (Number): 1900 N-m | Including Bracket, Hoses, and Tips |
| Shearbolt Bolt Size and Grade (PTO): | Chute: Two Part ONLY |
| M10 6.8 Metric | Dual Auger: N/A |
| Shearbolt Bolt Size and Grade (Auger): | Rotating Drum (Including Hoses and Tips): |
| 5/16 In. 5 SAE | N/A |
| Skid Shoe: Adjustable | |
| Skid Shoe Material: Steel | |
| End Plate Thickness: 3/16 In. (4.8 mm) | |
| Back Plate Thickness: 11 Gauge (3.18 mm) | |
| Impeller Housing Thickness: 11 Gauge (3.18 mm) | |
| Impeller Blade Thickness: 3/8 In. (9.5 mm) | |
| Side Panel Bottom Thickness: 3/16 In. (4.8 mm) | |
| Cutting Edge: Welded | |

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|----------|
| 380FXF | SB1194 - 94 In. 3-Point Medium Snowblower - Canada | 5,343.01 |
|--------|--|----------|

CHUTES

| | | |
|------|---|---------------|
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | 446.56 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|---|--------|
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | 331.50 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | 906.11 |

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS FOR FIELD CONVERSION ...Continued... | | | |
| Miscellaneous: | | | |
| 5RDF0021 | | Electric Kit for Chute Deflector - Includes 8 In. Actuator | 758.60 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0018 | | Hydraulic Cylinder Kit for Chute Rotation | 552.50 |
| 5RDF0016 | | Manual Chute Rotation Kit (SB11) | 130.50 |

FRONTIER PRODUCTS

Snow Products

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In. (1,879.6 mm)
 Transport Width: 74.5 In. (1892.3 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 835 lbs. (378.7 kg)
 Shipping Weight: 875 lbs. (396.9 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 383AXF | | SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> | 6,931.98 |
|--------|--|--|----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|--|--|--|--------|
| | | Miscellaneous: Cutting Edge - CHT400 Steel | 262.91 |
|--|--|--|--------|

FRONTIER PRODUCTS

Snow Products

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 80 In. (2,032 mm)
 Transport Width: 80.5 In. (2,044.7 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 895 lbs. (406 kg)
 Shipping Weight: 935 lbs. (424.1 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | | |
|--------|--|--|----------|
| 383BXF | | SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> | 7,136.04 |
|--------|--|--|----------|

ATTACHMENTS FOR FIELD CONVERSION

| | | | |
|--|--|--|--------|
| | | Miscellaneous: Cutting Edge - CHT400 Steel | 289.17 |
|--|--|--|--------|

FRONTIER PRODUCTS

Snow Products

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2233 lbs.
 Shipping Weight: 2280 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses, and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 381BXF | SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 12,872.60 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 615.49 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 326.80 |
| 9002 | Cutting Edge - Tivar | 697.44 |

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 676.92 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,553.44 |
| 9012 | | Serrated Main Auger | 2,794.36 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,401.68 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 281.93 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 820.51 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| | 5RDF0065 | 2nd Auger Kit - 15 In. Diameter | 1,300.56 |
| | 5RDF0052 | Cutting Edge - CHT400 Steel | 273.60 |
| | 5RDF0060 | Cutting Edge for SB1308 & SB1308R - Stainless Steel | 566.72 |
| | 5RDF0056 | Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 583.91 |
| | 5RDF0074 | Drift Cutters | 322.47 |
| | 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| | 5RDF0075 | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| | 5RDF0023 | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| | 5RDF0076 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| | 5RDF0069 | Serrated Main Auger for SB1308 & SB1308R | 2,490.16 |

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|---|-------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2160 lbs.
 Shipping Weight: 2205 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 381AXF | SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 11,083.03 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 615.49 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 326.80 |
| 9002 | Cutting Edge - Tivar | 697.44 |

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 676.92 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,553.44 |
| 9012 | | Serrated Main Auger | 2,794.36 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,401.68 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 281.93 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 820.51 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0065 | | 2nd Auger Kit - 15 In. Diameter | 1,300.56 |
| 5RDF0052 | | Cutting Edge - CHT400 Steel | 273.60 |
| 5RDF0060 | | Cutting Edge for SB1308 & SB1308R - Stainless Steel | 566.72 |
| 5RDF0056 | | Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 583.91 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0069 | | Serrated Main Auger for SB1308 & SB1308R | 2,490.16 |

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 104 In.
 Transport Width: 105 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2336 lbs.
 Shipping Weight: 2385 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 381CXF | SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 13,179.85 |
|--------|--|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 615.49 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 350.90 |
| 9002 | Cutting Edge - Tivar | 728.21 |

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 687.18 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,571.31 |
| 9012 | | Serrated Main Auger | 3,076.92 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,401.68 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 281.93 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 820.51 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0066 | | 2nd Auger Kit - 15 In. Diameter | 1,315.51 |
| 5RDF0053 | | Cutting Edge - CHT400 Steel | 293.78 |
| 5RDF0061 | | Cutting Edge for SB1309R - Stainless Steel | 575.31 |
| 5RDF0057 | | Cutting Edge for SB1309R - Tivar <i>Fully Plastic - Wear and Rust Resistant</i> | 609.67 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0070 | | Serrated Main Auger for SB1309R | 2,576.02 |

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 62.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12 3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1670 lbs.
 Shipping Weight: 1715 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 381EXF | SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 10,738.70 |
|--------|---|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 671.84 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 284.11 |
| 9002 | Cutting Edge - Tivar | 684.16 |

FRONTIER PRODUCTS

Snow Products

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 656.41 |
| 9010 | | 2nd Auger Kit <i>14 In. diameter.</i> | 1,449.88 |
| 9012 | | Serrated Main Auger | 2,820.51 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9060 | | Quick Hitch Kit (SB1388 & SB1388R Snowblower) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 717.95 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0063 | | 2nd Auger Kit - 14 In. Diameter | 1,213.85 |
| 5RDF0050 | | Cutting Edge - CHT400 Steel | 237.86 |
| 5RDF0058 | | Cutting Edge for SB1388 & SB1388R - Stainless Steel | 549.55 |
| 5RDF0054 | | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 572.78 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0077 | | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 601.08 |
| 5RDF0067 | | Serrated Main Auger for SB1388 & SB1388R | 2,361.36 |
| 5RDF0062 | | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 61 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12-3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1552 lbs.
 Shipping Weight: 1597 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|----------|
| 381DXF | SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 9,118.91 |
|--------|---|----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 671.84 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 284.11 |
| 9002 | Cutting Edge - Tivar | 684.16 |

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 656.41 |
| 9010 | | 2nd Auger Kit <i>14 In. diameter.</i> | 1,449.88 |
| 9012 | | Serrated Main Auger | 2,820.51 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9060 | | Quick Hitch Kit (SB1388 & SB1388R Snowblower) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 717.95 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0063 | | 2nd Auger Kit - 14 In. Diameter | 1,213.85 |
| 5RDF0050 | | Cutting Edge - CHT400 Steel | 237.86 |
| 5RDF0058 | | Cutting Edge for SB1388 & SB1388R - Stainless Steel | 549.55 |
| 5RDF0054 | | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 572.78 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0077 | | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 601.08 |
| 5RDF0067 | | Serrated Main Auger for SB1388 & SB1388R | 2,361.36 |
| 5RDF0062 | | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

| | |
|--|--|
| Function: Snow Removal Working Width: 92 In. Transport Width: 93 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In. Side Panel Bottom Thickness: 5/8 In. | Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 75-125 HP Operating Weight: 2183 lbs. Shipping Weight: 2230 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard |
|--|--|

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 381GXF | SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 12,313.06 |
|--------|---|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 615.49 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 298.09 |
| 9002 | Cutting Edge - Tivar | 666.67 |

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 666.67 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,470.59 |
| 9012 | | Serrated Main Auger | 2,871.79 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,401.68 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 281.93 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 820.51 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| | | Miscellaneous: | |
| | 5RDF0064 | 2nd Auger Kit - 15 In. Diameter | 1,231.19 |
| | 5RDF0051 | Cutting Edge - CHT400 Steel | 249.57 |
| | 5RDF0059 | Cutting Edge for SB1392 & SB1392R - Stainless Steel | 558.14 |
| | 5RDF0055 | Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 558.14 |
| | 5RDF0074 | Drift Cutters | 322.47 |
| | 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| | 5RDF0075 | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| | 5RDF0023 | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| | 5RDF0076 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| | 5RDF0068 | Serrated Main Auger for SB1392 & SB1392R | 2,404.29 |

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 92 In.
 Transport Width: 93 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 75-125 HP
 Operating Weight: 2044 lbs.
 Shipping Weight: 2100 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|-------|---|-----------|
| 381XF | SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada | 10,525.91 |
|-------|---|-----------|

CHUTES

| | | |
|------|--|---------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | 615.49 |

ATTACHMENTS - ORDER AS DESIRED

| | | |
|------|-----------------------------|--------|
| 9000 | Cutting Edge - CHT400 Steel | 298.09 |
| 9002 | Cutting Edge - Tivar | 666.67 |

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| ATTACHMENTS - ORDER AS DESIRED ...Continued... | | | |
| <i>Fully Plastic - Wear & Rust Resistant.</i> | | | |
| 9003 | | Cutting Edge - Stainless Steel | 666.67 |
| 9010 | | 2nd Auger Kit <i>15 In. diameter.</i> | 1,470.59 |
| 9012 | | Serrated Main Auger | 2,871.79 |
| 9020 | | Drift Cutters | 385.18 |
| 9030 | | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | 331.50 |
| 9040 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | 3,401.68 |
| 9050 | | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 281.93 |
| 9060 | | Quick Hitch Kit (13-Series Snowblower except SB1388 & SB1388R) <i>Required for Cat 2 & Cat 3 Quick-Hitch.</i> | 820.51 |
| 9070 | | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | 564.10 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| Miscellaneous: | | | |
| 5RDF0064 | | 2nd Auger Kit - 15 In. Diameter | 1,231.19 |
| 5RDF0051 | | Cutting Edge - CHT400 Steel | 249.57 |
| 5RDF0059 | | Cutting Edge for SB1392 & SB1392R - Stainless Steel | 558.14 |
| 5RDF0055 | | Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | 558.14 |
| 5RDF0074 | | Drift Cutters | 322.47 |
| 5RDF0071 | | Hydraulic Cylinder Kit for Chute Deflector | 277.53 |
| 5RDF0075 | | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | 686.94 |
| 5RDF0023 | | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | 236.03 |
| 5RDF0076 | | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | 2,847.91 |
| 5RDF0068 | | Serrated Main Auger for SB1392 & SB1392R | 2,404.29 |

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|--------------------------|---|-------------------------------------|
| | | ATTACHMENTS FOR FIELD CONVERSION ...Continued... | |
| | 5RDF0062 | Stainless Steel Pivoting Skid Shoes | 472.27 |

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|---|-----------|
| 382BXF | SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada <i>Must only be used with HP2025 Hydraulic Power Unit.</i> | 13,895.42 |
|--------|---|-----------|

HYDRAULIC POWER UNITS

| | | |
|------|---|---------------|
| 1000 | HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness to control the loader mounted implement.</i> | In Base Price |
| 1095 | Less HP2025 Hydraulic Power Unit | -6,810.11 |

OIL COOLER

| | | |
|------|---|---------------|
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i> | In Base Price |
| 2095 | Less Oil Cooler | -1,735.78 |

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| CHUTES | | | |
| 3000 | | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | | SB2164 Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | 646.43 |
| ATTACHMENTS - ORDER AS DESIRED | | | |
| 9020 | | Drift Cutters (SB21) | 154.70 |
| 9040 | | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i> | 101.66 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0026 | | Drift Cutters (SB21) | 129.52 |
| 5RDF0027 | | Kit for Hydraulic Chute Deflector (SB2164) | 582.04 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|------|-----------------------|-------------|-------------------------------|
|------|-----------------------|-------------|-------------------------------|

Select One Code From Each Required Category

BASE MACHINE

| | | |
|--------|--|-----------|
| 382AXF | SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada <i>Must only be used with HP2134 Hydraulic Power Unit.</i> | 14,288.36 |
|--------|--|-----------|

HYDRAULIC POWER UNITS

| | | |
|------|---|---------------|
| 1010 | HP2134 - Hydraulic Power Unit, 34 HP <i>Includes wiring harness to control the loader mounted implement.</i> | In Base Price |
| 1095 | Less HP2134 Hydraulic Power Unit | -6,924.73 |

OIL COOLER

| | | |
|------|---|---------------|
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i> | In Base Price |
| 2095 | Less Oil Cooler | -1,735.78 |

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada

Continued

| CODE | ATTACHMENT IDENTIFIER | DESCRIPTION | SUGGESTED LIST PRICE USD (\$) |
|---|-----------------------|--|-------------------------------|
| CHUTES | | | |
| 3000 | | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | | SB2176 Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | 646.43 |
| ATTACHMENTS - ORDER AS DESIRED | | | |
| 9020 | | Drift Cutters (SB21) | 154.70 |
| 9040 | | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i> | 101.66 |
| ATTACHMENTS FOR FIELD CONVERSION | | | |
| 5RDF0038 | | Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | 88.26 |
| 5RDF0026 | | Drift Cutters (SB21) | 129.52 |
| 5RDF0025 | | Kit for Hydraulic Chute Deflector (SB2176) | 582.04 |
| 5RDF0036 | | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | 1,650.86 |
| 5RDF0078 | | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | 126.19 |