

MINNESOTA  
PRICING SCHEDULE  
(Typed responses required)

Vendor Name: Mahindra USA INC  
 Contact Person: Steve Ricke  
 Street Address: PO Box 82189  
 P.O. Box: 12918 N Nebraska Ave  
 City, State, Zip: Tampa, FL 33682  
 Phone #: (813)977-7111  
 Toll Free #: \_\_\_\_\_  
 Fax #: (813)977-7112  
 Email Address: steve@federalcontractscorp.com

SPEC #	REQUESTED INFORMATION	ANSWER
1.0	TRACTOR CATALOG SECTION PRICE PRICE LIST TITLE: <u>Mahindra USA Master</u>	
	DATE AND ID# OF PRICE LIST: _____	<u>1/11/2016</u>
	PERCENTAGE DISCOUNT TO BE APPLIED TO PRICE LIST: <u>15% (excluding M force which will be 10%)</u>	
1.1	Price for manuals, (service, parts, repair, and operations)	<u>350</u>
1.2	Price for set of fluid and air filters	<u>180</u>
2.0	<b><u>PERFORMANCE/EXTENDED WARRANTY OPTIONS</u></b> Offer performance/warranty options. Numbers starting with 2.1, 2.2, etc. (Specify years, miles or hours extended term covers.)	
2.1	_____	<u>NC</u>
2.2	_____	<u>NC</u>
3.0	<b><u>INSTALLATION - PER HOUR</u></b> Installation services may be requested on an "as needed" basis. See Special Terms and Conditions	<u>95</u>
4.0	<b><u>NEW EQUIPMENT RENTAL PROGRAM</u></b> If rental programs are available on the new equipment offered, with the option to purchase, list the hourly/weekly/monthly rental rate. Indicate the percent of rental fee paid by the purchaser that will be applied to the purchase price. See Solicitation Special Terms & Conditions.	
	Hourly Rental Rate: _____	<u>-</u>
	Weekly Rental Rate: _____	<u>-</u>
	Monthly Rental Rate: _____	<u>-</u>
	Percent (%) of Rental Fee applied to purchase price: _____	<u>-</u>
	If the new rental equipment is purchased and finance charges are applicable for the actual rental term only, state the actual interest rate here: _____	
5.0	<b><u>VENDOR OWNED RENTAL RETURN OR DEMO EQUIPMENT PROGRAM</u></b> See Special Terms and Conditions. DEDUCT cost per Used Hour from the original Contract Price	<u>-</u>
6.0	<b><u>PERCENTAGE DISCOUNT OFF LIST PRICE FOR RELATED PARTS &amp; ACCESSORIES</u></b> See Special Terms and Conditions	<u>8%</u>
7.0	<b><u>DELIVERY STARTING POINT -</u></b> _____ <b>City, State, Zip</b> See Special Terms and Conditions - No flat rate allowed	<u>Houston, TX</u> <u>NC</u>

### Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kW).....22 (16.4)  
Compression Ratio.....21:1  
Displacement cu-in (cc).....61.5 (1007)  
Rated Speed.....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

### Power Take Off

Type.....Trans  
PTO HP (kW).....16.9 (12.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Synchro Mesh  
Number of speeds.....6F/2R  
Clutch.....Dry single disc, mechanic  
Brakes.....Wet disc brake, mechanical

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full live hydraulic  
Implement pump output  
.....4.5 gpm (17.03 liters/min)  
Steering pump output  
.....2.6 gpm (9.8 liters/min)  
Maximum total flow  
.....7.1 gpm (26.8 liters/min)  
Category 1, 3 point hitch.....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....1,322 lb. (600 kg)

### Operator Station

Reinforced steel hood and fenders  
Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

### Dimensions

Overall Length.....92.5 in. (2,350 mm)  
Overall Width.....50.8 in (1,290 mm)  
Overall Height.....89.7 in. (2,278 mm)  
Wheelbase.....66.1 in. (1,460 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

### Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

### Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System.....4.9 qts. (4.6 L)  
Engine Oil.....3.4 qts. (3.2 L)  
Transmission and Differential  
.....18 qts. (17 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

### Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

### Operating Weight

1,540 lb. (700kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EXS22H*	eMAX S 22G (T4)	008500M00	1540 (700)	\$ 11,900
EXS22G*M	eMAX S 22G & Mower	010600M00	1890 (859)	\$ 14,530
EXS22G*L	eMAX S 22G Loader	011550M00	2047 (930)	\$ 15,710
EXS22G*LM	eMAX S 22G Loader & Mower	013650M00	2397 (1090)	\$ 18,340
EXS22G*LB	eMAX S 22G Loader & Backhoe	015880M00	2757 (1253)	\$ 21,130
EXS22G*LBM	eMAX S 22G Loader, Mower & Backhoe	020080M00	3107 (1412)	\$ 23,750

\* Different tire options

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 420
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 80
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Loader w/bucket for eMax S	TYML25-S	03050M00	\$ 3,810
----------------------------	----------	----------	----------

### LOADER ATTACHMENTS

50" Material Bucket Pin-on	8750100100168	0225M00	\$ 290
----------------------------	---------------	---------	--------

### MID MOWER

60" Mid Mower	AEMAHMEG60	01850M00	\$ 2,315
---------------	------------	----------	----------

### BACKHOE

eMax 25B (Less Bucket)	AEMB63E	04330M00	\$ 5,420
------------------------	---------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 380
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 480

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.

### Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....22 (16.4)  
Compression Ratio.....21:1  
Displacement cu-in (cc).....61.5 (1007)  
Rated Speed.....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

### Power Take Off

Type.....Independent  
PTO HP (kW).....16.9 (12.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch.....Dry single disc  
Brakes.....Wet disc brake

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full live hydraulic  
Implement pump output  
.....4.5 gpm (17.03 liters/min)  
Steering pump output  
.....2.6 gpm (9.8 liters/min)  
Maximum total flow  
.....7.1 gpm (26.8 liters/min)  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....1,322 lb. (600 kg)

### Operator Station

Reinforced steel hood and fenders  
Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

### Dimensions

Overall Length.....92.5 in. (2,350 mm)  
Overall Width.....50.8 in. (1,290 mm)  
Overall Height.....89.7 in. (2,278 mm)  
Wheelbase.....66.1 in. (1,660 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

### Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

### Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System.....4.9 qts. (4.6 L)  
Engine Oil.....3.4 qts. (3.2 L)  
Transmission and Differential  
.....15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

### Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

### Operating Weight

1,540 lb. (700kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EXS22H*	eMAX S 22H (T4)	008900M00	1540 (700)	\$ 12,460
EXS22H*M	eMAX S 22H & Mower	011000M00	1890 (859)	\$ 15,090
EXS22H*L	eMAX S 22H Loader	011950M00	2047 (930)	\$ 16,270
EXS22H*LM	eMAX S 22H Loader & Mower	014050M00	2397 (1090)	\$ 18,900
EXS22H*LB	eMAX S 22H Loader & Backhoe	016280M00	2757 (1253)	\$ 21,690
EXS22H*LBM	eMAX S 22H Loader, Mower & Backhoe	020480M00	3107 (1412)	\$ 24,310

\* Different tire options

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 420
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 80
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Loader w/bucket for eMax S	TYML25-S	03050M00	\$ 3,810
----------------------------	----------	----------	----------

### LOADER ATTACHMENTS

50" Material Bucket Pin-on	875010010016B	0225M00	\$ 290
----------------------------	---------------	---------	--------

### MID MOWER

60" Mid Mower	AEMAHME60	01850M00	\$ 2,315
---------------	-----------	----------	----------

### BACKHOE

eMax 25B (Less Bucket)	AEMB63E	04330M00	\$ 5,420
------------------------	---------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 380
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 480

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax S 25 HST

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....24 (17.9)  
Compression Ratio.....21:1  
Displacement cu-in (cc).....61.5 (1007)  
Rated Speed.....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

## Power Take Off

Type.....Independent  
PTO HP (kW).....19.3 (14.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch.....Dry single disc  
Brakes.....Wet disc brake

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic  
Pump output.....4.5 gpm (17.03 liters/min)  
Steering pump output  
.....2.6 gpm (9.8 liters/min)  
Maximum total flow  
.....7.1 gpm (26.8 liters/min)  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....1,322 lb. (600 kg)

## Operator Station

Reinforced steel hood and fenders  
Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length .....92.5 in. (2,350 mm)  
Overall Width .....50.8 in. (1,290 mm)  
Overall Height .....89.7 in. (2,278 mm)  
Wheelbase .....66.1 in. (1,460 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System .....4.9 qts. (4.6 L)  
Engine Oil.....3.4 qts. (3.2 L)  
Transmission and Differential  
.....15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

## Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1,540 lb. (700 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EXS25H*	eMAX S 25H (T4)	009900M00	1540 (700)	\$ 13,860
EXS25H*M	eMAX S 25H & Mower	012000M00	1890 (859)	\$ 16,490
EXS25H*L	eMAX S 25H Loader	012950M00	2047 (930)	\$ 17,670
EXS25H*LM	eMAX S 25H Loader & Mower	015050M00	2397 (1090)	\$ 20,300
EXS25H*LB	eMAX S 25H Loader & Backhoe**	017280M00	2757 (1253)	\$ 24,090
EXS25H*LBM	eMAX S 25H Loader, Mower & Backhoe**	021480M00	3107 (1412)	\$ 25,710

\* Different tire options

\*\* Weight less backhoe bucket



# eMax S 25 HST

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 420
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 80
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Loader w/bucket for eMax S	TYML25-S	03050M00	\$ 3,810
----------------------------	----------	----------	----------

### LOADER ATTACHMENTS

50" Material Bucket Pin-on	87504001001GB	0225M00	\$ 285
----------------------------	---------------	---------	--------

### MID MOWER

60" Mid Mower	AEMAHME60	01850M00	\$ 2,315
---------------	-----------	----------	----------

### BACKHOE

eMax 25B (Less Bucket)	AEMB63E	04330M00	\$ 5,420
------------------------	---------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 380
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 480

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax S 25 HST Cab

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....24 (17.9)  
Compression Ratio..... 21:1  
Displacement cu-in (cc) .....61.5 (1007)  
Rated Speed.....3000 rpm  
Low Idle RPM..... 3230 ± 50 rpm  
High Idle RPM..... 1350 ± 50 rpm

## Power Take Off

Type.....Independent  
PTO HP (kW)..... 19.3 (14.2)  
Rear PTO RPM at engine RPM  
..... 540 @ 2893  
Mid PTO RPM at engine RPM  
..... 2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch ..... Dry single disc  
Brakes..... Wet disc brake

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type..... Open center, full live hydraulic  
Pump output..... 4.5 gpm (17.03 liters/min)  
Steering pump output  
..... 2.6 gpm (9.8 liters/min)  
Maximum total flow  
..... 7.1 gpm (26.8 liters/min)  
Category 1, 3 point hitch.... Category 1, with  
check chains  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity ..... 1,322 lb. (600 kg)

## Operator Station

Reinforced steel hood and fenders  
Cruise Control  
Wide Platform Steps  
Color Coded Controls  
External Mirrors  
Front Wiper w/ fluid  
Two front work lights  
Rear work light  
Heater w/ temperature control  
12V socket

## Dimensions

Overall Length ..... 92.5 in. (2,350 mm)  
Overall Width..... 50.8 in. (1,290 mm)  
Overall Height..... 78.2 in. (1,986 mm)  
Wheelbase ..... 66.1 in. (1,460 mm)  
Min. Ground Clearance..... 8.2 in. (207 mm)  
Turning Radius..... 7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear)..... 6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
..... 20x8-10/27x12.5-15  
Turf (Front/Rear)[Standard]  
..... 20x8-10/29x12.5-15

## Capacities

Fuel Tank..... 6.1 gal. (23.1 L)  
Cooling System..... 4.9 qts. (4.6 L)  
Engine Oil ..... 3.4 qts. (3.2 L)  
Transmission and Differential  
..... 15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
..... 3.7 qts. (3.5 L)

## Electrical

Battery..... 12 Volt, 50 AH 500 CCA  
Alternator..... 12 V 50 A  
Starter Capacity..... 12V, 1.7 KW

## Operating Weight

1,870 lb. (850 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EXS254CH*	eMAX S 25H Cab (T4)	012700M00	1870 (850)	\$ 17,780
EXS254CH*M	eMAX S 25H Cab & Mower	014800M00	2220 (1009)	\$ 20,410
EXS254CH*L	eMAX S 25H Cab Loader	015750M00	2377 (1080)	\$ 21,590
EXS254CH*LM	eMAX S 25H Cab Loader Mower	017850M00	2727 (1240)	\$ 24,220

\* Different tire options



# eMax S 25 HST Cab

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	TBD		-
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 80
Mulch Kit	AMEMHM647	0279M00	\$ 400

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

Loader w/bucket for eMax S	TYML25	03050M00	\$ 3,810
----------------------------	--------	----------	----------

## LOADER ATTACHMENTS

50" Material Bucket Pin-on	875040010016B	0225M00	\$ 390
----------------------------	---------------	---------	--------

## MID MOWER

60" Mid Mower	AEMAHME60	01850M00	\$ 2,315
---------------	-----------	----------	----------

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax™ 22 Gear

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....22 (16.4)  
Compression Ratio.....21:1  
Displacement cu-in (cc) .....61.5 (1007)  
Rated Speed .....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

## Power Take Off

Type.....Trans  
PTO HP (kW).....16.9 (12.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter .....  
Fuel Gauge .....  
Temperature Gauge.....  
Indicators for Warning Messages.....  
4WD Drive Lamp .....

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Synchro Mesh  
Number of speeds .....6F/2R  
Clutch.....Dry single disc, mechanic  
Brakes.....Wet disc brake, mechanic

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic  
Pump output.....4.5 gpm (17.03 liters/min)  
Category 1, 3 point hitch.....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity .....1,322 lb. (600 kg)

## Operator Station

Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length .....92.5 in. (2,350 mm)  
Overall Width.....50.8 in (1,290 mm)  
Overall Height.....89.7 in. (2,278 mm)  
Wheelbase .....66.1 in. (1,460 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)[Standard]  
.....20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System.....4.9 qts. (4.6 L)  
Engine Oil.....3.4 qts. (3.2 L)  
Transmission and Differential  
.....18 qts. (17 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

## Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1,540 lb. (700kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EX22G*	eMAX 22G (T4)	008300M00	1540 (700)	\$ 11,620
EX22G*M	eMAX 22G & Mower	010400M00	1890 (859)	\$ 14,250
EX22G*L	eMAX 22G Loader	011300M00	2047 (930)	\$ 15,370
EX22G*LM	eMAX 22G Loader & Mower	013400M00	2397 (1090)	\$ 18,000
EX22G*LB	eMAX 22G Loader & Backhoe	015630M00	2757 (1253)	\$ 20,790
EX22G*LBM	eMAX 22G Loader, Mower & Backhoe	019830M00	3107 (1412)	\$ 23,410

\* Different tire options

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 415
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 75
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

eMax 25L	Uninstalled	03000M00	\$ 3,750
----------	-------------	----------	----------

### LOADER ATTACHMENTS

50" Material Bucket Pin-on	87501001001GB	0225M00	\$ 285
----------------------------	---------------	---------	--------

### MID MOWER

eMax 25 M 60" Mid Mower	AEMAHMEG60 Uninstalled	01850M00	\$ 2,315
-------------------------	------------------------	----------	----------

### BACKHOE

eMax 25B (Less Bucket)	AEMB63E Uninstalled	04330M00	\$ 5,415
------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax™ 22 HST

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....22 (16.4)  
Compression Ratio..... 21:1  
Displacement cu-in (cc) .....61.5 (1007)  
Rated Speed .....3000 rpm  
Low Idle RPM..... 3230 ± 50 rpm  
High Idle RPM..... 1350 ± 50 rpm

## Power Take Off

Type.....Independent  
PTO HP (kW)..... 16.9 (12.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch ..... Dry single disc  
Brakes..... Wet disc brake

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic  
Pump output.....4.5 gpm (17.03 liters/min)  
Category 1, 3 point hitch..... Category 1, with  
check chains  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity ..... 1,322 lb. (600 kg)

## Operator Station

Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length .....92.5 in. (2,350 mm)  
Overall Width .....50.8 in. (1,290 mm)  
Overall Height .....89.7 in. (2,278 mm)  
Wheelbase .....66.1 in. (1,460 mm)  
Min. Ground Clearance ..... 8.2 in. (207 mm)  
Turning Radius..... 7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
..... 20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
..... 20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System..... 4.9 qts. (4.6 L)  
Engine Oil ..... 3.4 qts. (3.2 L)  
Transmission and Differential  
..... 15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
..... 3.7 qts. (3.5 L)

## Electrical

Battery..... 12 Volt, 50 AH 500 CCA  
Alternator ..... 12 V 50 A  
Starter Capacity..... 12V, 1.7 KW

## Operating Weight

1,540 lb. (700 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EX22H*	eMAX 22H (T4)	008700M00	1540 (700)	\$ 12,180
EX22H*M	eMAX 22H & Mower	010800M00	1890 (859)	\$ 14,810
EX22H*L	eMAX 22H Loader	011700M00	2047 (930)	\$ 15,930
EX22H*LM	eMAX 22H Loader & Mower	013800M00	2397 (1090)	\$ 18,560
EX22H*LB	eMAX 22H Loader & Backhoe	016030M00	2757 (1253)	\$ 21,350
EX22H*LBM	eMAX 22H Loader, Mower & Backhoe	020230M00	3107 (1412)	\$ 23,970

\* Different tire options



# eMax™ 22 HST

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 415
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 75
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

eMax 25L	Uninstalled	0300M00	\$ 3,750
----------	-------------	---------	----------

### LOADER ATTACHMENTS

50" Material Bucket Pin-on	875010010016B	0225M00	\$ 285
----------------------------	---------------	---------	--------

### MID MOWER

eMax 25 M 60" Mid Mower	AEMAHME60 Uninstalled	01850M00	\$ 2,315
-------------------------	-----------------------	----------	----------

### BACKHOE

eMax 25B (Less Bucket)	AEMB63E Uninstalled	04330M00	\$ 5,415
------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax™ 25 HST

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....24 (17.9)  
Compression Ratio.....21:1  
Displacement cu-in (cc).....61.5 (1007)  
Rated Speed.....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

## Power Take Off

Type.....Independent  
PTO HP (kW).....19.3 (14.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch.....Dry single disc  
Brakes.....Wet disc brake

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic  
Pump output.....4.5 gpm (17.03 liters/min)  
Category 1, 3 point hitch.....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....1,322 lb. (600 kg)

## Operator Station

Cruise Control  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length.....92.5 in. (2,350 mm)  
Overall Width.....50.8 in. (1,290 mm)  
Overall Height.....89.7 in. (2,278 mm)  
Wheelbase.....66.1 in. (1,460 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System.....4.9 qts. (4.6 L)  
Engine Oil.....3.4 qts. (3.2 L)  
Transmission and Differential  
.....15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

## Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1,540 lb. (700 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EX25H*	eMAX 25H (T4)	009700M00	1540 (700)	\$ 13,580
EX25H*M	eMAX 25H & Mower	011800M00	1890 (859)	\$ 16,210
EX25H*L	eMAX 25H Loader	012700M00	2047 (930)	\$ 17,330
EX25H*LM	eMAX 25H Loader & Mower	014800M00	2397 (1090)	\$ 19,960
EX25H*LB	eMAX 25H Loader & Backhoe**	017030M00	2757 (1253)	\$ 22,750
EX25H*LBM	eMAX 25H Loader, Mower & Backhoe**	021230M00	3107 (1412)	\$ 25,370

\* Different tire options

\*\* Weight less backhoe bucket



# eMax™ 25 HST

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	11105405000	0290M00	\$ 415
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 75
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
eMAX Snow Blower Valve Kit w/o Loader	87509000000	0936M00	\$ 1,340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

eMax 25L	Uninstalled	03000M00	\$ 3,750
----------	-------------	----------	----------

## LOADER ATTACHMENTS

50" Material Bucket Pin-on	87501001001GB	0225M00	\$ 285
----------------------------	---------------	---------	--------

## MID MOWER

eMax 25 M 60" Mid Mower	AEMAHME60 Uninstalled	01850M00	\$ 2,315
-------------------------	-----------------------	----------	----------

## BACKHOE

eMax 25B (Less Bucket)	AEMB63E Uninstalled	04330M00	\$ 5,415
------------------------	---------------------	----------	----------

## BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# eMax™ 25 HST Cab

## Engine

Type.....Four Stroke, Indirect Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....24 [17.9]  
Compression Ratio.....21:1  
Displacement cu-in (cc) .....61.5 (1007)  
Rated Speed .....3000 rpm  
Low Idle RPM.....3230 ± 50 rpm  
High Idle RPM.....1350 ± 50 rpm

## Power Take Off

Type.....Independent  
PTO HP (kW).....19.3 (14.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2893  
Mid PTO RPM at engine RPM  
.....2000 @ 2875

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST  
Number of speeds.....Infinite  
Clutch .....Dry single disc  
Brakes.....Wet disc brake

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic  
Pump output.....4.5 gpm [17.03 liters/min]  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....1,322 lb. (600 kg)

## Operator Station

Cruise Control  
Wide Platform Steps  
Color Coded Controls  
External Mirrors  
Front Wiper w/fluid  
Two front work lights  
Rear work light  
Heater w/temperature control  
12V socket

## Dimensions

Overall Length.....92.5 in. (2,350 mm)  
Overall Width.....50.8 in. (1,290 mm)  
Overall Height.....78.2 in. (1,986 mm)  
Wheelbase .....66.1 in. (1,460 mm)  
Min. Ground Clearance.....8.2 in. (207 mm)  
Turning Radius.....7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6-12 6PR/9.5-16 6PR  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23.1 L)  
Cooling System.....4.9 qts. (4.6 L)  
Engine Oil .....3.4 qts. (3.2 L)  
Transmission and Differential  
.....15.4 qts. (14.5 L)  
Front Axle and Final Drive Case  
.....3.7 qts. (3.5 L)

## Electrical

Battery.....12 Volt, 50 AH 500 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1,870 lb. (850 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
EX254CH*	eMAX 25H Cab (T4)	012500M00	1870 (850)	\$ 17,500
EX254CH*M	eMAX 25H Cab & Mower	014600M00	2220 (1009)	\$ 20,130
EX254CH*L	eMAX 25H Cab Loader	015500M00	2377 (1080)	\$ 21,250
EX254CH*LM	eMAX 25H Cab Loader Mower	017600M00	2727 (1240)	\$ 23,880

\* Different tire options



# eMax™ 25 HST Cab

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	TBD		-
Grille Guard	87501006000	0203M00	\$ 290
Heater for Lower Radiator Hose (eMAX)	L1009300013	050M00	\$ 75
Mulch Kit	AMEMHM647	0279M00	\$ 400

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

eMax 25L	Uninstalled	03000M00	\$ 3,750
----------	-------------	----------	----------

## LOADER ATTACHMENTS

50" Material Bucket Pin- on	875040010016B	0225M00	\$ 285
-----------------------------	---------------	---------	--------

## MID MOWER

eMax 25M 60" Mid Mower	AEMAHME60 Uninstalled	01850M00	\$ 2,315
------------------------	-----------------------	----------	----------

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# Max™ 24 HST

## Engine

Type.....Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....24.4 (18.2)  
Compression Ratio.....22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed.....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

## Power Take Off

Type.....Live  
PTO HP (kW).....19.5 (14.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2376  
Mid PTO RPM at engine RPM (optional)  
.....2000 @ 2556

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type..... Hydrostatic Transmission with Two  
Ranges of Selective Sliding Gears  
Number of speeds.....Infinite  
Clutch.....Dry, Single Disc, Diaphragm Type  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type..... Open center, full live hydraulic with  
position control  
Pump output.....4.6 GPM (17.5 liters/min)  
Category 1, 3 point hitch.... Category 1, with  
check chains  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity.....1400 lb. (636 kg)

## Operator Station

Cruise Control  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
Tool Box (optional)  
Cup holder

## Dimensions

Overall Length.....104.1 in. (2645 mm)  
Overall Width.....50.7 in. (1290 mm)  
Overall Height.....81.5 in. (2070 mm)  
Wheelbase.....58.2 in. (1480 mm)  
Min. Ground Clearance.....5.7 in. (145 mm)  
Turning Radius.....7.2 ft. (2.2 m)

## Tires & Wheels

Ag (Front/Rear).....6x12/9.5x16  
Industrial (Front/Rear)  
.....20x8-10/27x12.5-15  
Turf (Front/Rear)(Standard)  
.....20x8-10/29x12.5-15

## Capacities

Fuel Tank.....6.1 gal. (23 L)  
Cooling System.....5.1 qts. (4.8 L)  
Engine Oil.....4.4 qts. (4.2 L)  
Transmission and Differential  
.....15.9 qts. (15 L)  
Front Axle and Final Drive Case  
.....3.9 qts. (3.7 L)

## Electrical

Battery.....12 Volt, 45 AH 450 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1693 lb. (768 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MX24H*	Max 24 HST (T4)	010600M00	1693 (768)	\$ 14,840
MX24H*M	Max 24 HST & Mower	012900M00	2043 (929)	\$ 17,720
MX24H*L	Max 24 HST Loader	013700M00	2238 (1017)	\$ 18,720
MX24H*LM	Max 24 HST Loader & Mower	016000M00	2588 (1176)	\$ 21,590
MX24H*LB	Max 24 HST Loader Backhoe**	018030M00	3004 (1365)	\$ 23,940
MX24H*LBM	Max 24 HST Loader, Mower & Backhoe**	020330M00	3354 (1525)	\$ 26,820

\* Different tire options

\*\* Weight less backhoe bucket



# Max™ 24 HST

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDM2225	0812M00	\$ 1,160
Grill Guard	KMW15902083	0131M00	\$ 190
Auxiliary Valve Kit	KMW15652122	0686M00	\$ 980
Mulch Kit	AMEMHM647	0279M00	\$ 400
Backhoe Thumb Assembly 6'5"	KMW67051000	0301M00	\$ 430
Block Heater Assembly	19670050000	0241M00	\$ 345

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Max 24L	Uninstalled	03100M00	\$ 3,875
---------	-------------	----------	----------

### LOADER ATTACHMENTS

50" pin on bucket	KMW13003727	0225M00	\$ 300
-------------------	-------------	---------	--------

### MID MOWER

Max 24M 60" Mid Mower*	AEMMX24M Uninstalled	02050M00	\$ 2,560
------------------------	----------------------	----------	----------

### BACKHOE

Max 24B (Less Bucket)	KMWMAX24B Uninstalled	04330M00	\$ 5,225
-----------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" bucket	KMW67021169	0329M00	\$ 415
12" bucket	KMW67021170	0349M00	\$ 440
16" bucket	KMW67021171	0379M00	\$ 475

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.

\* Not compatible with single spool auxiliary valve kit.



# Max™ 26XL 4WD Shuttle

## Engine

Type.....Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....25.6 (19) @ 2500 (T4)  
Compression Ratio..... 22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed .....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

## Power Take Off

Type.....Trans  
PTO HP (kW).....21.5 (16)  
Rear PTO RPM at engine RPM  
.....540 @ 2376  
Mid PTO RPM at engine RPM (optional)  
.....2000 @ 2556

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type.....Constant mesh on gear shift and  
synchro mesh on F/R shuttle  
Number of speeds..... 8F/8R  
Clutch.....Dry Single Disc, Diaphragm Type  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type..... Open center, full live hydraulic with  
position control  
Pump output..... 22.1 liters/min (5.8 GPM)  
Category 1, 3 point hitch.... Category 1, with  
check chains  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity .....2205 lb. (1000 kg)

## Operator Station

Cruise Control  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
Tool Box (optional)  
Cup holder

## Dimensions

Overall Length ..... 109.3 in. (2775 mm)  
Overall Width .....54.3 in. (1380 mm)  
Overall Height .....84.3 in. (2140 mm)  
Wheelbase .....63.2 in. (1605 mm)  
Min. Ground Clearance... 11.4 in. (290 mm)  
Turning Radius.....6.6 ft. (2.0 m)

## Tires & Wheels

Ag (Front/Rear)..... 7x12/9.5x16  
Industrial (Front/Rear)  
.....23x8.5-12/12x16.5  
Turf (Front/Rear)(Standard)  
.....23x8.5-12/33x12.5-16.5

## Capacities

Fuel Tank.....6.1 gal. (23 L)  
Cooling System..... 5.1 qts. (4.8 L)  
Engine Oil ..... 4.4 qts. (4.2 L)  
Transmission and Differential  
.....23 qts. (21.5 L)  
Front Axle and Final Drive Case  
..... 4.2 qts. (4.0 L)

## Electrical

Battery..... 12 Volt, 45 AH 450 CCA  
Alternator..... 12 V 50 A  
Starter Capacity..... 12V, 1.7 KW

## Operating Weight

1819 lb. (827 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MX26G*	Max 26XL Shuttle (T4)	011050M00	1819 (827)	\$ 15,470
MX26G*M	Max 26XL Shuttle, Mower & Mid PTO	014251M00	2169 (986)	\$ 19,590
MX26G*L	Max 26XL Shuttle Loader	014250M00	2446 (1112)	\$ 19,470
MX26G*LM	Max 26XL Shuttle Loader, Mower & Mid PTO	017451M00	2796 (1271)	\$ 23,590
MX26G*LB	Max 26XL Shuttle Loader Backhoe	019180M00	3156 (1435)	\$ 25,640
MX26G*LBM	Max 26XL Shuttle Loader, Backhoe, Mower & Mid PTO	021770M00	3506 (1594)	\$ 29,760

\* Different tire options

## PARTS OPTIONS

Single Spool	SVDM25	0812M00	\$ 1,160
Auxiliary Valve Kit	KMW15652123	0811M00	\$ 1,160
Grill Guard	ANS2516B-4100	0120M00	\$ 175
Mulch Kit	AMEMHM639	0225M00	\$ 325
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
Street Pad Kit for MB63A Backhoe	AMEMHW604	0140M00	\$ 200
Mid PTO Kit	MPM26	0611M00	\$ 875
Block Heater Assembly	19670050000	0241M00	\$ 345

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Max 26 L-SKC Quick Attach Bucket & Grille Guard	Uninstalled	02900M00	\$ 3,625
---	-------------	----------	----------

### LOADER ATTACHMENTS

54" Pin on bucket	MVT25A1000	0350M00	\$ 450
-------------------	------------	---------	--------

### MID MOWER

60" Mid Mower (Must order mid PTO)	AEMMX26M Uninstalled	02340M00	\$ 2,925
------------------------------------	----------------------	----------	----------

### BACKHOE

Max 26B (Less Bucket)	AEMB63AFG Uninstalled	04930M00	\$ 6,165
-----------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

### DEALER INSTALLED CAB

Max 26XL ROPS Cab	A-12104 Uninstalled	03846M00	\$ 4,810
-------------------	---------------------	----------	----------

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# Max™ 26XL 4WD HST

## Engine

Type.....Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....25.6 (19)  
Compression Ratio.....22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed.....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

## Power Take Off

Type.....Live  
PTO HP (kW).....20 (14.9)  
Rear PTO RPM at engine RPM  
.....540 @ 2376  
Mid PTO RPM at engine RPM (optional)  
.....2000 @ 2556

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type.....Hydrostatic Transmission with Two  
Ranges of Selective Sliding Gears  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc, Diaphragm Type  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic with  
position control  
Pump output.....22.1 liters/min (5.8 GPM)  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2205 lb. (1000 kg)

## Operator Station

Cruise Control  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
Tool Box (optional)  
Cup holder

## Dimensions

Overall Length.....109.3 in. (2775 mm)  
Overall Width.....54.3 in. (1380 mm)  
Overall Height.....84.3 in. (2140 mm)  
Wheelbase.....63.2 in. (1605 mm)  
Min. Ground Clearance...11.4 in. (290 mm)  
Turning Radius.....6.6 ft. (2.0 m)

## Tires & Wheels

Ag (Front/Rear).....7x12/9.5x16  
Industrial (Front/Rear)  
.....23x8.5-12/12x16.5  
Turf (Front/Rear)(Standard)  
.....23x8.5-12/33x12.5-16.5

## Capacities

Fuel Tank.....6.1 gal. (23 L)  
Cooling System.....5.1 qts. (4.8 L)  
Engine Oil.....4.4 qts. (4.2 L)  
Transmission and Differential  
.....24 qts. (22.5 L)  
Front Axle and Final Drive Case  
.....4.2 qts. (4.0 L)

## Electrical

Battery.....12 Volt, 45 AH 450 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

1863 lb. (845 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MX26H*	Max 26XL HST (T4)	011900M00	1863 (845)	\$ 16,660
MX26H*M	Max 26XL HST, Mower & Mid PTO	015101M00	2213 (1006)	\$ 20,780
MX26H*L	Max 26XL HST Loader	015100M00	2408 (1095)	\$ 20,660
MX26H*LM	Max 26XL HST Loader, Mower & Mid PTO	018301M00	2758 (1254)	\$ 24,780
MX26H*LB	Max 26XL HST Loader Backhoe	020030M00	3118 (1417)	\$ 26,830
MX26H*LBM	Max 26XL HST Loader, Backhoe, Mower & Mid PTO	022620M00	3468 (1576)	\$ 30,950

\* Different tire options



# Max™ 26XL 4WD HST

## PARTS OPTIONS

Single Spool	SVDM25	0812M00	\$ 1,160
Auxiliary Valve Kit	KMW15652123	0811M00	\$ 1,160
Grill Guard	ANS25168-4100	0120M00	\$ 175
Mulch Kit	AMEMHM639	0225M00	\$ 325
Backhoe Thumb Assembly 6'3"	AMEMHB1637	0459M00	\$ 660
Street Pad Kit for MB63A Backhoe	AMEMHW604	0140M00	\$ 200
Mid PTO Kit	MPM26	0611M00	\$ 875
Block Heater Assembly	19670050000	0241M00	\$ 345

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Max 26 L-SKC Quick Attach Bucket & Grille Guard	Uninstalled	02900M00	\$ 3,625
---	-------------	----------	----------

### LOADER ATTACHMENTS

54" Pin on bucket	MBT25A1000	0350M00	\$ 450
-------------------	------------	---------	--------

### MID MOWER

60" Mid Mower (Must order mid PTO)	AEMMX26M Uninstalled	02340M00	\$ 2,925
------------------------------------	----------------------	----------	----------

### BACKHOE

Max 26B (Less Bucket)	AEMB63AFG Uninstalled	04930M00	\$ 6,165
-----------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

### DEALER INSTALLED CAB

Max 26XL ROPS Cab	A-12104 Uninstalled	03846M00	\$ 4,810
-------------------	---------------------	----------	----------

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# Max™ 26XL 4WD HST Cab

## Engine

Type.....Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....25.6 (19)  
Compression Ratio.....22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed.....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

## Power Take Off

Type.....Live  
PTO HP (kW).....20 (14.9)  
Rear PTO at engine RPM.....540 @ 2376  
Mid PTO at engine RPM (optional)  
.....2000 @ 2556

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type.....Hydrostatic Transmission with Two  
Ranges of Selective Sliding Gears  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc, Diaphragm Type  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full live hydraulic with  
position control  
Pump output.....22.1 liters/min (5.8 GPM)  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2205 lb. (1000 kg)

## Operator Station

Cruise Control  
Wide Platform Steps  
Color Coded Controls  
Front wiper

## Dimensions

Overall Length.....109.3 in. (2775 mm)  
Overall Width.....54.3 in. (1380 mm)  
Overall Height.....82 in. (2082 mm)  
Wheelbase.....63.2 in. (1605 mm)  
Min. Ground Clearance...11.4 in. (290 mm)  
Turning Radius.....6.6 ft. (2.0 m)

## Tires & Wheels

Ag (Front/Rear).....7x12/9.5x16  
Industrial (Front/Rear)  
.....23x8.5-12/12x16.5  
Turf (Front/Rear)(Standard)  
.....23x8.5-12/33x12.5-16.5

## Capacities

Fuel Tank.....6.1 gal. (23 L)  
Cooling System.....5.1 qts. (4.8 L)  
Engine Oil.....3.9 qts. (3.7 L)  
Transmission and Differential  
.....23 qts. (21.5 L)  
Front Axle and Final Drive Case  
.....4.2 qts. (4.0 L)

## Electrical

Battery.....12 Volt, 45 AH 450 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12V, 1.7 KW

## Operating Weight

2857 lb. (1299 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MX26CH*L	Max 26XL HST w/ Loader (T4)	019459M00	2857 (1299)	\$ 27,250
MX26CH*LM	Max 26XL HST Cab w/ Loader, Mower & Mid PTO	022660M00	3207 (1458)	\$ 31,370
MX26CH*LHTR	Max 26XL HST Cab w/ Loader & Heater	020026M00	2858 (1299)	\$ 27,980
MX26CH*LHTRM	Max 26XL HST Cab w/ Loader, Mower, Mid PTO & Heater	023227M00	3208 (1458)	\$ 32,100

\* Different tire options

\*\* Weight less backhoe bucket

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDM25	0812M00	\$ 1,160
Grill Guard	ANS2516B-4100	0120M00	\$ 175
Mulch Kit	AMEMHM639	0225M00	\$ 325
Block Heater Assembly	19670050000	0241M00	\$ 345
Mid PTO Kit	MPM26	0611M00	\$ 875
Cab Heater Kit	L1009600001	0506M00	\$ 725
Cab Front Work Light Kit	L1009600002	0226M00	\$ 325
Cab Warning Beacon Kit	L1009600003	0158M00	\$ 230
Cab Defroster Fan Kit	L1009600005	090M00	\$ 130
Cab Rear Light Kit	L1009600006	0132M00	\$ 190
Cab Exterior Mirror Kit	L1009600007	0120M00	\$ 175
Cab Rear Wiper Kit	L1009600008	0235M00	\$ 340

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

This Tractor must have a LOADER.

### LOADER ATTACHMENTS

54" Pin on bucket	MBT25A1000	0350M00	\$ 450
-------------------	------------	---------	--------

### MID MOWER

60" Mid Mower (Must order mid PTO)	AEMMX26M Uninstalled	02340M00	\$ 2,925
------------------------------------	----------------------	----------	----------

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 1526 Shuttle

### Engine

Type.....Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....25.6 (19)  
Compression Ratio.....22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed.....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

### Power Take Off

Type.....Independent  
PTO HP (kW).....19 (14.2)  
Rear PTO.....540 @ 2376  
Mid PTO (optional).....2000 @ 2525

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

### Drive Train

Type.....Synchronesh on Shuttle and  
main Gear Shift of constant mesh  
Number of speeds.....8F/8R  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center, Full Live hydraulic  
Implement pump output  
.....7.5 gal/min (28.5 liters/min)  
Steering pump output  
.....3.4 gal/min (12.8 liters/min)  
Maximum total flow  
.....10.9 gal/min (41.3 liters/min)  
Category 1, 3 point hitch....Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2646 lb. (1203 kg)

### Operator Station

Wide Platform Steps  
Color Coded Controls  
Toolbox

### Dimensions

Overall Length.....121.3 in. (3080 mm)  
Overall Width.....63 in. (1600 mm)  
Overall Height.....81.5 in. (2069 mm)  
Wheelbase.....67.3 in. (1710 mm)  
Min. Ground Clearance...11.4 in. (290 mm)  
Turning Radius.....7.9 ft. (2.4 m)

### Tires & Wheels

Ag (Front/Rear).....7x16/11.2x24  
Industrial (Front/Rear)  
.....27x8.5-15/15x19.5  
Turf (Front/Rear)(Standard)  
.....25x8.5-14/13.6x16

### Capacities

Fuel Tank.....7.1 gal. (27 L)  
Cooling System.....5.8 qts. (5.5 L)  
Engine Oil.....4.4 qts. (4.2 L)  
Transmission and Differential  
.....34.8 qts. (33 L)  
Front Axle and Final Drive Case  
.....4.2 qts. (4 L)

### Electrical

Battery.....12 Volt, 46 AH 540 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12 V, 1.7 KW

### Operating Weight

2437 lbs. (1105 kg)

MATERIAL CODE	DESCRIPTION**	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15264FS*	1526 Shuttle (T4)	012100M00	2437 (1105)	\$ 16,340
15264FS*M	1526 Shuttle, Mower*** & Mid PTO	015801M00	2877 (1308)	\$ 21,080
15264FS*L	1526 Shuttle Loader	015450M00	3217 (1462)	\$ 20,530
15264FS*LM	1526 Shuttle Loader, Mower*** & Mid PTO	019151M00	3667 (1667)	\$ 25,270
15264FS*LB	1526 Shuttle Tractor, Loader & Backhoe	020230M00	4202 (1910)	\$ 26,510

\* Different tire options  
\*\* Mower and backhoe not compatible together  
\*\*\* Mid-mower not compatible with ag tires

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDM2836	0690M00	\$ 990
Auxiliary Valve Kit	UNDER DEVELOPMENT		
Grill Guard	KMW15902079	0198M00	\$ 290
Ballast Box	KMW16011140	0612M00	\$ 880
Mid PTO	MPM1526	0611M00	\$ 880
Mulch Kit	AMEMHM742	0272M00	\$ 390
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	19670050000	0241M00	\$ 350

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Loader w/bucket for 1526	KMWML1526L	03350M00	\$ 4,190
--------------------------	------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	KMW13003793	0375M00	\$ 470
--------------------------------	-------------	---------	--------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1672N	02840M00	\$ 3,550
------------------------------------	------------	----------	----------

### BACKHOE

1526 B (Less Bucket)	KMW1526B	04780M00	\$ 5,980
----------------------	----------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	KMW67021169	0329M00	\$ 420
12" Bucket	KMW67021170	0349M00	\$ 440
16" Bucket	KMW67021171	0379M00	\$ 480

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.

### Engine

Type..... Tier IV, 3 Cylinders, Four Cycle,  
Valve in Cylinder Head, Naturally  
Aspirated, Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....25.6 (19)  
Compression Ratio.....22:1  
Displacement cu-in (cc).....80.4 (1318)  
Rated Speed.....2500  
Low Idle RPM.....2680 to 2720  
High Idle RPM.....970 to 1000

### Power Take Off

Type..... Live w/ORC  
PTO HP (kW).....18.5 (13.8)  
Rear PTO.....540 @ 2376  
Mid PTO (optional).....2000 @ 2525

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

### Drive Train

Type.....Hydrostatic - 3 Ranges  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center, Full Live hydraulic  
Implement pump output  
.....7.5 gal/min (28.5 liters/min)  
Steering pump output  
.....3.4 gal/min (12.8 liters/min)  
Maximum total flow  
.....10.9 gal/min (41.3 liters/min)  
Category 1, 3 point hitch....Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2646 lb. (1203 kg)

### Operator Station

Cruise Control  
6 Pin Pocket (optional)  
Debris Shield  
Wide Platform Steps  
Color Coded Controls  
Toolbox

### Dimensions

Overall Length.....121.3 in. (3080 mm)  
Overall Width.....63 in. (1600 mm)  
Overall Height.....81.5 in. (2069 mm)  
Wheelbase.....67.3 in. (1710 mm)  
Min. Ground Clearance...11.4 in. (290 mm)  
Turning Radius.....7.9 ft. (2.4 m)

### Tires & Wheels

Ag (Front/Rear).....7x16/11.2x24  
Industrial (Front/Rear)  
.....27x8.5-15/15x19.5  
Turf (Front/Rear)[Standard]  
.....25x8.5-14/13.6x16

### Capacities

Fuel Tank.....7.1 gal. (27 L)  
Cooling System.....5.8 qts. (5.5 L)  
Engine Oil.....4.4 qts. (4.2 L)  
Transmission and Differential  
.....36 qts. (34 L)  
Front Axle and Final Drive Case  
.....4.2 qts. (4 L)

### Electrical

Battery.....12 Volt, 46 AH 540 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12 V, 1.7 KW

### Operating Weight

2459 lbs. (1115 kg)

MATERIAL CODE	DESCRIPTION**	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15264FH*	1526 HST (T4)	012950M00	2459 (1115)	\$ 17,490
15264FH*M	1526 HST, Mower*** & Mid PTO	016651M00	2899 (1318)	\$ 22,230
15264FH*L	1526 HST Loader	016300M00	3239 (1472)	\$ 21,680
15264FH*LM	1526 HST Loader, Mower*** & Mid PTO	020001M00	3689 (1677)	\$ 26,420
15264FH*LB	1526 HST Tractor, Loader & Backhoe	021080M00	4224 (1920)	\$ 27,660

\* Different tire options

\*\* Mower and backhoe not compatible together

\*\*\* Mid-mower not compatible with ag tires

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDM2836	0690M00	\$ 990
Auxiliary Valve Kit	UNDER DEVELOPMENT		
Grill Guard	KMW15902079	0198M00	\$ 290
Ballast Box	KMW16011140	0612M00	\$ 880
Mid PTO	MPM1526	0611M00	\$ 880
Mulch Kit	AMEMHM742	0272M00	\$ 390
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	19670050000	0241M00	\$ 350

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

Loader w/bucket for 1526	KMWML1526L	03350M00	\$ 4,190
--------------------------	------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	KMW13003793	0375M00	\$ 470
--------------------------------	-------------	---------	--------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1672N	02840M00	\$ 3,550
------------------------------------	------------	----------	----------

### BACKHOE

1526 B (Less Bucket)	KMW1526B	04780M00	\$ 5,980
----------------------	----------	----------	----------

### BACKHOE BUCKET OPTIONS


10" Bucket	KMW67021169	0329M00	\$ 420
12" Bucket	KMW67021170	0349M00	\$ 440
16" Bucket	KMW67021171	0379M00	\$ 480

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....34.5 (25.7)  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc)..... 166.7 (2732)  
Rated Speed.....2400  
Low Idle RPM.....970 to 1030 RPM  
High Idle RPM.....2570 to 2630 RPM

### Power Take Off

Type.....Independent  
PTO HP (kW).....25.2 (18.8)  
Rear PTO.....540 rpm  
Mid PTO (optional).....2000 rpm

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

### Drive Train

Type.....Synchronesh  
Number of speeds.....8F/8R  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center, Full Live hydraulic  
Pump output.....29 liters/min {7.7GPM}  
Category 1, 3 point hitch.... Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity.....2646 lb. {1203 kg}

### Operator Station

6 Pin Pocket (optional)  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
Toolbox

### Dimensions

Overall Length.....127.8 in. (3245 mm)  
Overall Width.....63 in. (1600 mm)  
Overall Height.....90.2 in. (2290 mm)  
Wheelbase.....76.9 in. (1954 mm)  
Min. Ground Clearance...12.2 in. (310 mm)  
Turning Radius.....9.2 ft. (2.8 m)

### Tires & Wheels

Ag (Front/Rear).....7x16/11.2x24  
Industrial (Front/Rear)  
.....27x8.5-15/15x19.5  
Turf (Front/Rear)(Standard)  
.....25x8.5-14/13.6x16

### Capacities

Fuel Tank.....7.7 gal. (29 L)  
Cooling System.....5.8 qts. (5.5 L)  
Engine Oil.....6.7 qts. (6.3 L)  
Transmission and Differential  
.....32.8 qts. (31 L)  
Front Axle and Final Drive Case  
.....4.9 qts. (4.6 L)

### Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12V, 2.2 KW

### Operating Weight

3175 lb. (1440 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15334FS*	1533 Shuttle (T4)	015300M00	3175 (1440)	\$ 20,660
15334FS*M	1533 Shuttle, Mower & Mid PTO	018632M00	3625 (1648)	\$ 25,400
15334FS*L	1533 Shuttle Loader	019050M00	3955 (1798)	\$ 25,350
15334FS*LM	1533 Shuttle Loader, Mower & Mid PTO	022382M00	4405 (2002)	\$ 30,090
15334FS*LB	1533 Shuttle Tractor, Loader & Backhoe**	024650M00	5226 (2375)	\$ 32,350

\* Different tire options

\*\* Weight less backhoe bucket



# 1533 Shuttle

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDMT43338	0690M00	\$ 990
Grill Guard	KMW15902095	0214M00	\$ 310
Mid PTO	MPMT43338	0611M00	\$ 875
Mulch Kit	AMEMHM728	0242M00	\$ 350
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902096	01181M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

1538L w/ SKC Quick Attach Bucket & Grille Guard	Uninstalled	03750M00	\$ 4,690
---	-------------	----------	----------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1538M Uninstalled	02840M00	\$ 3,550
------------------------------------	------------------------	----------	----------


### BACKHOE

1538 B (Less Bucket)	KMW1538B Uninstalled	05600M00	\$ 7,000
----------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	KMW67021047	0329M00	\$ 415
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 475
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....34.5 (25.7)  
Compression Ratio.....18.7:1  
Displacement cu-in (cc).....166.7 (2732)  
Rated Speed.....2400  
Low Idle RPM.....2570 to 2630  
High Idle RPM.....970 to 1030

### Power Take Off

Type.....Live  
PTO HP (kW).....24.7 (18.4)  
Rear PTO.....540 rpm  
Mid PTO (optional).....2000 rpm

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

### Drive Train

Type.....Hydrostatic - 3 Ranges  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

### Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center, Full Live hydraulic  
Pump output.....29 liters/min (7.7GPM)  
Category 1, 3 point hitch.....Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2646 lb. (1203 kg)

### Operator Station

Cruise Control  
6 Pin Pocket (optional)  
Debris Shield  
Wide Platform Steps  
Color Coded Controls  
Toolbox

### Dimensions

Overall Length.....127.8 in. (3245 mm)  
Overall Width.....63 in. (1600 mm)  
Overall Height.....90.2 in. (2290 mm)  
Wheelbase.....76.9 in. (1954 mm)  
Min. Ground Clearance...12.2 in. (310 mm)  
Turning Radius.....9.2 ft. (2.8 m)

### Tires & Wheels

Ag (Front/Rear).....7x16/11.2x24  
Industrial (Front/Rear)  
.....27x8.5-15/15x19.5  
Turf (Front/Rear)[Standard]  
.....25x8.5-14/13.6x16

### Capacities

Fuel Tank.....7.7 gal. (29 L)  
Cooling System.....5.8 qts. (5.5 L)  
Engine Oil.....6.7 qts. (6.3 L)  
Transmission and Differential  
.....34.8 qts. (33 L)  
Front Axle and Final Drive Case  
.....4.9 qts. (4.6 L)

### Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12 V, 2.2 KW

### Operating Weight

3164 lbs. (1438 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15334FH*	1533 HST (T4)	016300M00	3164 (1438)	\$ 22,010
15334FH*M	1533 HST, Mower & Mid PTO	019632M00	3614 (1643)	\$ 23,380
15334FH*L	1533 HST Loader	020050M00	3944 (1793)	\$ 26,700
15334FH*LM	1533 HST Loader, Mower & Mid PTO	023382M00	4394 (1977)	\$ 28,070
15334FH*LB	1533 HST Tractor, Loader & Backhoe**	025650M00	5215 (2370)	\$ 30,250

\* Different tire options  
\*\* Weight less backhoe bucket

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDMT43338	0690M00	\$ 990
Grill Guard	KMW15902095	0214M00	\$ 310
Mid PTO	MPMT43338	0611M00	\$ 875
Mulch Kit	AMEMHM728	0242M00	\$ 350
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902096	01181M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

1538L w/ SKC Quick Attach Bucket & Grille Guard	Uninstalled	03750M00	\$ 4,690
---	-------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	KMW13003793	0375M00	\$ 490
--------------------------------	-------------	---------	--------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1538M Uninstalled	02840M00	\$ 3,550
------------------------------------	------------------------	----------	----------

### BACKHOE

1538 B (Less Bucket)	KMW1538B Uninstalled	05600M00	\$ 7,000
----------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	KMW67021047	0329M00	\$ 415
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 475
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 1538 Shuttle



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....38.7 (28.9)  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc)..... 166.7 (2732)  
Rated Speed..... 2400  
Low Idle RPM.....2570 to 2630  
High Idle RPM.....970 to 1030

## Power Take Off

Type.....Independent  
PTO HP (kW).....29.9 (22.3)  
Rear PTO.....540 rpm  
Mid PTO (optional).....2000 rpm

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type.....Synchromesh on Shuttle and  
main Gear Shift of constant mesh  
Number of speeds..... 8F/8R  
Clutch .....Dry Single Disc  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center, Full Live hydraulic  
Pump output..... 29 liters/min (7.7GPM)  
Category 1, 3 point hitch ....Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity .....2646 lb. (1203 kg)

## Operator Station

6 Pin Pocket (optional)  
Debris Shield  
Wide Platform Steps  
Color Coded Controls  
Toolbox

## Dimensions

Overall Length..... 127.8 in. (3245 mm)  
Overall Width .....62 in. (1575 mm)  
Overall Height.....91.5 in. (2325 mm)  
Wheelbase .....76.9 in. (1954 mm)  
Min. Ground Clearance... 12.8 in. (325 mm)  
Turning Radius.....9.2 ft. (2.8 m)

## Tires & Wheels

Ag (Front/Rear)..... 7x16/11.2x24  
Industrial (Front/Rear)  
..... 28x8.5-15/43x16-20  
Turf (Front/Rear)(Standard)  
..... 27x10.5-15/41x14-20

## Capacities

Fuel Tank.....7.7 gal. (29 L)  
Cooling System ..... 5.8 qts. (5.5 L)  
Engine Oil ..... 6.7 qts. (6.3 L)  
Transmission and Differential  
..... 32.8 qts. (31 L)  
Front Axle and Final Drive Case  
..... 4.9 qts. (4.6 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 90 A  
Starter Capacity..... 12 V, 2.2 KW

## Operating Weight

3186 lbs. (1448 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15384FS*	1538 Shuttle (T4)	017400M00	3186 (1448)	\$ 23,490
15384FS*M	1538 Shuttle, Mower & Mid PTO	020732M00	3636 (1653)	\$ 24,860
15384FS*L	1538 Shuttle Loader	021150M00	3966 (1803)	\$ 28,180
15384FS*LM	1538 Shuttle Loader, Mower & Mid PTO	024482M00	4416 (2007)	\$ 29,550
15384FS*LB	1538 Shuttle Tractor, Loader & Backhoe**	026750M00	5237 (2380)	\$ 31,730

\* Different tire options

\*\* Weight less backhoe bucket



# 1538 Shuttle

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDMT43338	0690M00	\$ 990
Grill Guard	KMW15902095	0214M00	\$ 310
Mid PTO	MPMT43338	0611M00	\$ 875
Mulch Kit	AMEMHM728	0242M00	\$ 350
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902096	01181M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

<b>LOADER</b>			
1538L w/ SKC Quick Attach Bucket & Grille Guard	Uninstalled	03750M00	\$ 4,690

<b>LOADER ATTACHMENTS</b>			
60" Material Bucket Skid Steer	KMW13003793	0375M00	\$ 490

<b>MID MOWER</b>			
72" Mid Mower (Must order mid PTO)	AEMAH1538M Uninstalled	02840M00	\$ 3,550


<b>BACKHOE</b>			
1538 B (Less Bucket)	KMW1538B Uninstalled	05600M00	\$ 7,000

<b>BACKHOE BUCKET OPTIONS</b>			
10" Bucket	KMW67021047	0329M00	\$ 415
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 475
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 1538 HST



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....38.7 [28.9]  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc)..... 166.7 (2732)  
Rated Speed .....2400  
Low Idle RPM.....2570 to 2630  
High Idle RPM.....970 to 1030

### Power Take Off

Type.....Live  
PTO HP (kW).....27.7 [20.6]  
Rear PTO.....540 rpm  
Mid PTO (optional).....2000 rpm

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

### Drive Train

Type.....Hydrostatic - 3 Ranges  
Number of speeds.....Infinite  
Clutch .....Dry Single Disc  
Brakes.....Wet Disc  
Front Axle  
Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center, Full Live hydraulic  
Pump output..... 29 liters/min (7.7GPM)  
Category 1, 3 point hitch.... Category 1, with  
telescoping stabilizers  
Rear Auxiliary Valves..... 1 spool optional  
Lift capacity .....2646 lb. (1203 kg)

### Operator Station

Cruise Control!  
6 Pin Pocket (optional)  
Debris Shield  
Wide Platform Steps  
Color Coded Controls  
Toolbox

### Dimensions

Overall Length ..... 127.8 in. (3245 mm)  
Overall Width ..... 62 in. (1575 mm)  
Overall Height.....91.5 in. (2325 mm)  
Wheelbase .....76.9 in. (1954 mm)  
Min. Ground Clearance... 12.8 in. (325 mm)  
Turning Radius.....9.2 ft. (2.8 m)

### Tires & Wheels

Ag (Front/Rear).....7x16/11.2x24  
Industrial (Front/Rear)  
.....28x8.5-15/43x16-20  
Turf (Front/Rear)[Standard]  
.....27x10.5-15/41x14-20

### Capacities

Fuel Tank.....7.7 gal. (29 L)  
Cooling System..... 5.8 qts. (5.5 L)  
Engine Oil..... 6.7 qts. (6.3 L)  
Transmission and Differential  
..... 34.8 qts. (33 L)  
Front Axle and Final Drive Case  
..... 4.9 qts. (4.6 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 90 A  
Starter Capacity..... 12 V, 2.2 KW

### Operating Weight

3175 lbs. (1440 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15384HS*	1538 HST (T4)	018400M00	3175 (1440)	\$ 24,840
15384HS*M	1538 HST, Mower & Mid PTO	021732M00	3625 (1648)	\$ 25,720
15384HS*L	1538 HST Loader	022150M00	3955 (1798)	\$ 24,840
15384HS*LM	1538 HST Loader, Mower & Mid PTO	025482M00	4405 (2002)	\$ 25,720
15384HS*LB	1538 HST Tractor, Loader & Backhoe**	027750M00	5226 (2375)	\$ 28,700

\* Different tire options

\*\* Weight less backhoe bucket

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDMT43338	0690M00	\$ 990
Grill Guard	KMW15902095	0214M00	\$ 310
Mid PTO	MPMT43338	0611M00	\$ 875
Mulch Kit	AMEMHM728	0242M00	\$ 350
Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902096	01181M00	\$ 1,690

Available through Parts Department: 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

1538L w/ SKC Quick Attach Bucket & Grille Guard	Uninstalled	03750M00	\$ 4,690
---	-------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	KMW13003793	0375M00	\$ 490
--------------------------------	-------------	---------	--------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1538M Uninstalled	02840M00	\$ 3,550
------------------------------------	------------------------	----------	----------

### BACKHOE

1538 B (Less Bucket)	KMW1538B Uninstalled	05600M00	\$ 7,000
----------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	KMW67021047	0329M00	\$ 415
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 475
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 1538 HST Cab



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....38.7 (28.9)  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc)..... 166.7 (2732)  
Rated Speed.....2400  
Low Idle RPM.....2570 to 2630  
High Idle RPM.....970 to 1030

## Power Take Off

Type.....Live  
PTO HP (kW).....27.7 (20.6)  
Rear PTO RPM at engine rpm  
.....540 @ 2376  
Mid PTO RPM at engine rpm (optional)  
.....2000 @ 2525

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge

## Drive Train

Type.....Hydrostatic - 3 Ranges  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center, Full Live hydraulic  
Pump output..... 29 liters/min (7.7GPM)  
Category 1, 3 point hitch....Category 1, with  
check chains  
Rear Auxillary Valves..... 1 spool optional  
Lift capacity .....2646 lb. (1203 kg)

## Operator Station

Cruise Control  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
Dome Light  
Radio Ready  
Front/Rear wipers  
Two worklights F/R

## Dimensions

Overall Length .....127.8 in. (3245 mm)  
Overall Width.....62 in. (1575 mm)  
Overall Height.....91.5 in. (2325 mm)  
Wheelbase .....76.9 in. (1954 mm)  
Min. Ground Clearance... 12.8 in. (325 mm)  
Turning Radius..... 9.2 ft. (2.8 m)

## Tires & Wheels

Ag (Front/Rear)..... 7x16/11.2x24  
Industrial (Front/Rear)  
..... 28x8.5-15/43x16-20  
Turf (Front/Rear)(Standard)  
..... 27x10.5-15/41x14-20

## Capacities

Fuel Tank.....7.7 gal. (29 L)  
Cooling System..... 7.7 qts. (7.3 L)  
Engine Oil..... 6.7 qts. (6.3 L)  
Transmission and Differential  
..... 34.8 qts. (33 L)  
Front Axle and Final Drive Case  
..... 4.9 qts. (4.6 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 90 A  
Starter Capacity..... 12 V, 2.2 KW

## Operating Weight

3627 lb. (1649 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
15384CH*	1538 HST Cab (T4)	024050M00	3627 (1649)	\$ 32,470
15384CH*M	1538 HST Cab, Mower & Mid PTO	027382M00	4077 (1853)	\$ 33,350
15384CH*L	1538 HST Cab Loader	027950M00	4407 (2003)	\$ 32,470
15384CH*LM	1538 HST Cab Loader, Mower & Mid PTO	031282M00	4857 (2208)	\$ 33,350
15384CH*LB	1538 HST Cab Loader & Backhoe**	033400M00	5217 (2371)	\$ 36,330

\* Different tire options

\*\* Weight less backhoe bucket



# 1538 HST Cab

## PARTS OPTIONS

Single Spool Auxiliary Valve Kit	SVDMT438C	0690M00	\$ 990
Grille Guard	KMW15902095	0214M00	\$ 310
Mid PTO	MPMT43338	0611M00	\$ 875
Mulch Kit	AMEMHM728	0242M00	\$ 350
Backhoe Thumb Assembly 6.5'	AMEMHB1603	0493M00	\$ 705
Block Heater Assembly	TISGE360	084M00	\$ 120
Street Pad Kit for 1538 CB 6.5 backhoe	AMEMHW604	0140M00	\$ 200
Third Function Diverter Valve Kit	KMW15902096	01181M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

1538L w/ SKC Quick Attach Bucket & Grille Guard	Uninstalled	03900M00	\$ 4,875
---	-------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	KMW13003739	0375M00	\$ 490
--------------------------------	-------------	---------	--------

### MID MOWER

72" Mid Mower (Must order mid PTO)	AEMAH1538 Uninstalled	02840M00	\$ 3,550
------------------------------------	-----------------------	----------	----------

### BACKHOE

1538 CB (Less Bucket)	AEMAH1538 CB Uninstalled	05450M00	\$ 6,815
-----------------------	--------------------------	----------	----------

### BACKHOE BUCKET OPTIONS

8" Bucket	AEMHW166	0299M00	\$ 375
12" Bucket	AEMHW167	0349M00	\$ 440
16" Bucket	AEMHW168	0379M00	\$ 475

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 2538 4WD HST



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....37.4 (27.5)  
Compression Ratio..... 18.7 ± 0.7:1  
Displacement cu-in (cc)..... 167(2732)  
Rated Speed .....2400  
Low Idle rpm .....2600  
High Idle rpm ..... 1000

### Power Take Off

Type.....Independent  
PTO HP (kW).....31 (23.1)  
Rear PTO RPM at engine RPM  
.....540 @ 2400

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....HST - 3 range  
Number of speeds.....Infinite  
Clutch..... Damper  
Brakes.....Wet Disc

### Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center with position control  
Implement pump output  
.....7.6 GPM (28.8 L/min)  
Steering pump output  
.....4.1 GPM (15.6 L/min)  
Maximum total flow  
..... 11.7 GPM (44.2 L/min)  
Category 1, 3 point hitch..... Category 1 with  
check chains  
Rear Auxillary Valves..... 1 spool optional  
Lift Capacity..... 2646 lb.

### Operator Station

7 Pin Pocket (optional)  
Cruise Control (optional)  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

### Dimensions

Overall Length.....119.3 in. (3030 mm)  
Overall Width.....59.8 in. (1520 mm)  
Overall Height.....94.4 in. (2400 mm)  
Wheelbase.....67.7 in. (1720 mm)  
Min. Ground Clearance... 12.8 in. (325 mm)  
Turning Radius.....7.87 ft. (2.4 m)

### Tires & Wheels

Ag (Front/Rear).....7-16/11.2-24  
Industrial (Front/Rear)  
.....10-16.5/43x16-20

### Capacities

Fuel Tank.....9.0 gal. (34 L)  
Cooling System..... 7.4 qts. (7 L)  
Engine Oil..... 6 qts. (5.7 L)  
Transmission and Differential  
..... 34 qts. (32 L)  
Front Axle and Final Drive Case  
..... 8.7 qts. (8.2 L)

### Electrical

Battery..... 12 Volt, 80 AH 800 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12V, 2.2 KW

### Operating Weight

3130 lb. (1420 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25384FH*	2538 HST (T4)	015400M00	3285 (1493)	\$ 20,790
25384FH*L	2538 HST Loader	019150M00	4270 (1941)	\$ 25,480
25384FH*LB	2538 HST Loader & Backhoe**	024300M00	5541 (2519)	\$ 31,920

\* Different tire options  
\*\* Weight less backhoe bucket



# 2538 4WD HST



## PARTS OPTIONS

First Spool Kit	12665082000	0479M00	\$ 690
Second Spool Kit	12665084000	0588M00	\$ 840
Grille Guard	85711006000	0191M00	\$ 280
Mechanical Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Aux. Exterior Float Valve	12285080940	0317M00	\$ 460
Trailer Socket Kit	12386410000	025M00	\$ 35
RH Foot Step Kit	12386310000	028M00	\$ 40
Cruise Control Kit	12386210000	0122M00	\$ 180
Mid PTO Kit (Not available until Oct. 2015)	12382700000	0234M00	\$ 340
Third Function Kit	85706000000	0876M00	\$ 1,260

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

<b>LOADER</b>			
2538L w/ SKC quick attach bucket and grille guard	TYMML2538L	03750M00	\$ 4,690

<b>LOADER ATTACHMENTS</b>			
66" Material Bucket Skid Steer	KMW13003793	0475M00	\$ 590

<b>BACKHOE</b>			
2538B - 7'6" Digging Depth (Less Bucket)	KMW2538B	05150M00	\$ 6,440

<b>BACKHOE BUCKET OPTIONS</b>			
10" Bucket	KMW67021047	0329M00	\$ 420
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 480
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....37.4 (27.5)  
Compression Ratio.....18.7 ± 0.7:1  
Displacement cu-in (cc).....167(2732)  
Rated Speed.....2400  
Low Idle rpm.....2600  
High Idle rpm.....1000

### Power Take Off

Type.....Independent  
PTO HP (kW).....29.5 (22)  
Rear PTO RPM at engine RPM  
.....540 @ 2400

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

ROPS Cab w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....HST - 3 range  
Number of speeds.....Infinite  
Clutch.....Damper  
Brakes.....Wet Disc

### Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center with position control  
Implement pump output  
.....7.6 GPM (28.8 L/min)  
Steering pump output  
.....4.1 GPM (15.6 L/min)  
Maximum total flow  
.....11.7 GPM (44.2 L/min)  
Category 1, 3 point hitch.....Category 1 with  
check chains  
Rear Auxillary Valves.....1 spool optional  
Lift Capacity.....2646 lb.

### Operator Station

7 Pin Pocket (optional)  
Wide Platform Steps  
Color Coded Controls  
Exterior Mirrors  
Cupholder  
2 Tool Trays  
Roof Vent  
2 F/R Worklights  
Dome Light  
Adjustable suspension seat

### Dimensions

Overall Length.....121.2 in. (3080 mm)  
Overall Width.....59.8 in. (1520 mm)  
Overall Height.....92.5 in. (2350 mm)  
Wheelbase.....67.7 in. (1720 mm)  
Min. Ground Clearance...12.8 in. (325 mm)  
Turning Radius.....7.87 ft. (2.4 m)

### Tires & Wheels

Ag (Front/Rear).....7-16/11.2-24  
Industrial (Front/Rear)  
.....10-16.5/43x16-20

### Capacities

Fuel Tank.....9.0 gal. (34 L)  
Cooling System.....7.6 qts. (7 L)  
Engine Oil.....6 qts. (5.7 L)  
Transmission and Differential  
.....34 qts. (32 L)  
Front Axle and Final Drive Case  
.....8.7 qts. (8.2 L)

### Electrical

Battery.....12 Volt, 80 AH 800 CCA  
Alternator.....12 V 45 A  
Starter Capacity.....12V, 2.2 KW

### Operating Weight

3351 lb. (1520 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25384CH*	2538 HST Cab (T4)	020900M00	3351 (1520)	\$ 28,220
25384CH*L	2538 HST Cab Loader	024650M00	4332 (1965)	\$ 32,910
25384CH*LB	2538 HST Cab Loader & Backhoe**	029800M00	5603 (2543)	\$ 39,350

\* Different tire options

\*\* Weight less backhoe bucket



## PARTS OPTIONS

First Spool Kit	12665082000	0479M00	\$ 690
Second Spool Kit	12665084000	0588M00	\$ 840
Grille Guard	85711006000	0191M00	\$ 280
Mechanical Thumb Kit	KMW67051001	0301M00	\$ 430
Block Heater Assembly	TISGE360	084M00	\$ 120
Aux. Exterior Float Valve	12285080940	0317M00	\$ 460
Trailer Socket Kit	12386410000	025M00	\$ 40
RH Foot Step Kit	12386310000	028M00	\$ 40
Cruise Control Kit	12386210000	0122M00	\$ 180
Mid PTO Kit (Not available until Oct. 2015)	12382700000	0234M00	\$ 340
Third Function Kit	85706000000	0876M00	\$ 1,260

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

2538L w/ SKC quick attach bucket and grille guard	TYMML2538L	03750M00	\$ 4,690
---	------------	----------	----------

### LOADER ATTACHMENTS

66" Material Bucket Skid Steer	KMW13003793	0475M00	\$ 590
--------------------------------	-------------	---------	--------

### BACKHOE

2538B (Less Bucket)	KMW2538B	05150M00	\$ 6,440
---------------------	----------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	KMW67021047	0329M00	\$ 420
12" Bucket	KMW67021048	0349M00	\$ 440
16" Bucket	KMW67021049	0379M00	\$ 480
20" Bucket	KMW67021050	0399M00	\$ 500

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 2540 Shuttle



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....40 (29.83)  
Compression Ratio..... 18.7 ± 0.7:1  
Displacement cu-in (cc).....167 (2732)  
Rated Speed .....2600  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....35 (26.1)  
Rear PTO RPM at engine RPM  
.....540 @ 2650

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Synchro mesh  
Number of speeds.....12F/12R  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc

## Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center with position control  
Pump output.....8.2 GPM (31 L/min)  
Category 1, 3 point hitch.....Category 1 with  
check chains  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....2646 lb.

## Operator Station

7 Pin Pocket  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length .....119.3 in. (3030 mm)  
Overall Width .....59.8 in. (1520 mm)  
Overall Height.....94.4 in. (2400 mm)  
Wheelbase .....68.8 in. (1747 mm)  
Min. Ground Clearance....128 in. (325 mm)  
Turning Radius.....7.87 ft. (2.4 m)

## Tires & Wheels

Ag (Front/Rear).....8.3x16/12.4x24  
Industrial (Front/Rear)  
.....10-16.5/43x16-20

## Capacities

Fuel Tank.....9.0 gal. (34 L)  
Cooling System.....7.4 qts. (7 L)  
Engine Oil.....8 qts. (7.5 L)  
Transmission and Differential  
.....37.1 qts. (35 L)  
Front Axle and Final Drive Case  
.....8.7 qts. (8.2 L)

## Electrical

Battery.....12 Volt, 80 AH 800 CCA  
Alternator.....12 V 50 A  
Starter Capacity.....12 V, 2.2 KW

## Operating Weight

3285 lb. (1493 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25404FS*	2540 Shuttle (T4)	017200M00	3285 (1493)	\$ 23,220
25404FS*L	2540 Shuttle Loader	021800M00	4462 (2028)	\$ 28,970
25404FS*LB	2540 Shuttle Loader & Backhoe**	027070M00	5831 (2650)	\$ 35,560

\* Different tire options

\*\* Weight less backhoe bucket



# 2540 Shuttle



PARTS OPTIONS			
First Spool Kit	12665082000	0479M00	\$ 685
Second Spool Kit	12665084000	0588M00	\$ 840
Grille Guard	85711006000	0191M00	\$ 275
Mechanical Thumb Kit	ANSANMTK7686	0583M00	\$ 835
Block Heater Assembly	TISGE360	084M00	\$ 120
Aux. Exterior Float Valve	12285080940	0317M00	\$ 455
Third Function Kit	85706000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

2540 L w/ SKC quick attach bucket and grille guard	Uninstalled	04300M00	\$ 5,375
--	-------------	----------	----------

### LOADER ATTACHMENTS

66" Material Bucket, Skid Steer		0475M00	\$ 610
---------------------------------	--	---------	--------

### BACKHOE

2540B w/ 16" bucket	ANBH2540B Uninstalled	05270M00	\$ 6,590
---------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	ANBKT12	0349M00	\$ 440
16" Bucket	ANBKT16	0379M00	\$ 475
24" Bucket	ANBKT24	0419M00	\$ 525

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 2555 Shuttle



### Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kw).....55 (41)  
Compression Ratio.....17.2:1  
Displacement cu-in (cc).....2648  
Rated Speed.....2300  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

### Power Take Off

Type.....Independent  
PTO HP (kW).....44.5 (32.7)  
Rear PTO RPM at engine RPM  
.....540 @ 2300

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Sync, shuttle w/part synchromesh  
Number of speeds.....12F/12R  
Clutch.....Diaphragm  
Brakes.....Wet Disc Brake, Mechanical

### Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open Center with position control  
Pump output.....9.5 GPM (36.1 L/min)  
Category 1, 3 point hitch.....Category 1 with  
telescoping stabilizers & flex link ends  
Rear Auxiliary Valves.....1 spool standard  
Lift capacity.....3314 lb. (1503 Kg)

### Operator Station

7 Pin Pocket  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

### Dimensions

Overall Length.....134.1 in. (3406 mm)  
Overall Width.....71.1 in. (1807 mm)  
Overall Height.....102 in. (2590 mm)  
Wheelbase.....73.7 in. (1872 mm)  
Min. Ground Clearance...13.8 in. (350 mm)  
Turning Radius.....11 ft. (3.36 m)

### Tires & Wheels

Ag (Front/Rear)  
.....9.5x16 6PR/14.9x24 6PR  
Industrial (Front/Rear)  
.....12x16.5 6PR/16.9x24 8PR  
Turf (Front/Rear)(Standard).....-

### Capacities

Fuel Tank.....16 US gal (60.5 L)  
Cooling System.....9.4 qts. (8.9 L)  
Engine Oil.....9 qts. (8.5 L)  
Transmission and Differential  
.....37.1 qts. (35 L)  
Front Axle and Final Drive Case  
.....10.5 qts. (10 L)

### Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12 V, 2.2 KW

### Operating Weight

4056 lb. (1844 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25554FS*	2555 Shuttle (T4)	020050M00	4056 (1844)	\$ 27,070
25554FS*L	2555 Shuttle Loader	024850M00	5326 (2421)	\$ 42,260
25554FS*LB	2555 Shuttle Loader & Backhoe**	032200M00	6751 (3069)	\$ 42,260

\* Different tire options

\*\* Weight less backhoe bucket



# 2555 Shuttle



## PARTS OPTIONS

Second Spool Kit	14215084000	0457M00	\$ 655
Third Spool Kit	14215086000	0457M00	\$ 655
Grille Guard	85901006000	0251M00	\$ 360
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Kit	85906000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

2555 L with SKC Quick attach Bucket & Grille Guard	Uninstalled	04500M00	\$ 5,625
--	-------------	----------	----------

## LOADER ATTACHMENTS

72" Material Bucket Skid Steer		0500M00	\$ 650
--------------------------------	--	---------	--------

## BACKHOE

75B (Less Bucket)	AT1175BL Uninstalled	07350M00	\$ 9,190
-------------------	----------------------	----------	----------

## BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 2555 Shuttle Cab



## Engine

Type.....Four Stroke, Direct Injection, Turbocharged and Intercooled, Diesel  
 No. of Cylinders.....3  
 Engine HP (kw).....55 (41)  
 Compression Ratio.....17.2:1  
 Displacement cu-in (cc).....2648  
 Rated Speed.....2300  
 Low Idle RPM.....2500 ± 50  
 High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
 PTO HP (kW).....44.5 (32.7)  
 Rear PTO RPM at engine RPM.....540 @ 2300

## Dash Instruments

Tachometer & Hour Meter  
 Fuel Gauge  
 Temperature Gauge  
 Indicators for Warning Messages  
 4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
 Safety Start Switches  
 Turn Signals/Hazard Light  
 Mechanical Wet Disc Brakes  
 Electric Key Shut off  
 Parking Brake indicator on Dash  
 Water Temperature Gauge  
 Horn

## Drive Train

Type.....Sync, shuttle w/part synchronesh  
 Number of speeds.....12F/12R  
 Clutch.....Diaphragm  
 Brakes.....Wet Disc Brake, Mechanical

## Front Axle

Power & Tilt Steering  
 Center Pivot, Reverse Eliot Type  
 Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center with position control  
 Pump output.....9.5 GPM (36.1 L/min)  
 Category 1, 3 point hitch.....Category 1 with telescoping stabilizers & flex link ends  
 Rear Auxiliary Valves.....1 spool standard  
 Lift capacity.....3314 lb. (1503 Kg)

## Operator Station

7 Pin Pocket  
 Wide Platform Steps  
 Color Coded Controls  
 Radio Included  
 Exterior Mirrors  
 Cup holder  
 2 Tool Trays  
 Roof Vent  
 Dome Light  
 2 F/R Work lights

## Dimensions

Overall Length.....134.1 in. (3406 mm)  
 Overall Width.....71.1 in. (1807 mm)  
 Overall Height.....102 in. (2590 mm)  
 Wheelbase.....73.7 in. (1872 mm)  
 Min. Ground Clearance...13.8 in. (350 mm)  
 Turning Radius.....11 ft. (3.36 m)

## Tires & Wheels

Ag (Front/Rear).....9.5x16 6PR/14.9x24 6PR  
 Industrial (Front/Rear).....12x16.5 6PR/16.9x24 8PR  
 Turf (Front/Rear)(Standard).....-

## Capacities

Fuel Tank.....16 gal. (60.5 L)  
 Cooling System.....9.4 qts. (8.9 L)  
 Engine Oil.....9 qts. (8.5 L)  
 Transmission and Differential.....37.1 qts. (35 L)  
 Front Axle and Final Drive Case.....10.5 qts. (10 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
 Alternator.....12 V 90 A  
 Starter Capacity.....12 V, 2.2 KW

## Operating Weight

4299 lb. (1950 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25554CS*	2555 Shuttle Cab (T4)	025550M00	4299 (1950)	\$ 34,500
25554CS*L	2555 Shuttle Cab Loader	030600M00	5569 (2531)	\$ 40,810
25554CS*LB	2555 Shuttle Cab Loader & Backhoe**	037950M00	6994 (3179)	\$ 50,000

\* Different tire options

\*\* Weight less backhoe bucket



# 2555 Shuttle Cab



PARTS OPTIONS			
Second Spool Kit	14215084000	0457M00	\$ 655
Third Spool Kit	14215086000	0457M00	\$ 655
Grille Guard	85901006000	0251M00	\$ 360
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Rear Wiper Kit	12427039900	0231M00	\$ 330
Third Function Kit	86106000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

2555 CL with SKC Quick Attach & Grille Guard	Uninstalled	04750M00	\$ 5,940
--	-------------	----------	----------

## LOADER ATTACHMENTS

72" Material Bucket Skid Steer		0500M00	\$ 650
--------------------------------	--	---------	--------

## BACKHOE

75B (Less Bucket)	AT1175BL Uninstalled	07350M00	\$ 9,190
-------------------	----------------------	----------	----------

## BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 2555 HST



## Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kw).....55 (41)  
Compression Ratio.....17.2:1  
Displacement cu-in (cc).....2648  
Rated Speed.....2300  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....42.4 (31.6)  
Rear PTO RPM at engine RPM  
.....540 @ 2300

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST - 3 ranges  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc Brake, Mechanical

## Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center with position control  
Pump output gpm ....9.7 GPM (36.7 L/min)  
Category 1, 3 point hitch.....Category 1 with  
telescoping stabilizers & flex link ends  
Rear Auxiliary Valves.....1 spool standard  
Lift capacity.....3314 lb. (1503 Kg)

## Operator Station

Cruise Control  
7 Pin Pocket  
Debris Shield  
Wide Platform Steps  
Color Coded Controls

## Dimensions

Overall Length.....134.1 in. (3406 mm)  
Overall Width.....71.1 in. (1807 mm)  
Overall Height.....102 in. (2590 mm)  
Wheelbase.....73.7 in. (1872 mm)  
Min. Ground Clearance...13.8 in. (350 mm)  
Turning Radius.....11 ft. (3.36 m)

## Tires & Wheels

Ag (Front/Rear)  
.....9.5x16 6PR/14.9x24 6PR  
Industrial (Front/Rear)  
.....12x16.5 6PR/16.9x24 8PR  
Turf (Front/Rear)(Standard).....-

## Capacities

Fuel Tank.....16 gal. (60.5 L)  
Cooling System.....9.4 qts. (8.9 L)  
Engine Oil.....9 qts. (8.5 L)  
Transmission and Differential  
.....37.1 qts. (35 L)  
Front Axle and Final Drive Case  
.....10.5 qts. (10 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12 V, 2.2 KW

## Operating Weight

4056 lb. (1844 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25554FH*	2555 HST (T4)	021150M00	4056 (1844)	\$ 28,560
25554FH*L	2555 HST Loader	025950M00	5326 (2421)	\$ 34,560
25554FH*LB	2555 HST Loader & Backhoe**	033300M00	6751 (3069)	\$ 43,750

\* Different tire options

\*\* Weight less backhoe bucket



# 2555 HST



## PARTS OPTIONS

Second Spool Kit	14215084000	0457M00	\$ 655
Third Spool Kit	14215086000	0457M00	\$ 655
Grille Guard	85901006000	0251M00	\$ 360
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	T1SGE360	084M00	\$ 120
Mid PTO Kit	12282700000	0548M00	\$ 785
Third Function Kit	85906000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

2555 L with SKC Quick attach Bucket & Grille Guard	Uninstalled	04500M00	\$ 5,625
--	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer		0500M00	\$ 650
--------------------------------	--	---------	--------

### BACKHOE

75B (Less Bucket)	AT1175BL Uninstalled	07350M00	\$ 9,190
-------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.


Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 2555 HST Cab



## Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kw).....55 (41)  
Compression Ratio.....17.2:1  
Displacement cu-in (cc).....2648  
Rated Speed.....2300  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....42.4 (31.6)  
Rear PTO RPM at engine RPM  
.....540 @ 2300  
Mid PTO RPM at engine RPM (optional).....-

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brake  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST - 3 ranges  
Number of speeds.....Infinite  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc Brake, Mechanical

## Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Elliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center with position control  
Pump output gpm.....9.7 GPM (36.7 L/min)  
Category 1, 3 point hitch.....Category 1 with  
telescoping stabilizers & flex link ends  
Rear Auxillary Valves.....1 spool standard  
Lift capacity.....3314 lb. (1503 Kg)

## Operator Station

Cruise Control  
7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Radio Included  
Exterior Mirrors  
Cupholder  
2 Tool Trays  
Roof Vent  
Dome Light  
2 F/R Worklights

## Dimensions

Overall Length.....134.1 in. (3406 mm)  
Overall Width.....71.1 in. (1807 mm)  
Overall Height.....102 in. (2590 mm)  
Wheelbase.....73.7 in. (1872 mm)  
Min. Ground Clearance...13.8 in. (350 mm)  
Turning Radius.....11 ft. (3.36 m)

## Tires & Wheels

Ag (Front/Rear)  
.....9.5x16 6PR/14.9x24 6PR  
Industrial (Front/Rear)  
.....12x16.5 6PR/16.9x24 8PR  
Turf (Front/Rear)(Standard)  
.....LSW305-521/LSW570-648 6PR

## Capacities

Fuel Tank.....16 gal. (60.5 L)  
Cooling System.....9.4 qts. (8.9 L)  
Engine Oil.....9 qts. (8.5 L)  
Transmission and Differential  
.....37.1 qts. (35 L)  
Front Axle and Final Drive Case  
.....10.5 qts. (10 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12 V, 2.2 KW

## Operating Weight

4299 lb. (1950 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25554CH*	2555 HST Cab (T4)	026650M00	4299 (1950)	\$ 35,980
25554CH*L	2555 HST Cab Loader	031700M00	5569 (2531)	\$ 42,290
25554CH*LB	2555 HST Cab Loader Backhoe* *	039050M00	6994 (3179)	\$ 51,480

\* Different tire options

\*\* Weight less backhoe bucket



# 2555 HST Cab



## PARTS OPTIONS

Second Spool Kit	14215084000	0457M00	\$ 655
Third Spool Kit	14215086000	0457M00	\$ 655
Grille Guard	85901006000	0251M00	\$ 360
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Rear Wiper Kit	12427039900	0231M00	\$ 330
Mid PTO Kit	12282700000	0548M00	\$ 785
Third Function Kit	86106000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

2556 CL with SKC Quick Attach & Grille Guard	Uninstalled	04750M00	\$ 5,910
--	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer		0500M00	\$ 650
--------------------------------	--	---------	--------

### BACKHOE

75B (Less Bucket)	AT11758L Uninstalled	07350M00	\$ 9,190
-------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 2565 Shuttle Cab



## Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kW).....65 (48.4)  
Compression Ratio.....17.2:1  
Displacement cu-in (cc).....2648  
Rated Speed.....2300  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....50 (36.8)  
Rear PTO RPM at engine RPM  
.....540 @ 2300

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Sync, shuttle w/part synchromesh  
Number of speeds.....12F/12R  
Clutch.....Dry Single Disc  
Brakes.....Wet Disc Brake, Mechanical

## Front Axle

Power & Tilt Steering  
Center Pivot, Reverse Eliot Type  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open Center with position and draft  
control  
Pump output gpm.....11 GPM (41.6 L/min)  
3 point hitch.....Category II with telescoping  
stabilizers & flex link ends  
Rear Auxiliary Valves.....1 spool standard  
Lift capacity.....3527 lb. (1600 kg)

## Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Radio Included  
Exterior Mirrors  
Cup holder  
2 Tool Trays  
Roof Vent  
Dome Light  
2 F/R Work lights

## Dimensions

Overall Length.....142 in. (3608 mm)  
Overall Width.....71.5 in. (1817mm)  
Overall Height.....99.2 in. (2520 mm)  
Wheelbase.....83 in. (2100 mm)  
Min. Ground Clearance...15.4 in. (392 mm)  
Turning Radius.....12.5 ft. (3.81 m)

## Tires & Wheels

Ag (Front/Rear).....9.5x20/14.9x28  
Industrial (Front/Rear)  
.....10.5/80x18/18.4x24  
Turf (Front/Rear)(Standard)  
.....LSW305-521/LSW570-648 6PR

## Capacities

Fuel Tank.....18.5 gal. (70L)  
Cooling System.....9.5 qts. (9 L)  
Engine Oil.....9 qts. (8.5 L)  
Transmission and Differential  
.....45.6 qts. (43 L)  
Front Axle and Final Drive Case  
.....17.4 qts. (16.4 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 90 A  
Starter Capacity.....12 V, 2.2 KW

## Operating Weight

5070 lb. (2305 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
25654CS*	2565 Shuttle Cab (T4)	028750M00	5070 (2305)	\$ 38,820
25654CS*L	2565 Shuttle Cab Loader	033800M00	6388 (2904)	\$ 44,760
25654CS*LB	2565 Shuttle Cab Loader & Backhoe**	041150M00	7813 (3551)	\$ 53,950

\* Different tire options

\*\* Weight less backhoe bucket



# 2565 Shuttle Cab



## PARTS OPTIONS

Second Spool Kit	12615084000	0457M00	\$ 655
Third Spool Kit	12615086000	0667M00	\$ 955
Grille Guard	85901008000	0251M00	\$ 360
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Rear Wiper Kit	12427039900	0231M00	\$ 330
Third Function Kit	86106000000	0876M00	\$ 1,255

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

2565 CL with SKC Quick Attach Bucket & Grille Guard	Uninstalled	04750M00	\$ 5,940
---	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer		0500M00	\$ 650
--------------------------------	--	---------	--------

### BACKHOE

75B (Less Bucket)	AT1175BL Uninstalled	07350M00	\$ 9,190
-------------------	----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 3540 PST



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....40 (29.8)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc) ..... 166.67 (2731)  
Rated Speed ..... 2800 rpm  
Low Idle RPM..... 2975 ± 50  
High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....31 (23.11)  
Rear PTO RPM at engine RPM  
..... 540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Power shuttle with full synchromesh  
Number of speeds ..... 12F/12R  
Clutch ..... Wet multidisc  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity .....3090 lb. (1405 kg)

## Operator Station

7 Pin Socket  
Debris Shield  
Wide Platform Steps  
Color Coded Controls  
2 Tool Boxes  
2 Cup Holders

## Dimensions

Overall Length ..... 128.9 in. (3274 mm)  
Overall Width..... 73.7 in. (1871 mm)  
Overall Height..... 98.7 in. (2492 mm)  
Wheelbase ..... 75 in. (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-16/14.9-24  
Industrial (Front/Rear)  
..... 12x16.5/16.9x24  
Turf (Front/Rear)(Standard)  
..... 29x12.50-15/44x18-20

## Capacities

Fuel Tank..... 11.3 gal. (42.7 L)  
Cooling System ..... 9 qts. (8.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
..... 36.8 qts. (34.7 L)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

4367 lb. (1985 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3540P*F	3540 PST (T4)	021950M00	4367 (1985)	\$ 27,440
3540P*FLSK	3540 PST Loader	027400M00	5817 (2644)	\$ 34,250
3540P*FLSKB	3540 PST Loader & Backhoe**	034820M00	7660 (3482)	\$ 43,525

\* Different tire options

\*\* Weight less backhoe bucket



# 3540 PST



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	AT1111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550L Loader w/ SSL GA bucket, 75"	Uninstalled	05150M00	\$ 6,440
------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

50B Backhoe (Less Bucket)	AT150BC Uninstalled	06850M00	\$ 8,560
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	AT181710	0329M00	\$ 415
12" Bucket	AT181712	0349M00	\$ 440
16" Bucket	AT181716	0379M00	\$ 475
18" Bucket	AT181718	0389M00	\$ 490
24" Bucket	AT181724	0419M00	\$ 525
36" Bucket	AT181736	0719M00	\$ 900

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....40 (29.8)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc)..... 166.67 (2731)  
Rated Speed.....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM..... 1000 ± 50

### Power Take Off

Type.....Independent  
PTO HP (kW).....31 (23.11)  
Rear PTO..... 540 rpm  
Rear PTO RPM at engine RPM  
..... 540 @ 2404

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Sync, shuttle w/ part synchromesh  
Number of speeds.....12F / 12R  
Clutch ..... Wet multidisc  
Brakes.....Oil immersed wet Disc Brakes

### Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity.....3090 lb. (1405 kg)

### Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Sun Visor  
Exterior & Rearview Mirrors  
Front Wiper w/Fluid  
2 F/R Work Lights  
2 Cup Holders  
Ashtray  
Tool Tray  
Cigarette Lighter  
12V Outlet  
Radio Ready  
Cab Light

### Dimensions

Overall Length..... 128.9 in. (3274 mm)  
Overall Width.....73.7 in. (1871 mm)  
Overall Height..... 100 in. (2540 mm)  
Wheelbase ..... 75 in. (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

### Tires & Wheels

Ag (Front/Rear).....9.5-16/14.9-24  
Industrial (Front/Rear)  
..... 12x16.5/ 16.9x24  
Turf (Front/Rear)(Standard)  
..... 29x12.50-15/44x18-20

### Capacities

Fuel Tank.....14.5 gal. (54.8 L)  
Cooling System..... 11.1 qts. (10.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
.....40.1 qts. (37.8)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

### Operating Weight

5167 lb. (2349 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3540PC*F	3540 PST Cab (T4)	029100M00	5167 (2349)	\$ 36,375
3540PC*FLSK	3540 PST Cab Loader	034550M00	6617 (3008)	\$ 43,188
3540PC*FLSKB	3540 PST Cab Loader Backhoe**	041970M00	8460 (3845)	\$ 52,463

\* Different tire options

\*\* Weight less backhoe bucket



# 3540 PST Cab



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	ATI111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690
Rear Wiper Assembly Kit 3500 Series	E007519794091	0209M00	\$ 300

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550CL Loader w/ SSL GA bucket, 75"	Uninstalled	05150M00	\$ 6,440
-------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

50B Backhoe (Less Bucket)	ATI50BK Uninstalled	06850M00	\$ 8,560
---------------------------	---------------------	----------	----------


### BACKHOE BUCKET OPTIONS

10" Bucket	ATI81710	0329M00	\$ 415
12" Bucket	ATI81712	0349M00	\$ 440
16" Bucket	ATI81716	0379M00	\$ 475
18" Bucket	ATI81718	0389M00	\$ 490
24" Bucket	ATI81724	0419M00	\$ 525
36" Bucket	ATI81736	0719M00	\$ 900

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 3540 HST



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....40 (29.8)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc) ..... 166.67 (2731)  
Rated Speed .....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....31 (23.11)  
Rear PTO RPM at engine RPM  
.....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST 3 Ranges  
Number of speeds .....Infinite  
Clutch .....N/A  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity.....3090 lb. (1405 kg)

## Operator Station

Cruise Control  
7 Pin Socket  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
2 Tool Boxes  
2 Cup Holders

## Dimensions

Overall Length ..... 128.9 in. (3274 mm)  
Overall Width ..... 73.7 in. (1871 mm)  
Overall Height.....98.7 in. (2492 mm)  
Wheelbase ..... 75 in. (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-16/14.9-24  
Industrial (Front/Rear)  
..... 12x16.5/16.9x24  
Turf (Front/Rear)(Standard)  
..... 29x12.50-15/44x18-20

## Capacities

Fuel Tank.....11.3 gal. (42.7 L)  
Cooling System..... 9 qts. (8.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
..... 40.1 qts. (37.8 L)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

4817 lb. (2190 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3540H*F	3540 HST (T4)	022950M00	4817 (2190)	\$ 28,688
3540H*FLSK	3540 HST Loader	028400M00	6267 (2849)	\$ 35,500
3540H*FLSKB	3540 HST Loader Backhoe**	035820M00	8110 (3686)	\$ 44,775

\* Different tire options

\*\* Weight less backhoe bucket



# 3540 HST



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	AT1111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550L Loader w/ SSL QA bucket, 75"	Uninstalled	05150M00	\$ 6,440
------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

50B Backhoe (Less Bucket)	AT150BC Uninstalled	06850M00	\$ 8,560
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	AT181710	0329M00	\$ 415
12" Bucket	AT181712	0349M00	\$ 440
16" Bucket	AT181716	0379M00	\$ 475
18" Bucket	AT181718	0389M00	\$ 490
24" Bucket	AT181724	0419M00	\$ 525
36" Bucket	AT181736	0719M00	\$ 900

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 3540 HST Cab



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....40 (29.8)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc) ..... 166.67 (2731)  
Rated Speed .....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....31 (23.11)  
Rear PTO..... 540 rpm  
Rear PTO RPM at engine RPM  
.....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST 3 Ranges  
Number of speeds.....Infinite  
Clutch .....N/A  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity .....3090 lb. (1405 kg)

## Operator Station

Cruise Control  
7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Sun Visor  
Exterior & Rearview Mirrors  
Front Wiper w/Fluid  
2 F/R Work Lights  
2 Cup Holders  
Ashtray  
Tool Tray  
Cigarette Lighter  
12V Outlet  
Radio Ready  
Cab Light

## Dimensions

Overall Length.....128.9 in. (3274 mm)  
Overall Width.....73.7 in. (1871 mm)  
Overall Height..... 100 in. (2540 mm)  
Wheelbase ..... 75 in. (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-16/14.9-24  
Industrial (Front/Rear)  
..... 12x16.5/ 16.9x24  
Turf (Front/Rear)[Standard]  
..... 29x12.50-15/44x18-20

## Capacities

Fuel Tank.....14.5 gal. (54.8 L)  
Cooling System..... 11.1 qts. (10.5 L)  
Engine Oil ..... 8 qts. (7.5 L)  
Transmission and Differential  
.....40.1 qts. (37.8)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

5617 lb. (2553 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3540HC*F	3540 HST Cab (T4)	030100M00	5617 (2553)	\$ 37,625
3540HC*FLSK	3540 HST Cab Loader	035550M00	7067 (3212)	\$ 44,438
3540HC*FLSKB	3540 HST Cab Loader Backhoe**	042970M00	8910 (4050)	\$ 53,713

\* Different tire options

\*\* Weight less backhoe bucket



# 3540 HST Cab



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	AT1111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690
Rear Wiper Assembly Kit 3500 Series	E007519794091	0209M00	\$ 300

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550CL Loader w/ SSL QA bucket, 75"	Uninstalled	05150M00	\$ 6,440
-------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

50B Backhoe (Less Bucket)	AT150BK Uninstalled	06850M00	\$ 8,560
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

10" Bucket	AT181710	0329M00	\$ 415
12" Bucket	AT181712	0349M00	\$ 440
16" Bucket	AT181716	0379M00	\$ 475
18" Bucket	AT181718	0389M00	\$ 490
24" Bucket	AT181724	0419M00	\$ 525
36" Bucket	AT181736	0719M00	\$ 900

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 3550 PST



## Engine

Type.....Four Stroke, Naturally Aspirated, Common Rail, Direct Injection, Water-Cooled Diesel  
 No. of Cylinders.....4  
 Engine HP (kw).....49 (36.5)  
 Compression Ratio..... 19.5:1  
 Displacement cu-in (cc) ..... 166.67 (2731)  
 Rated Speed .....2800 rpm  
 Low Idle RPM..... 2975 ± 50  
 High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
 PTO HP (kW).....40 (29.8)  
 Rear PTO RPM at engine RPM  
 .....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
 Fuel Gauge  
 Temperature Gauge  
 Indicators for Warning Messages  
 4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
 Safety Start Switches  
 Turn Signals/Hazard Light  
 Mechanical Wet Disc Brakes  
 Electric Key Shut off  
 Parking Brake Indicator on Dash  
 Water Temperature Gauge  
 Horn

## Drive Train

Type.....Power shuttle with full synchromesh  
 Number of speeds ..... 12F/12R  
 Clutch ..... Wet multidisc  
 Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
 Offset Type Live  
 Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with position and draft controls  
 Pump output..... 11 gallons/min  
 Category 1/2, 3 point hitch..... Telescopic stabilizers & flex links  
 Rear Auxiliary Valves  
 ..... 1 spool std., 2 optional  
 Lift capacity.....3090 lb. (1405 kg)

## Operator Station

7 Pin Pocket  
 Steel Front Foot Guard  
 Wide Platform Steps  
 Color Coded Controls  
 2 Tool Boxes  
 2 Cup Holders  
 Front Wiper with Fluid  
 Radio Ready

## Dimensions

Overall Length ..... 128.9 in. (3274 mm)  
 Overall Width.....75.4 in. (1915 mm)  
 Overall Height.....99.2 in. (2520 mm)  
 Wheelbase ..... 75 in. (1905 mm)  
 Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-20/16.9-24  
 Industrial (Front/Rear)  
 ..... 14x17.5/19.5Lx24  
 Turf (Front/Rear)[Standard]  
 .....31x13.50-15/21.5L-16.1

## Capacities

Fuel Tank.....11.3 gal. (42.7 L)  
 Cooling System ..... 9 qts. (8.5 L)  
 Engine Oil ..... 8 qts. (7.5 L)  
 Transmission and Differential  
 .....36.8 qts. (34.7 L)  
 Front Axle and Final Drive Case  
 ..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
 Alternator..... 12 V 45 A  
 Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

4939 lb. (2245 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3550P*F	3550 PST (T4)	024850M00	4939 (2245)	\$ 31,063
3550P*FLSK	3550 PST Loader	030300M00	6389 (2904)	\$ 37,875
3550P*FLSKB	3550 PST Loader Backhoe**	038200M00	8269 (3759)	\$ 47,750

\* Different tire options

\*\* Weight less backhoe bucket



# 3550 PST



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	AT1111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550L Loader w/ SSL GA bucket, 75"	Uninstalled	05150M00	\$ 6,440
------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

75B Backhoe (Less Bucket)	AT175BC Uninstalled	07330M00	\$ 9,160
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 3550 PST Cab



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw)..... 49 (36.5)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc)..... 166.67 (2731)  
Rated Speed.....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....40 (29.8)  
Rear PTO RPM at engine RPM  
.....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type..... Power shuttle with full synchromesh  
Number of speeds..... 12F/12R  
Clutch..... Wet multidisc  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity.....3090 lb. (1405 kg)

## Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Sun Visor  
Exterior & Rearview Mirrors  
Front Wiper w/ Fluid  
2 F/R Work Lights  
2 Cup Holders  
Ashtray  
Tool Tray  
Cigarette Lighter  
12V Outlet  
Radio Ready  
Cab Light

## Dimensions

Overall Length..... 128.9in (3274 mm)  
Overall Width..... 75.4in (1915 mm)  
Overall Height..... 100.7in (2558 mm)  
Wheelbase..... 75in (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-20/16.9-24  
Industrial (Front/Rear)  
..... 14x17.5/19.5Lx24  
Turf (Front/Rear)(Standard)  
.....31x13.50-15/21.5L-16.1

## Capacities

Fuel Tank.....14.5 gal. (54.8 L)  
Cooling System..... 11.1 qts. (10.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
.....40.1 qts. (37.8)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

5739 lb. (2609 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3550PC*F	3550 PST Cab (T4)	032300M00	5739 (2609)	\$ 40,375
3550PC*FLSK	3550 PST Cab Loader	037750M00	7189 (3268)	\$ 47,188
3550PC*FLSKB	3550 PST Cab Loader & Backhoe**	045650M00	9069 (4122)	\$ 57,063

\* Different tire options

\*\* Weight less backhoe bucket



# 3550 PST Cab



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902081	0214M00	\$ 310
Thumb Kit	ATI111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690
Rear Wiper Assembly Kit 3500 Series	E007519794091	0209M00	\$ 300

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

3550CL Loader w/ SSL GA bucket, 75"	Uninstalled	05150M00	\$ 6,440
-------------------------------------	-------------	----------	----------

### LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

### BACKHOE

75B Backhoe (Less Bucket)	ATI758K Uninstalled	07330M00	\$ 9,160
---------------------------	---------------------	----------	----------


### BACKHOE BUCKET OPTIONS

12" Bucket	ATI110012	0649M00	\$ 815
16" Bucket	ATI110016	0729M00	\$ 915
18" Bucket	ATI110018	0759M00	\$ 950
24" Bucket	ATI110024	0789M00	\$ 990
36" Bucket	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 3550 HST



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....49 (36.5)  
Compression Ratio.....19.5:1  
Displacement cu-in (cc).....166.67 (2731)  
Rated Speed.....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM.....1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....39.5 (29.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST 3 Ranges  
Number of speeds.....Infinite  
Clutch.....N/A  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output.....11 gallons/min  
Category 1/2, 3 point hitch.....Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
.....1 spool std., 2 optional  
Lift capacity.....3090 lb. (1405 kg)

## Operator Station

Cruise Control (optional)  
7 Pin Pocket (optional)  
Steel Front Foot Guard  
Wide Platform Steps  
Color Coded Controls  
2 Tool Boxes  
2 Cup Holders

## Dimensions

Overall Length.....128.9 in. (3274 mm)  
Overall Width.....75.4 in. (1915 mm)  
Overall Height.....99.2 in. (2520 mm)  
Wheelbase.....75 in. (1905 mm)  
Turning Radius.....10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-20/16.9-24  
Industrial (Front/Rear)  
.....14x17.5/19.5Lx24  
Turf (Front/Rear)[Standard]  
.....31x13.50-15/21.5L-16.1

## Capacities

Fuel Tank.....11.3 gal. (42.7 L)  
Cooling System.....9 qts. (8.5 L)  
Engine Oil.....8 qts. (7.5 L)  
Transmission and Differential  
.....40.1 qts. (37.8 L)  
Front Axle and Final Drive Case  
.....9 qts. (8.5 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 45 A  
Starter Capacity.....12 V, 2.0 KW

## Operating Weight

5389 lb. (2450 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3550H*F	3550 HST (T4)	025850M00	5389 (2450)	\$ 32,313
3550H*FLSK	3550 HST Loader	031300M00	6839 (3108)	\$ 39,125
3550H*FLSKB	3550 HST Loader Backhoe**	039200M00	8719 (3963)	\$ 49,000

\* Different tire options

\*\* Weight less backhoe bucket



# 3550 HST



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902061	0214M00	\$ 310
Thumb Kit	ATI111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

3550L Loader w/ SSL GA bucket, 75"	Uninstalled	05150M00	\$ 6,440
------------------------------------	-------------	----------	----------

## LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

## BACKHOE

75B Backhoe (Less Bucket)	ATI75BK Uninstalled	07330M00	\$ 9,160
---------------------------	---------------------	----------	----------

## BACKHOE BUCKET OPTIONS

Bucket 12"	ATI11012	0649M00	\$ 815
Bucket 16"	ATI11016	0729M00	\$ 915
Bucket 18"	ATI110018	0759M00	\$ 950
Bucket 24"	ATI110024	0789M00	\$ 990
Bucket 36"	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges [\$350 for 2500 series].

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 3550 HST Cab



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....49 (36.5)  
Compression Ratio..... 19.5:1  
Displacement cu-in (cc)..... 166.67 (2731)  
Rated Speed.....2800 rpm  
Low Idle RPM.....2975 ± 50  
High Idle RPM..... 1000 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....39.5 (29.4)  
Rear PTO RPM at engine RPM  
.....540 @ 2404

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....HST 3 Ranges  
Number of speeds.....Infinite  
Clutch.....N/A  
Brakes.....Oil immersed wet Disc Brakes

## Front Axle

Power Steering  
Offset Type Live  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 1/2, 3 point hitch..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves  
..... 1 spool std., 2 optional  
Lift capacity.....3090 lb. (1405 kg)

## Operator Station

Cruise Control  
7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Sun Visor  
Exterior & Rearview Mirrors  
Front Wiper w/Fluid  
2 F/R Work Lights  
2 Cup Holders  
Ashtray  
Tool Tray  
Cigarette Lighter  
12V Outlet  
Radio Ready  
Cab Light

## Dimensions

Overall Length..... 128.9 in. (3274 mm)  
Overall Width..... 75.4 in. (1915 mm)  
Overall Height..... 100.7 in. (2558 mm)  
Wheelbase..... 75 in. (1905 mm)  
Turning Radius..... 10.3 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5-20/16.9-24  
Industrial (Front/Rear)  
..... 14x17.5/19.5Lx24  
Turf (Front/Rear)(Standard)  
.....31x13.50-15/21.5L-16.1

## Capacities

Fuel Tank.....14.5 gal. (54.8 L)  
Cooling System..... 11.1 qts. (10.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
.....40.1 qts. (37.8)  
Front Axle and Final Drive Case  
..... 9 qts. (8.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

## Operating Weight

6189 lb. (2813 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
3550HC*F	3550 HST Cab (T4)	033300M00	6189 (2813)	\$ 41,625
3550HC*FLSK	3550 HST Cab Loader	038750M00	7639 (3472)	\$ 48,438
3550HC*FLSKB	3550 HST Cab Loader Backhoe**	046650M00	9519 (4327)	\$ 58,313

\* Different tire options

\*\* Weight less backhoe bucket



# 3550 HST Cab



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	TBD		-
Grille Guard	KMW15902081	0214M00	\$ 310
Thumb Kit	ATI111028	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690
Rear Wiper Assembly Kit 3500 Series	E007519794D91	0209M00	\$ 300

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

3550CL Loader w/ SSL QA bucket, 75"	Uninstalled	05150M00	\$ 6,440
-------------------------------------	-------------	----------	----------

## LOADER ATTACHMENTS

75" Material Bucket Skid Steer	KMW13003617	0480M00	\$ 600
Quick Attach Adapter	KMW13043164	0450M00	\$ 585

## BACKHOE

75B Backhoe (Less Bucket)	ATI75BK Uninstalled	07330M00	\$ 9,160
---------------------------	---------------------	----------	----------

## BACKHOE BUCKET OPTIONS

Bucket 12"	ATI11012	0649M00	\$ 815
Bucket 16"	ATI11016	0729M00	\$ 915
Bucket 18"	ATI110018	0759M00	\$ 950
Bucket 24"	ATI110024	0789M00	\$ 990
Bucket 36"	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 4540 2WD



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....41 (30.5)  
Compression Ratio.....18.7:1  
Displacement cu-in (cc).....166.67 (2731)  
Rated Speed.....2300 rpm  
Low Idle RPM.....2550 ± 50  
High Idle RPM.....750 ± 50

## Power Take Off

Type.....Live  
PTO HP (kW).....31 (23.1)  
Rear PTO RPM at engine RPM  
.....540 @ 2058

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Sliding Mesh  
Number of speeds.....8F/2R  
Clutch.....Dry Dual Clutch  
Brakes.....Fully enclosed dry disc

## Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output.....8.29 gallons/min  
3-point Hitch.....Category 1 & 2  
w/telescopic stabilizers  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....3527 lb.

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

## Dimensions

Overall Length.....115.3 in. (2930 mm)  
Overall Width.....69.4 in. (1763 mm)  
Overall Height.....88 in. (2235 mm)  
Wheelbase.....76.46 in. (1942 mm)  
Turning Radius.....9.7 ft. (3 m)

## Tires & Wheels

Ag (Front/Rear).....6x16/12.4x28

## Capacities

Fuel Tank.....14.55 gal. (55 L)  
Cooling System.....9 qts. (8.5 L)  
Engine Oil.....8 qts. (7.5 L)  
Transmission and Differential  
.....37.1 qts. (35 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 45 A  
Starter Capacity.....12 V, 2.0 KW


## Operating Weight

4191 lb. (1905 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
4540F	4540 2WD (T4)	013300M00	4191 (1905)	\$ 17,960
4540FLSK	4540 2WD w/ Loader	017850M00	6045 (2748)	\$ 23,650



# 4540 2WD



## PARTS OPTIONS

Grille Guard	ANS4025A4000	0383M00	\$ 550
Block Heater Assembly	TISGE360	084M00	\$ 120

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS LOADER

4550- 2L with SKC Quick Attach Bucket & Grille Guard	Uninstalled	04550M00	\$ 5,690
--	-------------	----------	----------

## LOADER ATTACHMENTS

60" Material Bucket Skid Steer	BT38H	0515M00	\$ 665
Quick Attach Adapter	B1000B-200F	0325M00	\$ 425

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 4540 4WD



## Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....41 (30.5)  
Compression Ratio.....18.7:1  
Displacement cu-in (cc).....166.67 (2731)  
Rated Speed.....2300 rpm  
Low Idle RPM.....2550 ± 50  
High Idle RPM.....750 ± 50

## Power Take Off

Type.....Live  
PTO HP (kW).....31 (23.1)  
Rear PTO RPM at engine RPM  
.....540 @ 2058

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Full constant mesh  
Number of speeds.....8F/2R  
Clutch.....Dry Dual Clutch  
Brakes.....Fully enclosed dry disc

## Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-five hydraulic with  
position and draft controls  
Pump output.....8.7 gallons/min  
3-point Hitch.....Category 1 & 2  
w/ telescopic stabilizers  
Rear Auxiliary Valves.....1 spool optional  
Lift capacity.....3527 lb.

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

## Dimensions

Overall Length.....128.9 in. (3275 mm)  
Overall Width.....82.6 in. (2098 mm)  
Overall Height.....92.6 in. (2352 mm)  
Wheelbase.....76.46 in. (1942 mm)  
Turning Radius.....10.5 ft. (3.2 m)

## Tires & Wheels

Ag (Front/Rear).....9.5x16/12.4x28  
Industrial (Front/Rear)  
.....12x16.5/16.9x24

## Capacities

Fuel Tank.....14.55 gal. (55 L)  
Cooling System.....9 qts. (8.5 L)  
Engine Oil.....8 qts. (7.5 L)  
Transmission and Differential  
.....42.4 qts. (40 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 45 A  
Starter Capacity.....12 V, 2.0 KW

## Operating Weight

5192 lb. (2360 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
45504*F	4540 4WD (T4)	017250M00	5192 (2360)	\$ 23,290
45504*FLSK	4540 4WD w/ Loader	021800M00	7200 (3273)	\$ 29,980
45504*FLSKB	4540 4WD w/ Loader & Backhoe**	027220M00	8589 (3904)	\$ 35,630

\* Different tire options

\*\* Weight less backhoe bucket



# 4540 4WD



## PARTS OPTIONS

Grille Guard	ANS4025A4000	0383M00	\$ 550
Block Heater Assembly	TISGE360	084M00	\$ 120
Mechanical Thumb Kit	ANSANMTK7686	0583M00	\$ 835

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

4550-4L SKC Quick Attach Bucket and Grille Guard	Uninstalled	04550M00	\$ 5,690
--	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer	BT38J	0515M00	\$ 665
--------------------------------	-------	---------	--------

### BACKHOE

4450B w/ 16" bucket	ANBH4550B Uninstalled	05420M00	\$ 6,650
---------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	ANBKT12	0349M00	\$ 440
16" Bucket	ANBKT16	0379M00	\$ 475
24" Bucket	ANBKT24	0419M00	\$ 525

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges [\$350 for 2500 series].

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 4550 2WD



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....48 (35.8)  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc) ..... 166.67 (2731)  
Rated Speed ..... 2300 rpm  
Low Idle RPM..... 2550 ± 50  
High Idle RPM..... 750 ± 50

### Power Take Off

Type.....Live  
PTO HP (kW).....38 (28.3)  
Rear PTO RPM at engine RPM  
.....540 @ 2058

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Full constant mesh  
Number of speeds..... 8F/2R  
Clutch .....Dry Dual Clutch  
Brakes.....Fully enclosed dry disc

### Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 8.7 gallons/min  
3-point Hitch .....Category 1 & 2  
w/ telescopic stabilizers  
Rear Auxiliary Valves..... 1 spool Standard  
Lift capacity ..... 3527 lb.

### Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

### Dimensions

Overall Length ..... 119.4 in. (3034 mm)  
Overall Width.....69.4 in. (1763 mm)  
Overall Height.....92.5 in. (2350 mm)  
Wheelbase ..... 76.46 in. (1942 mm)  
Turning Radius.....9.7 ft. (2.97 m)

### Tires & Wheels

Ag (Front/Rear)..... 6x16/12.4x28

### Capacities

Fuel Tank..... 14.55 gal. (55 L)  
Cooling System..... 9 qts. (8.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
..... 42.4 qts. (40 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

### Operating Weight

4267 lb. (1940 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
4550F	4550 2WD (T4)	014950M00	4267 (1940)	\$ 20,190
4550FLSK	4550 2WD w/ Loader	019500M00	6121 (2782)	\$ 25,880



# 4550 2WD



## PARTS OPTIONS

Grille Guard	ANS4025A4000	0383M00	\$ 550
Block Heater Assembly	TISGE360	084M00	\$ 120

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

4550- 2L with SKC Quick Attach Bucket & Grille Guard	Uninstalled	04550M00	\$ 5,690
--	-------------	----------	----------

### LOADER ATTACHMENTS

60" Material Bucket Skid Steer	BT38H	0515M00	\$ 665
Quick Attach Adapter	B1000B-200F	0325M00	\$ 425

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Naturally Aspirated,  
Common Rail, Direct Injection, Water-  
Cooled Diesel  
No. of Cylinders.....4  
Engine HP (kw).....48 (35.8)  
Compression Ratio..... 18.7:1  
Displacement cu-in (cc)..... 166.67 (2731)  
Rated Speed.....2300 rpm  
Low Idle RPM..... 2550 ± 50  
High Idle RPM..... 750 ± 50

### Power Take Off

Type.....Live  
PTO HP (kW).....38 (28.3)  
Rear PTO RPM at engine RPM  
.....540 @ 2058

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Full constant mesh  
Number of speeds..... 8F/2R  
Clutch.....Dry Dual Clutch  
Brakes.....Fully enclosed dry disc

### Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output.....8.7 gallons/min  
3-point Hitch.....Category 1 & 2  
w/telescopic stabilizers  
Rear Auxiliary Valves..... 1 spool Standard  
Lift capacity..... 3527 lb.

### Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

### Dimensions

Overall Length..... 127 in. (3227 mm)  
Overall Width.....82.6 in. (2098 mm)  
Overall Height.....93.7 in. (2380 mm)  
Wheelbase.....76.77 in. (1950 mm)  
Turning Radius..... 10.5 ft. (3.2 m)

### Tires & Wheels

Ag (Front/Rear).....9.5x16/12.4x28  
Industrial (Front/Rear)  
.....12.6x16.5/16.9x24

### Capacities

Fuel Tank.....14.55 gal. (55 L)  
Cooling System..... 9 qts. (8.5 L)  
Engine Oil..... 8 qts. (7.5 L)  
Transmission and Differential  
.....42.4 qts. (40 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.0 KW

### Operating Weight

5292 lb. (2405 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
45504*F	4550 4WD (T4)	018900M00	5292 (2405)	\$ 25,520
45504*FLSK	4550 4WD w/ Loader	023450M00	7300 (3318)	\$ 31,210
45504*FLSKB	4550 4WD w/ Loader & Backhoe**	028870M00	8689 (3950)	\$ 37,860

\* Different tire options

\*\* Weight less backhoe bucket



# 4550 4WD



## PARTS OPTIONS

Grille Guard	ANS4025A4000	0383M00	\$ 550
Block Heater Assembly	TISGE360	084M00	\$ 120
Mechanical Thumb Kit	ANSANMTK7686	0583M00	\$ 835

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

4550-4L With SKC Quick Attach Bucket and Grille Guard	Uninstalled	04550M00	\$ 5,690
---	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer	BT38J	0515M00	\$ 665
--------------------------------	-------	---------	--------

### BACKHOE

4450B w/ 16" bucket	ANBH4550B Uninstalled	05420M00	\$ 6,650
---------------------	-----------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	ANBKT12	0349M00	\$ 440
16" Bucket	ANBKT16	0379M00	\$ 475
24" Bucket	ANBKT24	0419M00	\$ 525

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



# 4565 2WD



## Engine

Type.....Four Stroke, Direct Injection, Turbocharged and Intercooled, Diesel  
 No. of Cylinders.....3  
 Engine HP (kw).....62 (46.2)  
 Compression Ratio..... 17.2:1  
 Displacement cu-in (cc)..... 161.5 (2646)  
 Rated Speed.....2100 rpm  
 Low Idle RPM.....2300 ± 50  
 High Idle RPM..... 850 ± 50

## Power Take Off

Type.....Live  
 PTO HP (kW).....52 (38.8)  
 Rear PTO RPM at engine RPM.....540 @ 2059

## Dash Instruments

Tachometer & Hour Meter  
 Fuel Gauge  
 Temperature Gauge  
 Indicators for Warning Messages  
 4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
 Safety Start Switches  
 Turn Signals/Hazard Light  
 Mechanical Wet Disc Brakes  
 Electric Key Shut off  
 Parking Brake Indicator on Dash  
 Water Temperature Gauge  
 Horn

## Drive Train

Type.....Full constant mesh  
 Number of speeds..... 8F/2R  
 Clutch .....Dry Dual Clutch  
 Brakes.....Fully enclosed dry disc

## Front Axle

Power Steering  
 Square Tube Design  
 Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with position and draft controls  
 Pump output..... 10.5 gallons/min  
 3-point Hitch .....Category 1 & 2 w/telescopic stabilizers  
 Rear Auxiliary Valves.... 1 or 2 spool optional  
 Lift capacity..... 3527 lb.

## Operator Station

Wide Platform Steps  
 Color Coded Controls  
 Tool Box

## Dimensions

Overall Length..... 119.0 in. (3022mm)  
 Overall Width..... 78.0 in. (1981mm)  
 Overall Height..... 95 in. (2413mm)  
 Wheelbase .....76.5 in. (1943)  
 Turning Radius.....9.6 ft. (2.9 m)

## Tires & Wheels

Ag (Front/Rear).....7.5x16/14.9x28

## Capacities

Fuel Tank.....14.8 gal. (55.9 L)  
 Cooling System..... 9 qts. (8.5 L)  
 Engine Oil.....9 qts. (8.5 L)  
 Transmission and Differential ..... 37 qts. (34.9 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
 Alternator..... 12 V 55 A  
 Starter Capacity..... 12 V, 2.2 KW

## Operating Weight

4928 lb. (2240 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
4565FV	4565 2WD (T4) w/ Valve	016800M00	4928 (2240)	\$ 22,680
4565FLSKTV	4550 2WD w/ Loader & Valve	021650M00	6278 (2854)	\$ 28,740



# 4565 2WD



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	008001230B91	0723M00	\$ 1,035
Grille Guard	KMW15902082	0249M00	\$ 360
Block Heater Assembly	TISGE360	084M00	\$ 120

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

4565-2L with SKC Quick Attach Bucket and Grill Guard	Uninstalled	04850M00	\$ 6,060
--	-------------	----------	----------


### LOADER ATTACHMENTS

72" Material Bucket Skit Steer (Std.)	KMW13003605	0530M00	\$ 660
Quick Attach Adapter	KMW13044076	0475M00	\$ 595
Single Spool Auxiliary Valve Kit	008001227B91 Uninstalled	0415M00	\$ 520

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 5545 4WD



## Engine

Type.....Four Stroke, Direct Injection,  
Water-Cooled Diesel  
No. of Cylinders.....3  
Engine HP (kw).....43 {32}  
Compression Ratio..... 17.5:1  
Displacement cu-in (cc)..... 161.7 (2650)  
Rated Speed.....2100 rpm  
High Idle RPM.....2300 ± 50  
Low Idle RPM..... 850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....34 {25.3}  
Rear PTO RPM at engine RPM  
.....540 @ 2058

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Dry Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Forward/reverse synchro  
shuttle w/synchro speeds & constant  
mesh range  
Number of speeds..... 8F/8R  
Clutch .....Dry Dual Clutch  
Brakes..... Fully enclosed Dry Disc

## Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump Output..... 10.9 gallons/min  
3-point Hitch .....Category 1 & 2  
with Telescopic Stabilizers  
Rear Auxiliary Valves..... 1 spool std  
Lift Capacity.....3968 lbs

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

## Dimensions

Overall Length..... 134 in. {3400 mm}  
Overall Width..... 72.5 in. {1842 mm}  
Overall Height.....93.3 in. {2371 mm}  
Wheelbase .....85.15 in. {2163 mm}  
Turning Radius..... 10.8 ft. {3.3 m}

## Tires & Wheels

Ag (Front/Rear).....9.5x20/13.6x28  
Industrial (Front/Rear)  
..... 10.5/80x18/16.9x24

## Capacities

Fuel Tank.....12 gal. {45.4 L}  
Cooling System..... 9 qts. {8.5 L}  
Engine Oil..... 9 qts. {8.5 L}  
Transmission and Differential  
..... 42.2 qts. {40 L}  
Front Axle and Final Drive Case  
..... 13.7 qts. {13 L}

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 45 A  
Starter Capacity..... 12 V, 2.2 KW

## Operating Weight

5567 lb. {2530 kg}

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
55454FS*	5545 4WD (T4)	020100M00	5567 {2530}	\$ 27,140
55454FS*L	5545 4WD w/ Loader	025200M00	7167 {3258}	\$ 33,520
55454FS*L758E	5545 4WD w/ Loader & Backhoe**	033020M00	9047 {4112}	\$ 42,680

\* Different tire options

\*\* Weight less backhoe bucket



# 5545 4WD



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	007202664C91	0901M00	\$ 1,290
Grille Guard	KMW15902027	0214M00	\$ 310
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

5545-4L with SKC Quick Attach Bucket & Grille Guard	Uninstalled	04800M00	\$ 6,000
---	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer	KMW13003198	0500M00	\$ 650
Quick Attach Adapter	KMW13043086	0450M00	\$ 585

### BACKHOE

75B Backhoe (Less bucket)	AT175BE Uninstalled	07330M00	\$ 9,160
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

12" Bucket	AT1110012	0649M00	\$ 815
16" Bucket	AT1110016	0729M00	\$ 915
18" Bucket	AT1110018	0759M00	\$ 950
24" Bucket	AT1110024	0789M00	\$ 990
36" Bucket	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.



### Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kw).....55 (41.0)  
Compression Ratio..... 17.2:1  
Displacement cu-in [cc]..... 161.7 (2650)  
Rated Speed .....2100 rpm  
High Idle RPM.....2300 ± 50  
Low Idle RPM..... 850 ± 50

### Power Take Off

Type.....Independent  
PTO HP (kW).....45 (33.6)  
Rear PTO RPM at engine RPM  
.....540 @ 2059

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Constant mesh with  
Forward/Reverse synchro shuttle  
Number of speeds ..... 8F/8R  
Clutch .....Dual dry with cerametallic lining  
Brakes.....Wet Disc

### Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

### Hydraulic System

Type.....Open center, full-five hydraulic with  
position and draft controls  
Pump Output..... 10.6 gallons/min  
3-point Hitch .....Category 1 & 2  
with Telescopic Stabilizers & flex ends  
Rear Auxiliary Valves..... 1 standard; 2 spool  
optional  
Lift Capacity.....3968 lbs

### Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

### Dimensions

Overall Length ..... 138.4 in. (3515 mm)  
Overall Width.....75.3 in. (1918 mm)  
Overall Height..... 100.5 in. (2553 mm)  
Turning Radius..... 11.6 ft. (3.5 m)

### Tires & Wheels

Ag (Front/Rear).....7.5x16/14.9x28

### Capacities

Fuel Tank.....17.1 gal. (64.8 L)  
Cooling System..... 9 qts. (8.5 L)  
Engine Oil ..... 9 qts. (8.5 L)  
Transmission and Differential  
.....44.4 qts. (41.9 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 55 A  
Starter Capacity..... 12 V, 3.6 KW


### Operating Weight

5379 lb. (2445 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
5555SF	5555 2WD (T4)	019700M00	5379 (2445)	\$ 24,625
5555SFLSK	5555 2WD w/ Loader	025100M00	6729 (3059)	\$ 31,375



# 5555 2WD



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	007202664C91	0901M00	\$ 1,290
Grille Guard	KMW15902027	0214M00	\$ 310
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

5565-2L With SKC Quick Attach Bucket & Grille Guard	Uninstalled	05100M00	\$ 6,375
---	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer	KMW13003605	0530M00	\$ 660
Quick Attach Adapter	KMW13044076	0475M00	\$ 595

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 5555 4WD



## Engine

Type.....Four Stroke, Direct Injection, Turbocharged and Intercooled, Diesel  
 No. of Cylinders.....3  
 Engine HP (kW).....55 (41.0)  
 Compression Ratio..... 17.2:1  
 Displacement cu-in (cc)..... 161.7 (2650)  
 Rated Speed.....2100 rpm  
 High Idle RPM.....2300 ± 50  
 Low Idle RPM..... 850 ± 50

## Power Take Off

Type.....Independent  
 PTO HP (kW).....45 (33.6)  
 Rear PTO RPM at engine RPM  
 .....540 @ 2059

## Dash Instruments

Tachometer & Hour Meter  
 Fuel Gauge  
 Temperature Gauge  
 Indicators for Warning Messages  
 4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
 Safety Start Switches  
 Turn Signals/Hazard Light  
 Mechanical Wet Disc Brakes  
 Electric Key Shut off  
 Parking Brake Indicator on Dash  
 Water Temperature Gauge  
 Horn

## Drive Train

Type.....Constant mesh with Forward/Reverse synchro shuttle  
 Number of speeds..... 8F/8R  
 Clutch.....Dual dry with cerametallic lining  
 Brakes.....Wet Disc

## Front Axle

Power Steering  
 Square Tube Design  
 Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-five hydraulic with position and draft controls  
 Pump Output..... 10.6 gallons/min  
 3-point Hitch .....Category 1 & 2 with Telescopic Stabilizers & flex ends  
 Rear Auxiliary Valves..... 1 standard; 2 spool optional  
 Lift Capacity.....3968 lbs

## Operator Station

Wide Platform Steps  
 Color Coded Controls  
 Tool Box

## Dimensions

Overall Length..... 140 in (3556 mm)  
 Overall Width..... 79 in. (2007 mm)  
 Overall Height.....98.8 in. (2508 mm)  
 Wheelbase .....85.2 in. (2164 mm)  
 Turning Radius..... 13.75 ft. (4.19 m)

## Tires & Wheels

Ag (Front/Rear).....9.5x24/ 14.9x28  
 Industrial (Front/Rear)  
 ..... 12.5/80x18/ 16.9x24

## Capacities

Fuel Tank.....17.1 gal. (64.6 L)  
 Cooling System ..... 9 qts. (8.5 L)  
 Engine Oil..... 9 qts. (8.5 L)  
 Transmission and Differential  
 .....47.5 qts. (44.8 L)  
 Front Axle and Final Drive Case  
 ..... 8.1 qts. (7.6)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
 Alternator..... 12 V 55 A  
 Starter Capacity..... 12 V, 3.6 KW

## Operating Weight

6039 lb. (2745 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
55554*FT	5555 4WD (T4)	024250M00	6039 (2745)	\$ 30,313
55554*FLSKT	5555 4WD w/ Loader	030050M00	7999 (3636)	\$ 37,563
55554*FLSKTB75G	5555 4WD w/ Loader & 75B Backhoe* *	038485M00	9879 (4490)	\$ 48,106
55554*FLSKTB85G	5555 4WD w/ Loader & 85B Backhoe* *	038785M00	10048 (4567)	\$ 48,481

\* Different tire options  
 \*\* Weight less backhoe bucket



# 5555 4WD



## PARTS OPTIONS

Second Spool Auxiliary Valve Kit	007203152B91	0901M00	\$ 1,290
Grille Guard	KMW15902027	0214M00	\$ 310
Thumb Kit	ATI16610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

<b>LOADER</b>			
5565 4L- W/ SKC Quick Attach & Grille Bucket	Uninstalled	05500M00	\$ 6,875

<b>LOADER ATTACHMENTS</b>			
78" Material Bucket Skid Steer	KMW13003147	0650M00	\$ 810
Quick Attach Adapter	KMW13043086	0495M00	\$ 620


<b>BACKHOE</b>			
75B Backhoe (Less bucket)	ATI75BJ Uninstalled	07330M00	\$ 9,165
85B Backhoe (Less bucket)	ATI85BJ Uninstalled	07730M00	\$ 9,660

<b>BACKHOE BUCKET OPTIONS</b>			
12" Bucket	ATI110012	0649M00	\$ 815
16" Bucket	ATI110016	0729M00	\$ 915
18" Bucket	ATI110018	0759M00	\$ 950
24" Bucket	ATI110024	0789M00	\$ 990
36" Bucket	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# 5570 2WD



## Engine

Type.....Four Stroke, Direct Injection,  
Turbocharged and Intercooled, Diesel  
No. of Cylinders.....3  
Engine HP (kw).....70 {52.1}  
Compression Ratio.....17.2:1  
Displacement cu-in (cc).....161.7 {2650}  
Rated Speed.....2100 rpm  
High Idle RPM.....2300 ± 50  
Low Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....61 {45.4}  
Rear PTO RPM at engine RPM  
.....540 @ 2059

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Constant mesh with  
Forward/Reverse synchro shuttle  
Number of speeds.....8F/8R  
Clutch.....Dual dry with cerametallic lining  
Brakes.....Wet Disc

## Front Axle

Power Steering  
Square Tube Design  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump Output.....10.6 gallons/min  
3-point Hitch.....Category 1 & 2, Adjustable  
outside Telescopic Stabilizer  
Rear Auxiliary Valves.....2 spool std  
Lift Capacity.....3968 lbs

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box

## Dimensions

Overall Length.....138.3 in. {3515mm}  
Overall Width.....77.3 in. {1961mm}  
Overall Height.....103.3 in. {2624mm}  
Wheelbase.....84.9 in. {2156 mm}  
Turning Radius.....14 ft. {4.2mm}

## Tires & Wheels

Ag (Front/Rear).....9.5Lx15/16.9x28

## Capacities

Fuel Tank.....17.1 gal. {64.6 L}  
Cooling System.....9 qts. {8.5 L}  
Engine Oil.....9 qts. {8.5 L}  
Transmission and Differential  
.....44.4 qts. {41.9 L}

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 55 A  
Starter Capacity.....12 V, 3.6 KW


## Operating Weight

5557 lb. {2526 kg}

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
55702FSA	5570 2WD (T4)	021500M00	5557 {2526}	\$ 26,875
55702FSAL	5570 2WD w/ Loader	026900M00	6907 {3140}	\$ 33,625



# 5570 2WD



## PARTS OPTIONS

Grille Guard	KMW15902027	0214M00	\$ 310
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

5565-2L With SKC Quick Attach Bucket & Grille Guard	Uninstalled	05100M00	\$ 6,375
---	-------------	----------	----------

### LOADER ATTACHMENTS

72" Material Bucket Skid Steer	KMW13003605	0530M00	\$ 660
Quick Attach Adapter	KMW13044076	0475M00	\$ 595


Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement. Outgoing freight is not included in the above prices.



# 5570 4WD



## Engine

Type.....Four Stroke, Direct Injection, Turbocharged and Intercooled, Diesel  
 No. of Cylinders.....3  
 Engine HP (kw).....70 (52.1)  
 Compression Ratio.....17.2:1  
 Displacement cu-in (cc).....161.7 (2650)  
 Rated Speed.....2100 rpm  
 High Idle RPM.....2300 ± 50  
 Low Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
 PTO HP (kW).....61 (45.4)  
 Rear PTO RPM at engine RPM.....540 @ 2059

## Dash Instruments

Tachometer & Hour Meter  
 Fuel Gaug  
 Temperature Gauge  
 Indicators for Warning Messages  
 4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
 Safety Start Switches  
 Turn Signals/Hazard Light  
 Mechanical Wet Disc Brakes  
 Electric Key Shut off  
 Parking Brake Indicator on Dash  
 Water Temperature Gauge  
 Horn

## Drive Train

Type.....Constant mesh with Forward/Reverse synchro shuttle  
 Number of speeds.....8F/8R  
 Clutch.....Dual dry with cerametallic lining  
 Brakes.....Wet Disc

## Front Axle

Power Steering  
 Square Tube Design  
 Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with position and draft controls  
 Pump Output.....10.6 gallons/min  
 3-point Hitch.....Category 1 & 2, Adjustable outside Telescopic Stabilizer  
 Rear Auxiliary Valves.....2 spool std  
 Lift Capacity.....3968 lbs

## Operator Station

Wide Platform Steps  
 Color Coded Controls  
 Tool Box

## Dimensions

Overall Length.....145 in. (3683 mm)  
 Overall Width.....81 in. (2057 mm)  
 Overall Height.....99.7 in. (2532 mm)  
 Wheelbase.....85.2 in. (2164 mm)  
 Turning Radius.....15.7 in. (4.8 m)

## Tires & Wheels

Ag (Front/Rear).....11.2x24/16.9x30  
 Industrial (Front/Rear).....12.5/80x18/16.9x24

## Capacities

Fuel Tank.....17.1 gal. (64.6 L)  
 Cooling System.....9 qts. (8.5 L)  
 Engine Oil.....9 qts. (8.5 L)  
 Transmission and Differential.....49.6 qts. (46.8 L)  
 Front Axle and Final Drive Case.....8.1 qts. (7.6)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
 Alternator.....12 V 55 A  
 Starter Capacity.....12 V, 3.6 KW

## Operating Weight

6302 lb. (2865 kg)


MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
55704FS*	5570 4WD (T4)	026400M00	6302 (2865)	\$ 33,000
55704FS*L	5570 4WD w/ Loader	032200M00	8262 (3755)	\$ 40,250
55704FS*L75BG	5570 4WD w/ Loader & 75B Backhoe**	040635M00	10142 (4610)	\$ 50,794
55704FS*L85BJ	5570 4WD w/ Loader & 85B Backhoe**	040935M00	10311 (4687)	\$ 51,169

\* Different tire options

\*\* Weight less backhoe bucket



# 5570 4WD



## PARTS OPTIONS

Grille Guard	KMW15902027	0214M00	\$ 310
Thumb Kit	ATI16610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

5565 4L-W/ SKC Quick Attach & Grille Bucket	Uninstalled	05500M00	\$ 6,875
---	-------------	----------	----------

### LOADER ATTACHMENTS

78" Material Bucket Skid Steer	KMW13003147	0650M00	\$ 810
Quick Attach Adapter	KMW13043086	0495M00	\$ 620

### BACKHOE

75B Backhoe (Less bucket)	ATI75BJ Uninstalled	07330M00	\$ 9,165
85B Backhoe (Less bucket)	ATI85BJ Uninstalled	07730M00	\$ 9,665

### BACKHOE BUCKET OPTIONS

12" Bucket	ATI110012	0649M00	\$ 815
16" Bucket	ATI110016	0729M00	\$ 915
18" Bucket	ATI110018	0759M00	\$ 950
24" Bucket	ATI110024	0789M00	\$ 990
36" Bucket	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



### Engine

Type..... Turbocharged, Four Stroke,  
Common Rail, Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw).....74.4 (55.4)  
Compression Ratio..... 17.2:1  
Displacement cu-in (cc).....215.4 (3531.46)  
Rated Speed ..... 2300 rpm  
Low Idle RPM.....2500 ± 50  
High Idle RPM..... 850 ± 50

### Power Take Off

Type.....Independent  
PTO HP (kW).....61 (45.5) mad  
Rear PTO RPM at engine RPM  
.....540 @ 2186

### Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

### Safety Equipment

Foldable ROPS w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

### Drive Train

Type.....Forward/Reverse synchro  
shuttle with full synchro mesh  
Number of Speeds..... 12F/12R  
Clutch .....Dual dry with ceremetallic lining  
Brakes.....Wet disc

### Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for wider steering

### Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 2, 3 point hitch ..... Telescopic  
stabilizers and flex links  
Rear Auxiliary Valves.....2 spool standard  
with detent type raise and lower with  
kickback and float position in front  
Lift capacity .....5100 lb. (2318 kg)

### Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box

### Dimensions

Overall Length ..... 162 in. (4116 mm)  
Overall Width.....77.3 in. (1963 mm)  
Overall Height (to top of cab)  
.....94.5 in. (2400mm)  
Wheelbase .....85.8 in. (2179 mm)  
Turning Radius..... 13.1 ft. (4 m)

### Tires & Wheels

Ag (Front/Rear)..... 11.2x24/16.9x30  
Industrial (Front/Rear)  
..... 12.5/80x18/19.5Lx24

### Capacities

Fuel Tank.....19.28 gal. (73 L)  
Cooling System ..... 10.3 qts. (9.7 L)  
Engine Oil ..... 9.5 qts. (8.9 L)  
Transmission and Differential  
..... 41.2 qts. (38.9 L)  
Front Axle and Final Drive Case  
..... 7.2 qts. (6.8 L)

### Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator ..... 12 V 55 A


### Operating Weight

7100 lb. (3227 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MP75*F	mPower 75 (T4)	028200M00	7100 (3227)	\$ 35,250
MP75*FLSK	mPower 75 w/ Loader	034450M00	8960 (4073)	\$ 43,063
MP75*FLSKB75F	mPower 75 w/ Loader & 75B Backhoe**	042950M00	10385 (4720)	\$ 53,688

\* Different tire options

\*\* Weight less backhoe bucket



## PARTS OPTIONS

Third Spool Kit	007601892D91	0901M00	\$ 1,290
Diagnostic Tool for Tier IV Engine	DEIGAR000001	0601M00	\$ 860
Grille Guard	KMW15902058	0214M00	\$ 310
Thumb Kit	ATI16610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

75L SK W/ SKC Quick Attach & Grille Guard	Uninstalled	06000M00	\$ 7,500
---	-------------	----------	----------

### LOADER ATTACHMENTS

78" Bucket	KMW13003147	0650M00	\$ 845
Quick Attach Adapter	KMW13043086	0495M00	\$ 645
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

### BACKHOE

85B Backhoe (Less bucket)	ATI85BF Uninstalled	07930M00	\$ 9,915
---------------------------	---------------------	----------	----------


### BACKHOE BUCKET OPTIONS

Bucket 12"	ATI110012	0649M00	\$ 815
Bucket 16"	ATI110016	0729M00	\$ 915
Bucket 18"	ATI110018	0759M00	\$ 950
Bucket 24"	ATI110024	0789M00	\$ 990
Bucket 36"	ATI110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# mPOWER™ 75P



## Engine

Type..... Turbocharged, Four Stroke,  
Common Rail, Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw).....74.4 (55.4)  
Compression Ratio..... 17.2:1  
Displacement cu-in {cc} ... 215.4 (3531.46)  
Rated Speed ..... 2300 rpm  
Low Idle RPM..... 2500 ± 50  
High Idle RPM..... 850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....61 (45.5)  
Rear PTO RPM at engine RPM  
..... 540 @ 2186

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

ROPS Cab w/ Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type..... Forward/Reverse synchro  
shuttle with full synchro mesh  
Number of Speeds..... 12F/12R  
Clutch.....Dual dry with ceremetallic lining  
Brakes.....Wet disc

## Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for wider steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output..... 11 gallons/min  
Category 2, 3 point hitch ..... Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves.....2 spool standard  
with detent type raise and lower with  
kickback and float position in front  
Lift capacity.....5100 lb. (2318 kg)

## Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Exterior & Rearview Mirrors  
4F/2R Work Lights  
HVAC  
Radio Ready  
Sun Visor  
Front Wiper & Fluid  
Entry Light  
Cup Holder  
Tool Tray  
Ashtray  
Cigarette Lighter  
Coat Hook  
12V Socket

## Dimensions

Overall Length ..... 166 in. (4216mm)  
Overall Width..... 81.4 in. (2067mm)  
Overall Height (to top of cab)  
..... 108.2 in. (2747mm)  
Wheelbase ..... 89.7 in. (2278 mm)  
Turning Radius..... 13.3 ft. (4 m)

## Tires & Wheels

Ag (Front/Rear)..... 11.2x24/ 16.9x30  
Industrial (Front/Rear)  
..... 12.5/80x18/19.5Lx24

## Capacities

Fuel Tank.....21.9 gal. (82.8 L)  
Cooling System ..... 10.3 qts. (9.7 L)  
Engine Oil..... 9.5 qts. (8.9 L)  
Transmission and Differential  
..... 41.2 qts. (38.9 L)  
Front Axle and Final Drive Case  
..... 7.2 qts. (6.8 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 55 A

## Operating Weight

7900 lb. (3591 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MP75C*	mPower 75P Cab (T4)	037000M00	7900 (3591)	\$ 46,250
MP75C*LSK	mPower 75P Cab w/ Loader	043250M00	9960 (4527)	\$ 54,063

\* Different tire options

\*\* Weight less backhoe bucket



# mPOWER™ 75P



## PARTS OPTIONS

Third Spool Kit	E007606659D91	02435M00	\$ 3,480
Diagnostic Tool for Tier IV Engine	DEIGAR000001	0601M00	\$ 860
Grille Guard	KMW15902058	0214M00	\$ 310
Rear Wiper Kit	E007518772D91	0209M00	\$ 300
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

75 PL SKC Quick Attach Bucket & Grille Guard	Uninstalled	06000M00	\$ 7,500
--	-------------	----------	----------

### LOADER ATTACHMENTS

78" Bucket	KMW13003147	0650M00	\$ 845
Quick Attach Adapter	KMW13043086	0495M00	\$ 645
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# mPOWER™ 85



## Engine

Type..... Turbocharged, Four Stroke,  
Common Rail, Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw).....83 (61.9)  
Compression Ratio..... 17.2:1  
Displacement cu-in (cc)....215.4 (3531.46)  
Rated Speed.....2300 rpm  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....70 (52.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2187, 1000 @ 2180

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Forward/Reverse synchro  
shuttle with full synchro mesh  
Number of Speeds.....12F/12R  
Clutch.....Dual dry with ceremetallic lining  
Brakes.....Wet disc

## Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for wider steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump output.....16.17 gallons/min  
Category 2, 3 point hitch.....Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves.....Standard 2 spool,  
3rd optional with detent in raise, lower  
and float position. Kickback in raise and  
lower.  
Lift capacity.....5500 lb. (2500 kg)

## Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box

## Dimensions

Overall Length.....162 in. (4116 mm)  
Overall Width.....77.3 in. (1963 mm)  
Overall Height (to top of cab)  
.....94.5 in. (2400 mm)  
Wheelbase.....85.8 in. (2179 mm)  
Turning Radius.....13.1 ft. (4 m)

## Tires & Wheels

Ag (Front/Rear).....12.4x24/16.9x30  
Industrial (Front/Rear)  
.....12.4/80x18/19.5Lx24

## Capacities

Fuel Tank.....19.28 gal. (73 L)  
Cooling System.....10.3 qts. (9.7 L)  
Engine Oil.....9.5 qts. (8.9 L)  
Transmission and Differential  
.....44.4 qts. (41.9 L)  
Front Axle and Final Drive Case  
.....7.2 qts. (6.8 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 55 A

## Operating Weight

7297 lb. (3317 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
85604*FT4	mPower 85 (T4)	030200M00	7297 (3317)	\$ 37,750
85604*FLSKT4	mPower 85 w/ Loader	036650M00	9157 (4162)	\$ 45,813
85604*FLSKB511FT4	mPower 85 w/ Loader & 85B Backhoe**	045150M00	10751 (4887)	\$ 56,438

\* Different tire options

\*\* Weight less backhoe bucket



## PARTS OPTIONS

Third Spool Kit	E007606659D91	02435M00	\$ 3,480
Diagnostic Tool for Tier IV Engine	DEIGAR000001	0601M00	\$ 860
Grille Guard	KMW15902058	0214M00	\$ 310
Thumb Kit	AT116610	0978M00	\$ 1,400
Block Heater Assembly	TISGE360	084M00	\$ 120
Third Function Diverter Valve Kit	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

86 L W/ SKC Quick Attach & Grille Guard	Uninstalled	06150M00	\$ 7,690
---	-------------	----------	----------

### LOADER ATTACHMENTS

84" Bucket	KMW13003148	0680M00	\$ 880
Quick Attach Adapter	KMW13043087	0535M00	\$ 695
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

### BACKHOE

85B Backhoe (Less bucket)	AT185BF Uninstalled	07930M00	\$ 9,915
---------------------------	---------------------	----------	----------

### BACKHOE BUCKET OPTIONS

Bucket 12"	AT1110012	0649M00	\$ 815
Bucket 16"	AT1110016	0729M00	\$ 915
Bucket 18"	AT1110018	0759M00	\$ 950
Bucket 24"	AT1110024	0789M00	\$ 990
Bucket 36"	AT1110036	0829M00	\$ 1,040

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# mPOWER™ 85P



## Engine

Type..... Turbocharged, Four Stroke,  
Common Rail, Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw).....83 (61.9)  
Compression Ratio..... 17.2:1  
Displacement cu-in (cc) ....215.4 (3531.46)  
Rated Speed .....2300 rpm  
Low Idle RPM.....2500 ± 50  
High Idle RPM.....850 ± 50

## Power Take Off

Type.....Independent  
PTO HP (kW).....70 (52.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2187, 1000 @ 2180

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

ROPS Cab w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Forward/Reverse synchro  
shuttle with full synchro mesh  
Number of Speeds.....12F/12R  
Clutch.....Dual dry with ceremetallic lining  
Brakes.....Wet disc

## Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for wider steering

## Hydraulic System

Type.....Open center, full-five hydraulic with  
position and draft controls  
Pump output.....16.17 gallons/min  
Category 2, 3 point hitch.....Telescopic  
stabilizers & flex links  
Rear Auxiliary Valves.....Standard 2 spool,  
3rd optional with detent in raise, lower  
and float position. Kickback in raise and  
lower  
Lift capacity.....5500 lb. (2500 kg)

## Operator Station

7 Pin Pocket  
Wide Platform Steps  
Color Coded Controls  
Tool Box  
Exterior & Rearview Mirrors  
4F/2R Work Lights  
HVAC  
Radio Ready  
Sun Visor  
Front Wiper & Fluid  
Entry Light  
Cup Holder  
Tool Tray  
Ashtray  
Cigarette Lighter  
Coat Hook  
12V Socket

## Dimensions

Overall Length.....165.9 in. (4216 mm)  
Overall Width.....81.4 in. (2068 mm)  
Overall Height (to top of cab)  
.....108.2 in. (2748 mm)  
Wheelbase.....89.7 in. (2278 mm)  
Turning Radius.....13.92 ft. (4.24 m)

## Tires & Wheels

Ag (Front/Rear).....12.4x24/18.4x30  
Industrial (Front/Rear)  
.....12.5/80x18/19.5Lx24

## Capacities

Fuel Tank.....21.7 gal. (82 L)  
Cooling System.....10.3 qts. (9.7 L)  
Engine Oil.....9.5 qts. (8.9 L)  
Transmission and Differential  
.....44.4 qts. (41.9 L)  
Front Axle and Final Drive Case  
.....7.2 qts. (6.8 L)

## Electrical

Battery.....12 Volt, 96 AH 925 CCA  
Alternator.....12 V 120 A

## Operating Weight

8177 lb. (3717 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
85604C*FT4	mPower 85P Cab (T4)	039000M00	8177 (3717)	\$ 48,750
85604C*FLSKT4	mPower 85P Cab w/ Loader	045450M00	10237 (4653)	\$ 56,813

\* Different tire options



# mPOWER™ 85P



## PARTS OPTIONS

Third Spool Kit	E007606659D91	02435M00	\$ 3,480
Diagnostic Tool for Tier IV Engine	DEIGAR000001	0601M00	\$ 860
Grille Guard	KMW15902058	0214M00	\$ 310
Block Heater Assembly	TISGE360	084M00	\$ 120
Rear Wiper Kit	E007518772D91	0209M00	\$ 300
Third Function Diverter	KMW15902089	01182M00	\$ 1,690

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

86 PL SKC Quick Attach Bucket & Grille Guard	Uninstalled	06150M00	\$ 7,690
--	-------------	----------	----------

### LOADER ATTACHMENTS

84" Material Bucket	KMW13003148	0680M00	\$ 880
Quick Attach Adapter	KMW13043084	0535M00	\$ 695
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# mFORCE™ 105S

## Engine

Type..... Turbocharged, Four Stroke,  
Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw).....105 (78.3)  
Compression Ratio..... 18.2:1  
Displacement cu-in (cc) ..... 268.6 (4400)  
Rated Speed .....2300 rpm  
Low Idle RPM.....2350  
High Idle Rpm ..... 750

## Power Take Off

Type.....Independent  
PTO HP (kW).....95.5 (70.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2220, 1000 @ 2227

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

Foldable ROPS w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Power Shuttle with synchromesh  
Number of Speeds..... 12F/12R  
Clutch.....Torsional Damper  
Brakes.....Hydraulic

## Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump Output..... 15.6 gallons/min  
Category 2, 3 Point Hitch  
..... Telescopic stabilizers & flex links  
Rear Auxillary Valves  
.....2 Spool Std. 3 optional  
Lift Capacity.....6860 lb. (3118 kg)

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box  
2 F/R Work Lights  
Front Wiper w/Fluid  
External/Rearview Mirrors  
Roof Vent  
Tool Tray  
Cup Holder  
Sun Visor  
Radio Included  
Dome Light  
Coat Hook  
2 12V Sockets  
HVAC

## Dimensions

Overall Length..... 162 in. (4110 mm)  
Overall Width.....84.3 in. (2141 mm)  
Overall Height (to top of cab)  
..... 107 in. (2718 mm)  
Wheelbase .....90.6 in. (2300 mm)  
Turning Radius..... 11.98 ft. (3.6 m)

## Tires & Wheels

Ag (Front/Rear)..... 13.6R 24/18.4R 34

## Capacities

Fuel Tank.....29 gal. (110 L)  
Cooling System..... 16.8 qts. (16 L)  
Engine Oil ..... 15.8 qts. (15 L)  
Transmission and Differential  
..... 79.5 qts. (75 L)  
Front Axle and Final Drive Case  
..... 18.6 qts. (17.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 85 A  
Starter Capacity..... 12 V, 2.7 KW

## Operating Weight

8666 lb. (3939 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MF1054CSA	mForce 105 S	050750M00	8666 (3939)	\$ 63,438
MF1054CSALSK	mForce 105 S Loader	057600M00	10633 (4833)	\$ 72,000



# mFORCE™ 105S

## PARTS OPTIONS

Third Spool Kit	19155158001	0747M00	\$ 1,070
Front Weight Bracket	17684104300GB	0229M00	\$ 330
Grille Guard	84901006000	0296M00	\$ 425
Third Function Aux. Val Kit	84906000000	0970M00	\$ 1,390
Block Heater (Cartridge Style)	L1009300015	084M00	\$ 120

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

105 L with SKC Quick Attach Bucket and Grille Guard	Uninstalled	06550M00	\$ 8,190
---	-------------	----------	----------

### LOADER ATTACHMENTS

87" Material Bucket	84904001000	01250M00	\$ 1,560
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.  
 Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).  
 Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.  
 Outgoing freight is not included in the above prices.



# mFORCE™ 105P

## Engine

Type..... Turbocharged, Four Stroke,  
Direct Injection Diesel  
No. of Cylinders.....4  
Engine HP (kw)..... 105 (78.3)  
Compression Ratio..... 17:01  
Displacement cu-in (cc) ..... 268.6 (4400)  
Rated Speed ..... 2300 rpm  
Low Idle RPM..... 2350  
High Idle RPM..... 750

## Power Take Off

Type.....Independent  
PTO HP (kW).....95.5 (70.2)  
Rear PTO RPM at engine RPM  
.....540 @ 2220, 750 @ 2208,  
1000 @ 2227

## Dash Instruments

Tachometer & Hour Meter  
Fuel Gauge  
Temperature Gauge  
Indicators for Warning Messages  
4WD Drive Lamp

## Safety Equipment

ROPS Cab w/Retractable Seat Belt  
Safety Start Switches  
Turn Signals/Hazard Light  
Mechanical Wet Disc Brakes  
Electric Key Shut off  
Parking Brake Indicator on Dash  
Water Temperature Gauge  
Horn

## Drive Train

Type.....Power Shuttle, Power Shift with  
synchromesh  
Number of Speeds  
..... 24F/24R + 8 Creepers  
Clutch.....Torsional Damper  
Brakes.....Hydraulic

## Front Axle

Power Steering  
Live Front Axle, Planetary Reduction  
Level Gears for Wider Steering

## Hydraulic System

Type.....Open center, full-live hydraulic with  
position and draft controls  
Pump Output..... 15.6 gallons/min  
Category 2, 3 Point Hitch..... Telescopic  
stabilizers & flex links  
Rear Auxillary Valves  
..... 3 Spool Std. 4 optional  
Lift Capacity.....6860 lb. (3118 kg)

## Operator Station

Wide Platform Steps  
Color Coded Controls  
Tool Box  
2 F/R Work Lights  
Front Wiper w/Fluid  
External/Rearview Mirrors  
Roof Vent  
Tool Tray  
Cup Holder  
Sun Visor  
Radio Included  
Dome Light  
Coat Hook  
2 12V Sockets  
HVAC

## Dimensions

Overall Length..... 162 in. (4110 mm)  
Overall Width.....84.3 in. (2141 mm)  
Overall Height (to top of cab)  
..... 107 in. (2718 mm)  
Wheelbase.....90.6 in. (2300 mm)  
Turning Radius..... 11.98 ft. (3.6 m)

## Tires & Wheels

Ag (Front/Rear)..... 13.6R 24/18.4R 34

## Capacities

Fuel Tank.....29 gal. (110 L)  
Cooling System..... 16.8 qts. (16 L)  
Engine Oil..... 15.8 qts. (15 L)  
Transmission and Differential  
..... 79.5 qts. (75 L)  
Front Axle and Final Drive Case  
..... 18.6 qts. (17.5 L)

## Electrical

Battery..... 12 Volt, 96 AH 925 CCA  
Alternator..... 12 V 85 A  
Starter Capacity..... 12 V, 2.7 KW

## Operating Weight

8666 lb. (3939 kg)

MATERIAL CODE	DESCRIPTION	REFERENCE NUMBER	SHIPPING WT lb. (kg)	MSRP
MF1054CPA	mForce 105 P	055300M00	8666 (3939)	\$ 69,125
MF1054CPALSK	mForce 105 P Loader	062150M00	10633 (4833)	\$ 77,688

## PARTS OPTIONS

Fourth Spool Kit	19025159301	0903M00	\$ 1,290
Front Weight Bucket	17684104300GB	0229M00	\$ 330
Grille Guard	84901006000	0296M00	\$ 425
Third Function Aux. Val Kit	84906000000	0970M00	\$ 1,390
Block Heater (Cartridge Style)	L1009300015	084M00	\$ 120

Available through Parts Department 1-800-561-9265

## WHOLEGOODS OPTIONS

### LOADER

105 L SKC Quick Attach Bucket and Grille Guard	Uninstalled	06550M00	\$ 8,190
--	-------------	----------	----------

### LOADER ATTACHMENTS

87" Material Bucket	84901001000	01250M00	\$ 1,560
Grapple Fork	KMW13031030	01765M00	\$ 2,210
78" Grapple Bucket	KMW13003634	01340M00	\$ 1,680

Note: For installed TLB units shipped from Mahindra facilities, including Houston-Satsuma, please plan on a 4/5 week lead time.

Note: All installed Backhoe prices include \$220 for incoming freight + assembly charges (\$350 for 2500 series).

Note: All Backhoe prices are ex MUSA Works (incl. Houston-Satsuma). Remember to add price of bucket as per size requirement.

Outgoing freight is not included in the above prices.